GGG-F-601C
AMENDMENT 1
March 24, 1976

FEDERAL SPECIFICATION

FORK; HAY, MANURE, MILL AND SPADING; HAND

This amendment, which forms part of Federal Specification GGG-F-601C, dated May 15, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, Washington, DC 20406 for use by all Federal agencies.

PAGE 1

Paragraph 1.2.1: Under Type IV - Spading, delete Styles 1 and 2

Paragraph 1.2.2: Under Type IV, delete "Bent long handles."

PAGE 2

Paragraph 3.1.1: Change from "grade XX" to "grade B." Add the following: "Moisture content of finished handles shall be not less than 10% and not greater than 15%."

Paragraph 3.3.3: Delete the first sentence and substitute "The fork shank shall be forced into the handle." Delete the last sentence and substitute "Forks with tubular pattern ferrules (see 3.3.2) may be furnished with or without rivets."

PAGE 3

Paragraph 3.3.4: Delete sentence 5 and substitute "The tines of spading forks shall be rectangular in cross section with dimensions equal to those listed in Table IV."

Paragraph 3.4.1: Delete sentences 3, 4 and 5 and substitute "The tines of Type IV spading forks shall be polished, shot peened or otherwise provided with a smooth, scale free surface. The metal parts of the fork, including tines, tine bridge and ferrule, shall have a neatly applied coating of pigmented paint, lacquer or enamel. Polished tines shall have a coating of clear lacquer or a grease or oil compound suitable for prevention of rust in storage without adversely affecting the material coated."

FSC 3750

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

Paragraph 3.4.2: Change first sentence from "-- varnish, or lacquer." to "-- varnish, lacquer or lacquer wax."

Paragraph 3.6: Change permanent set from "1/8 inch" to "3/16 inch."

PAGE 4

Table II: Change tolerance on D-handle length from "± 1/2" to "± 1-1/2" and change the D-handle length from "32" to "31."

PAGE 5

Table III: Change tolerance for handle length from "± 1/2" to "± 1-1/2" and change handle length from "30" to "31."

Table IV: Delete the table and substitute the following:

TABLE IV - Type IV, Spading Forks

Class	Fork head				Handle	
	Tines			Overall width of head ± 5/8 inch	Length ± 1-1/2 inch	Diameter ± 1/16 inch
	Thickness minimum	Width minimum	Length ± 1/2 inch			
	Inches	Inches	Inches	Inches	Inches	Inches
Class A - four tines	7/16	1/4	11-1/2	7-1/2	31	1-1/2

Note: Tine thickness and width measured at midpoint of tines between tine points and back of tine bridge. Tine length measured in a straight line from tine point to front of tine bridge. Overall width of head measured across fork midway between tine points and tine bridge. Handle length measured in a straight line from back of tine bridge to free end of handle. Handle diameter measured 12 inches from back of tine bridge.

PAGE 6

Paragraph 4.4.1: Change test load for spading forks from "250 pounds" to "175 pounds."

Paragraph 4.4.1.1: Change the last two words in the first sentence from "fork end" to "tine bridge."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.