FEDERAL SPECIFICATION

LATHE, BRAKE DRUM

This amendment, which forms a part of Federal Specification OO-L-90B, dated August 4, 1969, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 5

3.4, last line: Insert "and when specified, brake and drum disks" between "drums" and "within."

3.4.1, add:

(h) disk diameter - 15 inches.
(i) number of feeds for disk attachment - 2.
(j) Feed range for disk attachment - 0.002 - 0.010 inch per revolution.

PAGE 6

3.4.4 Delete and substitute:

"3.3.4 Performance accuracy for brake discs. When the requirement for truing brake discs is specified in 3.2, the lathe shall be capable of truing both friction surfaces of brake discs simultaneously with the tolerances specified below:

(a) Each finish trued surface of the brake disc shall not deviate from the brake disc true plane in excess of ± 0.002 inch.

(b) Each finish trued surface of the brake disc shall be parallel to its opposite counterpart surface with a total tolerance not to exceed 0.004 inch.

Source: https://assist.dla.mil -- Downloaded: 2025-07-26T19:50Z
Check the source to verify that this is the current version before use.

(c) The final trued surface finish of the brake disc shall not have a finish numerically greater than 60 microinches a. a.

Note: Brake disc true plane - the true plane of the brake disc is a plane, perpendicular to the axis of the functional bearing cup surfaces."

PAGE 7

3.5.3 Delete and substitute:

"3.5.3 Spindles and arbors. Spindles and arbors shall be high-grade alloy steel, properly heat treated and ground on all aligning surfaces. Spindles and arbors shall be of a size to insure the accuracy required of this type of lathe and so mounted as to permit turning brake drums and brake discs of the size specified. The arbors shall be mounted in the spindle by means of a suitable taper with a positive lock and release system which will prevent damage to spindle or arbor. The length of the arbors shall be adequate to mount brake drums and brake discs of all vehicles within the sizes specified."

PAGE 9

3.9 Delete and substitute:

"3.9 Identification marking. The brake drum lathe shall be marked for identification in accordance with MIL-STD-130 and unless otherwise specified (see 6.2), shall include the Federal Stock Number."

MILITARY INTERESTS:

Custodians:
Army - WC
Navy - YD
Air Force - 82

Civil Agency Coordinating Activity:
GSA-FSS

Review activities:
Army - None
Navy - None
Air Force - 82

Preparing activity:
Army - WC

User activities:
Army - AT
Navy - MC
Air Force - None

Project No. 4910-0465

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.