S-T-540E
AMENDMENT-2
June 28, 1977
SUPERSEDING
Int. Amendment-1 (Army-GL)
January 11, 1977

FEDERAL SPECIFICATION

TOASTERS, CONTINUOUS (CONVEYOR, HEAVY DUTY);

ALL ELECTRIC AND COMBINATION GAS AND ELECTRIC

This amendment, which forms part of Federal Specification S-T-540E, dated January 22, 1976, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

2.2, under "American National Standards Institute (ANSI)", add the following in proper sequence:

"Z 21.41 - Quick-Disconnect Devices for Use with Gas Fuel"

"Z 21.45 - Flexible Connectors of Other Than All-Metal Construction for Gas Appliances."

PAGE 4

2.2 (cont'd), line 10: Delete "Tariff Order Section" and substitute "Traffic Department".

PAGE 5

3.2.1.2, line 3: Delete "or" and substitute "and".

PAGE 8

3.4.4 and 3.4.4.1 Delete them in their entirety and substitute the following:

"3.4.4 Fuel System. The fuel system including burners shall be designed to efficiently burn natural or liquefied petroleum gas (LPG) with appropriate conversion."

"3.4.4.1 Natural Gas. The unit shall be furnished to operate on natural gas. Main burners shall be provided with fixed orifices with orifice hoods or spuds that can be interchanged. The orifice hoods or spuds installed for natural gas shall be unpainted brass. An automatic pilot including a 100 percent shutoff shall be provided on each unit."

"3.4.4.2 LPG. The contractor shall furnish black color-coded orifice hoods or spuds to convert the unit to operate on LPG. The contractor shall also furnish complete instructions for conversions to operate on LPG."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

PAGE 8 (con.)

"3.4.4.3 Accessories. A pressure regulator for natural gas shall be furnished with each unit. The unit shall be furnished with a connector conforming to Z21.45 and a quick disconnect conforming to Z21.41. The connector length shall be 60 inches."

"3.4.4.4 Automatic ignition. Type II toasters main burners shall be equipped with means for automatic ignition of gas. A pilot, including a 100 percent shut-off device shall be provided for each toaster burner. The pilot shall automatically shut off the gas to all toaster burners including the toaster pilot burners, in the event means of ignition becomes inoperative (see 4.4.1)."

3.4.5, line 4: Delete "2 5/8" and substitute "4".

3.7, line 4: Delete "photosensitive" and substitute "by photosensitive means".

PAGE 13

4.2.1, line 2: Delete "and tested".

PAGE 14

Table I (cont'd): Delete "13th and 14th defects" in their entirety.

PAGE 16

4.4.1, line 4: Delete "3.4.4.1" and substitute "3.4.4.4".

PAGE 19

6.2, subparagraphs "(h)" and "(i)", delete in their entirety.

Military Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD

User activities:

Army - CE
Navy - MC, SA

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS
VA - DMS

Project No. 7310-0582

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.