W-S-890b
INT. AMENDMENT - 2 (GSA-FSS)
July 29, 1968
SUPERSEDING
Int. Amendment - 1 (GSA-FSS)
May 31, 1968

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

SWITCH, SNAP, MISCELLANEOUS

This interim amendment was developed by General Services Administration, Federal Supply Service, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification W-S-890b, dated December 31, 1963,

PAGE 1

Paragraph 1.2.1, under Type II, delete: "Kind C - Ceiling mounting
Kind W - Wall mounting."

Paragraph 2.1 Federal Specification: PPP-B-566, Boxes, Folding, Paperboard; PPP-B-665, Boxes, Paperboard, Metal Stayed (Including Stay Material); PPP-B-676, Boxes, Setup. Delete "Federal Standard No. 102 - Preservation, Packaging and Packing Levels." Add to Military Specifications "MIL-P-116 - Preservation, Methods of."

PAGE 3

Section 5: Delete the section and substitute the following:

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each switch shall be packaged in conformance to submethod IC-2 of MIL-P-116.

5.1.2 Level B. Each switch shall be packaged in a snug-fitting paperboard box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be secured to prevent accidental opening.

5.1.3 Level C. Each switch shall be packaged to afford adequate protection against deterioration and damage during shipment from the supplier to the initial destination.

5.1.4 Intermediate packaging.

5.1.4.1 Types I, II, and IV. Ten unit packages of one stock number of switches shall be intermediate packaged in snug-fitting paperboard or fiberboard box conforming to PPP-B-566, PPP-B-665, PPP-B-676, or PPP-B-636, class domestic. Box shall be secured to prevent accidental opening.

5.1.4.2 Type III. Twenty-five unit packages of one stock number shall be packaged in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic, grade 200. Closure shall be in accordance with the appendix to PPP-B-636.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

5 5.2.1 Level A. Switches in quantities as specified (see 6.2), of a single stock number shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class weather-resistant, grade V3c. Closure shall be in accordance with paragraph 30.3.2 of the appendix to PPP-B--636.

5.2.2 Level B. For small quantity shipments the intermediate container may be used for the shipping container. For shipments of 200 or more switches, eight intermediate packages of type III switches or ten intermediate packages of type I, II, and IV switches (200 switches) of one stock number shall be packed in a fiberboard box conforming to PPP-B-636, class domestic, grade 275. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The switches, packaged as specified in 5.1 shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the Uniform Freight Classification Rules of National Motor Freight Classification Rules as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required in the contract or order, shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special marking required in the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.