INCH-POUND

MIL-C-48155 (AR)
AMENDMENT 2
25 OCTOBER 1990
SUPERSEDING
AMENDMENT 1
22 April 1975

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, XM299
PARTS FOR

This Amendment forms a part of Military Specification MIL-C-48155 (PA), dated 1 September 1974 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, Specifications and Standards: Add new listing as follows:

"MIL-STD-810 - Environmental Test Methods."

PAGE 2

* 3.2.1, Add new paragraph which reads as follows:

"3.2.1 Corrosion resistance (salt spray). Parts selected for the salt spray test shall show no evidence of pitting or mottling when tested in accordance with 4.5.2."

PAGE 6

4.4.2.3 Body
Major Category:

Major B149: Substitute "Min" for "Max"

Major B151: Delete in its entirety.

Major B152 and B153: Change number "152" to "151" and "153" to "152"

Minor category:
Minor 201: Delete in its entirety.

Minor 202 thru 206: Change "202" to "201", "203" to "202", "204" to "203", "205" to "204", and "206" to "205"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

PAGE 7

* 4.4.2.3, Major 153: Delete in its entirety and substitute the following:

"153 Salt spray test...0.065%...3.2.1...Visual/4.5.2"

PAGE 9

4.4.2.5 Head:
Major Category:
Major 141: Delete in its entirety and substitute the following:

"141 Diameter of external thread undercut...0.40%...3.2... Gage"

Major 142: Delete in its entirety and substitute the following:

"142 Large internal diameter...0.40%...3.2...Gage"

Major B144: Add new CD which reads as follows:

"144 True position of large internal diameter to external thread...0.40%...3.2...Gage"

Major B145: Add new CD which reads as follows:

"145 True position of small internal diameter to external thread...0.40%...3.2...Gage"

Major B146: Add new CD which reads as follows:

"146 True position of internal thread to external thread ...0.40%...3.2...Gage"

Minor Category:

Minor 204: Delete in its entirety and substitute the following:

"204 Length from small outside diameter to shoulder of large outside diameter...0.65%...3.2...Gage"

Minor 205: delete in its entirety.

Minor 206 thru 211: Change "206" to "205", "207" to "206", "208" to "207", "209" to "208", "210" to "209", and "211" to "210"

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the currentversion before use.

PAGE 11

* 4.4.2.6, Major 137: Delete in its entirety and substitute the following:

"137 Salt spray test...0.065%...3.2.1...Visual/4.5.2"

Minor 202: Delete in its entirety.

Minor 203: Change "203" to "202"

PAGE 12

4.4.2.7, Major B136: Add new CD which reads as follows:

"136 Evidence of protective finish...0.40%...3.2...Gage"

PAGE 15

* 4.5.2: Add new paragraph which reads:

"4.5.2 Salt spray test. Samples selected for this test shall be tested using equipment and procedures in accordance with MIL-STD-810, Method 509.2, Salt Fog. Parts shall be tested with the black powder pellet end up and the pellet cavity inclined approximately six degrees from the vertical in fixturing which does not obstruct the longitudinal flash hole. Parts shall be tested for 336 hours minimum. After testing parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish, especially on all black powder pellet contact surfaces (rear face of flash tube or cavity in body). The body (dwg. 9293428) prior to rinsing shall be transversely sectioned approximately 0.25 inch from the front face in order to facilitate visual inspection of the cavity. The cutting tool must not remove any part of the black powder pellet cavity. One or more pits or mottling shall be cause for rejection of all anodized parts represented by the sample. After three (3) consecutive lots have been accepted the sampling may be reduced to an AQL of 0.25%, inspection level S-4."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A996)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.