MIL-I-51192B(EA)
12 September 1979
SUPERSEDING
MIL-I-51192(MU)
6 April 1967

MILITARY SPECIFICATION

INSTALLATION KIT, ARMORED VEHICLE

GAS-PARTICULATE FILTER UNIT, M29Al

This specification is approved for use by US Army Armament Research and Developent Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of filter unit installation kit.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-621 - Boxes, Wood, Nailed and Lock-Comer.
PPP-B-636 - Boxes, Shipping, Fiberboard. -
PPP-T-60 - Tape, Packaging, Waterproof
PPP-T-76 - Tape, Packaging, Paper (For Carton Sealing).

FSC 4240

: Beneficial commemts (recommendations, additions, deletions) and any : pertinent data which may be of use in improving this document should be : addressed to: Commander, US Army Armament Research and Development . Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Groud, MD 21010 by us- : ing the self-addressed Standardization Document Improvement Proposal : (DD Form 1426) appearing at the end of this document or by letter. :

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation-Packaging, Methods of.
MIL-B-117 - Bags, Sleeves and Tubing - Interior Packaging.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-B-46506 - Boxes, Ammunition Packing, Wood, Wirebound,

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

TDPL5-19-3052 - Installation Kit, Armored Vehicle, Gas-Particulate Filter Unit, M29Al.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components,

3.1.1 Materials. All materials cited on TDPL5-19-3052 or on the subsidiary drawings shall conform to the specifications listed thereon, Or . to the-specified characteristics set forth on the drawings.

3.1.2 Comments. All components of the installation kit shall conform to the specifications and drawings listed on TDPL5-19-3052 and subsidiary drawings.

3.2 Manufacture and assembly. All components of the installation kit shall be manufactured and assembled in accordance with their respective assembly drawings listed on TDPL5-19-3052. Electrical components shall function properly and have electrical continuity, as applicable, when tested as specified in 4.2.4.1.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:52Z
Check the source to verify that this is the current version before use.

3.3 Workmanship. All metal parts of the installation kit shall be free from burrs and sharp edges and defects such as bent, broken, or cracked members. All parts shall be free from foreign matter such as dirt, grease, oil, or viscous material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection,

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perfom any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the installation kits produced by one manufacturer, at one plant, from the same materialist under essentially the same manufacturing conditions.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection Procedure.

4.2.3.1 Examination. Sample installation kits shall be examined in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:52Z
Check the source to verify that this is the current version before use.

4.2.3.2 Classification of defects.

(a) Installation kit. armored vehicle. gas-particulate filter unit, M29A1. (TDPL5-19-3052). --

Categories	Defects	Acceptance standards
Critical:	None defined l	
Major:	AQL 0.65 percent defective	
101	Switch or circuit breaker nonfunctioning	4.2,4.1
	AQL 1.0 percent defective	
102	Component missing or incorrect	
103	Component incorrectly assembled	
104	Hardware component inoperative	
105	Welding not as specified	
106	Mounting holes for component assemblies not as specified	
107	Workmanship (3.3)	
Minor :	AQL 2.5 percent defective	
201	Protective finish missing	
202	Marking incorrect, missing, or illegible	

4.2.4 Test.

4.2.4.1 Electrical continuity and circuit breaker/switch functioning test. The electrical continuity of the cables and functioning of the circuit breaker and switch shall be determined using a test lamp.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:52Z
Check the source to verify that this is the current version before use.

5, PACKAGING

5.1 Preservation (levels A and commercial).

5.1.1 Level A.

5.101.1 Cleaning and drying. The components of the installation kit shall be cleaned in accordance with cleaning process C-1 of MIL-P-116. Drying shall be accomplished using any process of MIL-P-116, providing the selected process is not harmful to the item.

5.1.1.2 Unit packing.

5.1.1.2.1 Preparation for unit pack. The components of the kit shall be prepared for placement in the unit pack using the methods and procedures of MIL-P-116 as follows:

(1) Frame assembly. Package the frame assembly in accordance with method III, Secure the mounting bracket to the frame with tape or twine.

(2) Adapters [5-19-1676-1 (3 es). 5-19-1676-2 (4 es)]. Package each adapter in accordance with method III by wrapping in MIL-B-121 barrier material, type II, grade A, class 1, size 8 inches by 8 inches and securing with PPP-T-76 tapes size 2 inches by b inches.

(3) Brackets [5-19-1831 (4 es)]. Package the brackets in accordance with method 111 by wrapping each bracket in MIL-B-121 barrier material, type II, grade A, class 1, size 6 inches by 6 inches, and securing with PPP-T-60 tape; size 2 inches by 4 inches.

(4) Retaining ring [MS 16624 - 4037 (4 es)]. package the retaining rings in accordance with method IC-1 by applying type P-7 preservative oil to all surfaces of each item, and placing each in a MIL-B-117 bag, type I, class C, style 1, size 2-1/2 inches by 3 inches. Close each bag by heat sealing.

(5) Connector orifice assembly [5-19-1829 (4 ea)} Package the connector in accordance with method IA-8 by wrapping each connector in MIL-B-121 barrier material, type II, grade A, class 1, size 6 inches by 6 inches and securing with PPP-T-60 tape, size 2 inches by 4 inches, Place the four wrapped items in a MIL-B-117 bag, type I, style 1, class E, size 8 inches by 8 inches. Close the bag by heat sealing.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:52Z
Check the source to verify that this is the current version before use.

(6) Toggle switch (Ms 39061-1) and circuit breaker (M13516/1-1). Package both items in accordance with method IA-8. Wrap each item in barrier material. conforming to type II, grade A, class 1 of MIL-B-121, size 6 inches by 6 inches, then place each in a MIL-B-117 bag, type I, style 1, class E, size 4 inches by 6 inches. Close each bag by heat sealing

5,1.1.2.2 Unit pack. The unit pack shall be assembled as follows: Place the frame assembly (5.1.1,2.1) in a PPP-B-636 fiberboard box, style RSC, grade W5C, size 13-3/8 inches by 6-1/2 inches by 8-1./4 inches inside dimensions, Place the remaining components [5.1.l.2.1(2) thru (6)] in a PPP-B-636 fiberboard box, style RSC, grade W6c, size 7-1/2 inches by 5-1/4 inches by 5-1/2 inches and place it inside the frame assembly. Close both boxes in accordance with PPP-B-636, appendix.

5.1.2 Commercial. The kit shall be packaged in accordance with MIL-STD-1188.

5.2 Packing (levels A. B and commercial).

5.2.1 Level A. A quantity of kits, not to exceed 10 per box, shall be packed in PPP-B-621 or MIL-B-46506 boxes for overseas shipment. Boxes shall meet size and weight limitations of their respective specifications and shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.2.2 Level B. A quantity of kits, not to exceed 10 per box, shall be packed in a PPP-B-636 fiberboard box, style RSC, grade V3C. Boxes shall meet size and weight limitations of specifications PPP-B-636 and shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.2.3 Commercial, Commercial packing shall be *in* accordance with MIL-STD-1188.

5.3 Marking (levels A, B and commercial).

5.3.1 Levels A and B. Each separately wrapped item (5.1.1.2) shall be identified by part number and item nomenclature. When more than one item is placed in a wrap or bag, the quantity shall be included in the marking, In addition to any special. markings required by the contract or order, unit packages, intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129,

5.3.2 Commercial, Commercial marking shall be in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:52Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This specification covers one type of installation kit designed to facilitate installation of M13A1 filter unit in applicable armored vehicles.

6.2 Ordering data. Procurement-documents should specify the following:

(a) Title, number and date of this specification.
(b) Level of packaging and packing required,

Custodian:

Army-EA

Preparing activity:

Army-EA

project No. 4240-A532

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:52Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-I-5-11/92 D

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DOD-314

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament Research
and Development Command
ATTN: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:52Z
Check the source to verify that this is the currentversion before use.