MIL-D-51453A(EA)
16 January 1986
SUPERSEDING
MIL-D-51453(EA)
21 May 1979

MILITARY SPECIFICATION

DISPERSER, RIOT CONTROL AGENT, PORTABLE, 3 GALLON, M33A1

This specification is approved for use within U.S. Army Chemical Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of disperser.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-26 - Bag, Plastic, (General Purpose).
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-C-1120 - Cushioning Material, Uncompressed Bound Fiber, for Packaging.
PPP-F-320 - Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.
PPP-p-291 - Paperboard, Wrapping and Cushioning.
PPP-T-76 - Tape, Packaging, Paper (For Carton Sealing).

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, U.S. Army Chemical Research and Development Center, ATTN: SMCCR-SPD-TS, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-117 - Bags, Sleeves and Tubing - Interior Packaging.
MIL-B-2427 - Box, Ammunition Packing; Wood, Nailed.
MIL-c-5501/7 - Caps and Plugs, Protective, Dust and Moisture Seal (Cap-Plug, General Purpose).

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized and Containerized Unit Loads 40 Inch Pallets, Skids, Runners or Pallet Type Base.
MIL-STD-1168 - Ammunition Lot Numbering.

2.1.2 Other Government documents and drawings. The following other Government documents and drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

U.S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH AND DEVELOPMENT CENTER

TDPL 116-3-121 - Disperser, Riot Control Agent, Portable, 3 Gallon, M33A1 .

(Copies of specifications, standards, drawings and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on TDPL 116-3-121 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the disperser shall conform to the specifications and drawings listed on TDPL 116-3-121 and on subsidiary drawings.

3.2 Assembly. The disperser shall be assembled as shown on Drawing 116-3-121.

3.3 Functioning. When the high pressure cylinder is charged to 2100± 100 pounds per square inch gage (psig), the regulator shall deliver air at 180 ±20 psig, the gun shall function freely, and the assembly shall not leak when tested in accordance with 4.4.4.1.

3.4 Container (Drawing 116-3-101).

3.4.1 Leakage and deformation. The container shall not leak or be permanently deformed when subjected to a minimum hydrostatic pressure of 350 psig for 1 minute when tested in accordance with 4.4.4.2.

3.4.2 Rupture. The container shall not rupture prior to sustaining a minimum hydrostatic pressure of 800 psig when tested in accordance with 4.4.4.3.

3.5 Gun. The gun shall function freely and not leak for a minimum period of 30 seconds when subjected to a minimum hydrostatic or air pressure of 200 psig when tested in accordance with 4.4.4.4.

3.6 Container assembly. The container assembly shall not leak at a minimum air pressure of 200 psig when tested in accordance with 4.4.4.5.

3.7 Harness.

3.7.1 Stitching. All stitching, except barracking, shall be stitch type 301 or 401 of FED-STD-751, 8 to 10 stitches per inch.

3.7.1.1 Type 301 stitching. Ends of all stitching shall be backstitched 1 inch minimum (1/2 inch on box X and W-W stitching), except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose or tight stitching, and the lock shall be embedded in the materials sewn.

3.7.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

(a) When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of one inch (1/2 inch for box X and W-W stitching) back of the end of the stitching.1/

(b) Thread breaks, or two or more consecutive skipped stitches or run-offs, noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of one inch in back of the defective area (1/2 inch on box X and W-W stitching), continue over the defective area and continue a minimum of one inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner.1/

1/When making the above repairs the ends of the stitching are not required to be backstitched.

3.7.1.2 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.7.1.1(a) and 3.7.1.1.1(b) except substitute 3/4 inch for one inch wherever one inch appears.

3.7.1.3 Automatic stitching. Automatic machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping, or back stitches are used to secure the ends of the stitching

3.7.1.4 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing.

3.7.1.5 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.7.2 Location marks. Location and notice marks shall not be drilled.

3.7.3 Snap fasteners and rivets. The lengths of the rivets and fasteners shall be determined by the contractor and shall effect a secure clinch of the assembled components.

3.7.3.1 Setting. The hole shall be punched before inserting the fastener or rivet and shall be smaller than the outside diameter of the fastener barrel or rivet so that it must be forced through the hole. The fastener or rivet shall be securely clinched without cutting the surrounding material. When installed, the clinched end shall have a uniform roll that will effect a secure hold. All burrs shall be removed from the rivet.

3.7.4 Repairs. Repairs such as mends, darns, patches or splices are not permitted *on* the harness.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

3.8 Frame and frame assembly riveting. Final sizing of rivet holes shall be done at assembly to preclude misalignment of mating holes at time of assembly. Punching of rivet holes in tubular components shall not be permitted. Mating surfaces of riveted components shall be drawn tight with the rivet head in contact with its mating surface. The set rivets shall be free of splits, burrs, and sharp edges.

3.9 Preproduction. Prior to the start of regular production, a preproduction sample of dispersers and components shall be produced for examination and tests in accordance with this specification.

3.10 Workmanship. The disperser and components shall be free from damage, cracks, splits, tears, burrs, sharp edges, sharp corners and foreign matter such as dirt, grease or oil that could impair their intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Lot. "A preproduction sample of five assembled dispersers, 38 containers and five guns shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection procedure.

4.3.2.1 For nondestructive tests. The assembled dispersers shall be tested in accordance with 4.4.4,1. The containers shall be tested in accordance with 4.4.4.2. The guns shall be tested in accordance with 4.4.4.4.

4.3.2.2 For destructive tests. Twenty-two containers shall be tested in accordance with 4.4.4.3. If one container fails the test, the remaining sixteen containers shall be tested in accordance with 4.4.4.3.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with 4.3.2.1 and 4.3.2.2 to be acceptable except for the containers. If two or more containers fail the test the entire sample of containers shall be destroyed. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot of dispersers shall be identified and controlled in accordance with MIL-STD-1168, produced by one manufacturer from the same materials and under essentially the same manufacturing conditions. However, for rupture test, a lot shall consist of 200 consecutively manufactured containers of one interfix number.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.1.2.2 For destructive test. One container shall be taken at random from each lot.

4.4.3 Inspection procedures.

4.4.3.1 For examination and nondestructive test. The disperser and the level A packaging shall be examined in accordance with the classification of defects and with MIL-STD-105. Each assembled disperser shall be tested in accordance with 4.4.4.1. Each gun shall be tested in accordance with 4.4.4.4. All defective items shall be removed from the lot.

4.4.3.2 For destructive test. Each sample container shall be tested in accordance with 4.4.4.3. A failure of any one sample to meet the specified pressure shall be cause to reject the entire lot from which the sample was drawn.

4.4.3.3 Critical defects. Each cylinder and each container in the lot shall be inspected for its critical characteristics listed in the classification of defects. Any cylinder or container failing to meet the specified test requirements shall cause the lot to be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

4.4.3.4 Classification of def'ects.

(a) Cylinder, compressed gas (Drawing 116-3-64, 116-3-240).

Categories	Defects
Critical:	
1	Torque incorrect
2	DOT markings missing or incorrect
Major:	AQL 1.0 percent defective
101	Finish missing or incorrect

(b) Container assembly (Drawing 116-3-74).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Leakage	4.4.4.5

(c) Frame assembly (Drawing 116-3-131).

Categories	Defects
Critical:	None defined
MaJor:	AQL 1.0 percent defective
101	Component missing, incorrect or incorrectly assembled
102	Dimension (2.88) incorrect
103	Dimension (6.88) incorrect
104	Dimension (2.25) incorrect
105	Dimension (3.00) incorrect
1.06	Dimension (13.12) incorrect
107	Angle (30° ± 5°) incorrect
1.08	Clamping, incorrect (use an empty agent tank and an unpressurized air cylinder to check for proper operation and snug fit)
109	Nameplate missing or incorrectly marked
110	Protective finish missing or incorrect
111	Poor workmanship (3.10)

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

(d) Frame and harness assembly (Drawing 116-3-130).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Type of stitching incorrect
102	Number of stitches per inch incorrect
103	Type of thread incorrect
104	Webbing cut, torn, exhibits holes," frayed or scalloped edges
105	Webbing not firmly, or tightly woven
106	Rivets missing, burred, loose or not clinched as specified
107	Fasteners clinched too tight, loose or not functioning " properly to provide a secure closure or open too freely
108	Fastener style or type incorrect
109	Bartacks stitching omitted, loose, incomplete, broken, or number of stiches not as specified
110	Poor workmanship (3.10)
Minor:	AQL 4.0 percent defective
201	Ends of webbing not fused, nor fused smooth and even
202	Cord cut, ends not fused, nor fused smooth and even
203	Material puckering
204	Stitches not secured as specified
205	Thread ends not trimmed throughout
206	Threads too loose, open, tight, skipped, or not continuous
207	Strap not turned under and sewn as specified

(e) Jet spray unit (Drawing 116-3-96).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective "
101	Tip internal diameter incorrect
102	Outside diameter incorrect
103	Component missing or incorrectly assembled
104	Finish missing or incorrect
Minor:	AQL 4.0 percent defective
201	Counterbore incorrect
202	Length of spray tip incorrect

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T21:01Z
Check the source to verify that this is the currentversion before use.

(f) Orifice (Drawing 116-3-107).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	O.D. incorrect
102	I.D. incorrect
103	Length incorrect
104	Spherical radius missing

(g) Agitator (Drawing 116-3-106)*

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Torque incorrect
102	Component missing or incorrectly assembled
103	Overall length of tube incorrect
104	Orifice extends past connector nut
105	1/8 inch pipe thread incorrect

h) Check valve assembly (Drawing 116-3-72 and 116-3-73).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Thread incorrect (pipe)
102	Component missing or incorrectly assembled
103	Finish missing or incorrect

(i) MultiJet spray unit liquid agent (Drawing 116-3-95).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Orifice tip internal diameter incorrect
102	Outside diameter of orifice tip flange incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

103	Outside diameter or orifice tip incorrect
104.	Component missing or incorrectly assembled
105	Machine finish or internal diameter incorrect

Minor: AQL 4.0 percent defective

201	Counterbore diameter, or depth incorrect
202	Overall length of orifice tip incorrect

(j) Container (Drawing 116-3-101).

Categories	Defects	Acceptance Standards
Critical:		
1	Leakage and deformation	4.4.4.2
Major:	AQL 1.0 percent defective	
101	Protective finish missing or incorrect	

(k) Pressure hose (Drawing 11.6-3-70).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Components incorrectly assembled
102	Overall length incorrect
103	End fittings not as specified
104	Date of manufacture missing
105	Service life tag missing or incorrectly dated
106	Workmanship (3.10)
Minor:	AQL 4.0 percent defective
201	Finish missing or incorrect (applies to steel fittings or fitting components only)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

(l) Discharge hose (Drawing 116-3-61).

Categories		Defects
Critical:		None defined
Major:	AQL	1.0 percent defective
101		Components incorrectly assembled
102		Hose assembly length incorrect
103		End fittings not as specified
104		Date of manufacture missing
105		Service life tag missing or incorrectly dated
106		Quick disconnect couplings class or end style incorrect
107		Workmanship (3.10)
Minor:	AQL	4.0 percent defective
201		Finish on end fittings missing or incorrect (applies to steel fittings only)
202		Finish on coupling missing *or* incorrect

(m) Packaging (section 5).

Categories		Defects
Critical:		None defined
Major:	AQL	4.0 percent defective
101		Components or repair parts missing
102		Components and repair parts not cleaned and dried as specified
103		Preservation missing
104		Packaging method incorrect
105		Container incorrect
106		Containers closure incorrect.
107		Container or package damaged
108		Marking missing *or* incorrect
109		Strapping loose or missing

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Functioning. Connect a test gage between the low pressure pneumatic hose and the quick-disconnect at the regulator outlet. Charge the high pressure cylinder to 2100 + 100 psig air, and connect it to the disperser. slowly open the high pressure valve. Record the regulator outlet pressure when needle has stabilized. Using a suitable leak-detecting solution, check all joints for

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T21:01Z
Check the source to verify that this is the currentversion before use.

leakage. Discharge the disperser in 5-second bursts, Pausing 5 seconds between bursts to check the gun for leakage. During periods of air flow, listen for a "rattling" sound, indicating presence of agitator (see 6.2).

4.4.4.2 Leakage and deformation. The container shall be subjected to the specified hydrostatic pressure for the indicated time (see 6.2).

4.4.4.3 Rupture. The container shall be subjected to hydrostatic pressure until the container leaks or ruptures. Record the leak or rupture pressure.

4.4.4.4 Gun. The gun shall be connected to a regulated source of air or hydrostatic pressure. Gradually increase the pressure to 200 psig minimum. Maintain that pressure for a minimum period of 1 minute, and observe for leakage. Pull the trigger to operate the gun for a 5-second burst. The gun shall function freely and when the trigger is released the flow of air or water shall stop.*

(Note: This test may be performed at the same time as 4.4.4.1 with the air connected to the disperser.

4.4.4.5 Container assembly. The container less the cam action closure shall be tested for the specified pressure for the specified time and checked with a suitable leak detection solution.

59 PACKAGING

5.1 Cleaning. The interior and exterior surfaces of the disperser components shall be cleaned, as necessary, to be free of foreign matter that could result in deterioration or affect satisfactory performance of the the assembled unit in use. Cleaning shall be in accordance with cleaning process Cl and drying shall be in accordance with any of the drying procedures outlined in MIL-P-116.

5.2 Preservation and packaging. Level shall be as specified (see 6.1)..

5.2.1 Level A.

5.2.1.1 Disperser assembly. The agent container, air cylinder and associate hoses and fittings, cleaned in accordance with 5.1, shall be prepared as follows : The wing nut shall be tightened on the neck of the agent container to secure the adapter and the manifold and prevent leakage. The discharge opening in the manifold shall be closed by use of a plastic cap-plug conforming to MIL-c-5501/7. The loose harness shall be secured to the frame as necessary to prevent excessive movement.

5.2.1.2 Gun and hose. The gun and hose, cleaned in accordance with 5.1, shall be packaged together as follows. The openings of the hose and gun shall be closed with snug-fitting plastic cap-plugs conforming to MIL-C-5501/70 The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

hose shall be loosely coiled and, it and the gun and the packaged multi-jet spray unit (see 5.2.1.3) shall be packaged together in a fiberboard box conforming to class domestic, style FOL, type CF, grade 175, SW of PPP-B-636, having inside dimensions in inches of 10 by 2-3/4 by 15-1/4 length, width and depth respectively. The hose shall not be bent or kinked to the extent it could cause permanent defamation that would affect its performances A piece of bound fiber cushioning material, size 1 by 9 by 12 inches, conforming to type IV, Class A, of PPP-C-1120 shall be included in the box in a manner to restrict free movement of and prevent damage to the contents. The box shall be closed in accordance with method I or II of the appendix to PPP-B-636. The closed box shall be sealed in a barrier bag conforming to type II, Class E, style 1 of MIL-B-117. Included air volume shall be kept to a practicable minimum when sealing the bag.

5.2.1.3 Multi-jet spray unit. The spray units, cleaned in accordance with 5.1, shall be sealed, one per bag, within polyethylene bags conforming to type II, style 1 of PPP-B-26, size 6 by 6 inches with 4 mil wall thickness. Included air volume shall be kept to a practicable minimum when sealing the bags.

5.2.1.4 Check valve assembly. The assemblies, cleaned in accordance with 5.1, shall be sealed, one each per polyethylene bag conforming to type 11, style 1, PPP-B-26, size 1-1/2 by 24 inches with a 4 mil wall thickness. Included air volume shall be kept to a practicable minimum when sealing the bags.

5.2.1.5 Static strap and clamp. The strap and clamp shall be sealed, one of each, together in a polyethylene bag conforming to type II, style 1, of PPP-B-26, size 4 by 6 inches with a 4 mil wall thickness. Included air volume shall be kept to a practicable minimum when sealing the bag.

5.2.1.6 Closure plug. The closure plug shall be sealed, one each per polyethylene bag conforming to type II, style 1, of PPP-B-26, size 4 by 6 inches with a 4 mil wall thickness. Included air volume shall be kept to a practicable minimum when sealing the bags.

5.2.1.7 Technical publications. The applicable technical publications for inclusion with each disperser shall be sealed in a polyethylene bag conforming to type II, style 1 of PPP-B-26, size 12 by 14 inches with 4 mil wall thickness. Included air volume shall be kept to a practicable minimum when sealing the bag.

5.2.1.8 Cylinder, compressed gas. The compressed gas cylinder shall be packaged in a fiberboard box conforming to Grade W5c, style RSC of PPP-B-636. Inside dimensions of the box in inches shall be 4-1/4 by 4-1/4 by 17 length, width and depth respectively. A mailing tube measuring 2 inches in diameter by 2-3/8 inches long shall be used as a collar to surround the nipple assembly and shall bear on the cylinder neck. As an alternate, the collar may be formed from Ppp-p-291, style 1, type 111, material measuring 3 by 22 inches. The

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

loose end shall be secured with PPP-T-76 tape. Closure of the fiberboard box shall be in accordance with the overseas closure requirements of the appendix to PPP-B-636.

5.2.1.9 Container assembly, agent. The agent container shall be packaged within a fiberboard box conforming to Grade W5c, style RSC of PPP-B-636. Inside dimensions of the box in inches shall be 7-1/8 by 7-1/8 by 23-3/4 length, width and depth respectively. A sleeve conforming to Grade W5c of PPP-F-320 shall be constructed in inches to measure 4 by 4 by 3-3/8 length, width and depth respectively having a 2 inch MFR joint. The sleeve shall be placed over the cam-action closure to rest on the cylinder neck. The MFR joint shall be stapled in six places. Closure of the fiberboard box shall be in accordance with the overseas closure requirements of appendix to PPP-B-636.

5.2.2 Level B.

5.2.2.1 Disperser assembly. The disperser assembly shall be prepared in accordance with 5.2.1.1.

5.2.2.2 Gun and hose. The gun and hose with the multi-jet spray unit (see 5.2.2.3) shall be packaged in accordance with 5.2.1.2, except the barrier bag for the box shall be omitted.

5.2.2.3 Multi-jet spray unit. The spray unit shall be packaged in accordance with 5.2.1.3 and 5.2.2.2.

5.2.2.4 Check valve assembly. The assembly shall be packaged in accordance with 5.2.1.4.

5.2.2.5 Static strap and clamp. The strap and clamp shall be packaged in accordance with 5.2.1.5.

5.2.2.6 Closure plug. The closure plug shall be packaged in accordance with 5.2.1.6.

5.2.2.7 Technical publications. The applicable technical publications shall be packaged in accordance with 5.2.1.7.

5.2.2.8 Cylinder, compressed gas. The compressed gas cylinder shall be packaged in accordance with 5.2.1.8 except closure of the fiberboard box shall be in accordance with the domestic closure requirements of the appendix to PPP-B-636.

5.2.2.9 Container assembly, agent. The agent container shall be packaged in accordance with 5.2.1.9 except closure of the fiberboard box shall be in accordance with the domestic closure requirements of the appendix to PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

5.3 Packing. Level shall be as specified (see 6.1).

5.3.1 Disperser assembly.

5.3.1.1 Level A. The disperser assembly, gun and hose, multi-jet spray unit, check valve assembly, static strap and clamp, closure plug and applicable technical publications, prepared and packaged in accordance with 5.2.1, shall be packed together in a shipping and storage container in accordance with Drawing 116-3-125.

5.3.1.2 Level B. The disperser assembly, gun and hose, multi-Jet spray unit, static strap and clamp, closure plug, check valve assembly and applicable technical publications prepared and packaged as specified, shall be packed together in accordance with Drawing 116-3-125, except the shipping and storage container shall be Grade B, non-preservative treated.

5.3.2 Cylinder, compressed gas and container assembly, agent.

5.3.2.1 Level A. One of each of the cylinders (cylinder, compressed gas and container assembly, agent), packaged as specified above (5.2.2.8, 5.2.2.9) shall be packed together in a wood box conforming to type II, Class 2, Grade A of MIL-B-2427. The box shall be of minimum size to contain the two packaged cylinders. Fiberboard pads conforming to Grade W5c of PPP-F-320 shall be used as required to restrict movement within the container.

5.3.2.2 Level B. One of each of the cylinders (cylinder, compressed gas and container assembly, agent), packaged as specified above (5.2.2.8, 5.2.2.9) shall be packed together in a wood box conforming to type II, class 2, grade B of MIL-B-2427, non-preservative treated. The box shall be of minimum size to contain the two packaged cylinders. Fiberboard pads conforming to grade W5c of PPP-F-320 shall be used as required to restrict movement within the container.

5.4 Marking. In conjunction with information furnished in the contract or order, marking shall be as specified herein.

5.4.1 Package marking. The component packages (5.2) shall be marked by labeling in accordance with requirements for interior package marking in MIL-STD-129. The disperser assembly shall be marked by tagging in accordance with MIL-STD-129. Marking shall include information pertinent to the National Stock Number, item description, quantity and unit of issue, contract or purchase order number and level of packaging and date packaged, as applicable. The technical publications packages will not require further marking when identification of the contents is possible through the transparent package.

5.4.2 Packing marking. The shipping and storage container shall be marked in accordance with Drawings 116-3-133 and 116-3-138.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

5.5 Palletization. . Unless otherwise specified in the contract or order, the packed dispersers and extra cylinders (5.3.2) shall be palletized in accordance with Drawing 116-3-124. The packed cylinders shall be palletized in accordance with the applicable requirements of MIL-STD-147.

6. NOTES

6.1. Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification-
(b) Level of packaging and packing required.
(c) Serial number assigned for the dispersers.
(d) preproduction.

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.

(2) Name and address of test facility and shipping instructions when testing is performed by the Government.

(3) Time required for the Government to notify the contractor whether to proceed with production

6.2 Caution. Due to the hazards inherent in testing with high pressures, contractors are advised that every precaution possible should be exercised for the safety and protection of personnel engaged in such testing.

6.3 International interest. Certain provisions of this specification are the subject of international standardization agreement ABCA-Army Quadripartite Standardization Agreement - 317. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accomodations

6.4 Components. The following specifications reflect the components required to complete this item:

Service Kit, M254 - MIL-S-51371(EA)
Regulator MIL-R-51516(EA)

Custodian:

Army - EA

Preparing activity:

Army-EA

Project No. 1040-A173

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

STANDARIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See *Instructions - Reverse Side)*

DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL -D-5143A(EA)	DISPERSER, RIOT CONTROL AGENT, PORTABLE , 3 GALLON, M33A1

3a NAME OF SUBMITTING ORGANIZATION

4. TYPE oF organization **(Mark** one)

VENDOR

uSER

MANUFACTURER

☐ OTHER *(Specify):*

bı. ADDRESS **(Street, City, State,** ***ZIP Code)***

5. PROBLEM AREAS

a Paragraph Number and Wording:

b, Recommended Wording:

c, Reeson/Rationale for Recommendation:

5. REMARKS

7a. NAME OF SUBMITTER ***(Last, First, MI)*** **- Optional**

b. **WORK TELEPHONE NUMBER** ***(Includ***
Code) - Optional

c. MAILING **ADDRESS** ***(street,*** **City,** ***state, ZIP*** code **- *optional***

8.. **DATE OF SUBMISSION (YYMMDD)**

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:01Z
Check the source to verify that this is the current version before use.