INCH-POUND

MIL-D-80262B
AMENDMENT 1
6 December 1991

MILITARY SPECIFICATION

DRILLING MACHINE, RADIAL, FLOOR MOUNTED

This amendment forms a part of MIL-D-80262B, dated 15 March 1990, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGES 3 and 4

2.2: Under "Non-Government publications" delete:

"JOINT INDUSTRIAL COUNCIL (JIC)

JIC H-1 - Hydraulic Standards for Industrial Equipment and General Purpose Machine Tools.

(Application for copies should be addressed to the Joint Industrial Council, c/o The National Tool Builders' Association, 7901 Westpark Drive, McLean, VA 2201-4269.)"

substitute:

"NATIONAL FLUID POWER ASSOCIATION (NFPA)

NFPA/JIC T.2.24.1 - Hydraulic fluid power - Systems standard for stationary industrial machinery

(Application for copies should be addressed to the National Fluid Power Association, Inc., 3333 N. Mayfair Road, Milwaukee, WI 53222-3291.)"

Page 5

3.2.1.1 Dials. Line 2: delete "0.015 inch"and substitute "1/16 inch".

Page 6

3.2.9 Lubrication. Line 5: delete "and shall be in clear view of the operator's normal work station". Line 7: delete "ways and axis screws" and substitute "column, ways, and axis screws".

3.3.7 Drive train gears. Line 8: delete "drive train" and substitute "headstock".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:51Z
Check the source to verify that this is the current version before use.

Page 9

3.4.7 Speeds and feeds. Delete third sentence "All speed and feed gears shall be of heat treated alloy steel."

3.4.9 Hydraulic system. Line 2: delete "JIC H-1" and substitute "NFPA/JIC T2.24.1".

Page 12

4.7.4 Performance test. Line 1: delete "15" and substitute "10". Line 4: delete "4" and substitute "3".

Page 17

TABLE I. Sizes and capacities. under Characteristics:

Spindle to base, minimum, not more than, inches, sizes B1, B2, and B3: delete "14" and substitute "15".

Spindle feeds, number of spindle feed ranges, inch per revolution, sizes B1, B2, and B3: delete "0.003" and substitute "0.004".

Page 20

Spindle speed range, RPM, sizes G1, G2, G3, and G4: delete "8 to 800" and substitute "15 to 1500".

Spindle feeds, number of spindle feed ranges, inch per revolution, size F3: delete "0.0025" and substitute "0.004".

Page 21

Spindle speed range, RPM, sizes H2, H3, H4, and H5: delete "8-800" and substitute "15-1500".

Page 22

TABLE II. Alignment and accuracy tolerances. under Components:

Arm parallel with base (low at outer end): delete "0 to 0.0024 inch per foot".

For machines up to 4 foot 7 inch length of radial arm: delete "0 to 0.0036 inch per foot" and substitute "0 to 0.0024".

For machines over 4 foot 7 inch length of radial arm: delete 0.0 to 0.0024" and substitute " 0.0 to 0.0036.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:51Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review activity:
Air Force - 84

USER ACTIVITIES:
ARMY - SM
NAVY - YD, MC

Preparing activity:
DLA - IP

Project (3413-0151)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:51Z
Check the source to verify that this is the current version before use.