INCH-POUND

MIL-F-48625A (AR)
AMENDMENT 2
03 April 1995
SUPERSEDING
AMENDMENT 1
2 November 1993

MILITARY SPECIFICATION

FUZE, 25MM, POINT DETONATING, SELF DESTRUCT
M758

This amendment forms a part of MIL-F-48625A (AR), dated 25 August 1989, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.4.1, Jolt; Delete "MIL-STD-331, Test 101.3" and substitute "MIL-STD-331, Test A-1".

PAGE 4

3.4.2, Jumble; Delete "MIL-STD-331, Test 102.2: and substitute "MIL-STD-331, Test A-2".

3.4.3, Salt Spray (fog); Delete "MIL-STD-331, Test 107.1" and substitute "MIL-STD-331, Test C-3".

3.4.4, Transportation vibration/temperature; Delete "MIL-STD-331, Test 404" and substitute "MIL-STD-331, Test B-1, Section 6.2".

3.4.5, Leak detection; Delete "MIL-STD-331, Test No. 118 (Bubble Method)" and substitute "MIL-STD-331, Test C-2".

PAGE 26

* 4.4.2.13, Critical 1, Inspection Method Reference; Delete "SMTE/ X-ray" and substitute "SMTE/X-ray 2/".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:34Z
Check the source to verify that this is the current version before use.

* 4.4.2.13, Add note 2: "2/ This inspection is to be performed either after assembly per drawing 11820609 or just prior to insertion of lead into fuze assembly."

PAGE 29

4.4.2.14, Delete "Salt Fog 18 100% 3.4.3 4.5.4.2" and substitute "Salt Fog 18 100% 3.4.3 4.5.4".

PAGE 30

4.5.2, Jolt; Delete "MIL-STD-331, Test 101.3" and substitute "MIL-STD-331, Test A-1".

4.5.3, Jumble; Delete "MIL-STD-331, Test 102.2" and substitute "MIL-STD-331, Test A-2".

Delete 4.5.4, 4.5.4.1, and 4.5.4.2 in its entirety and substitute:

"4.5.4 Salt Spray (fog). The test shall be performed in accordance with procedures specified in MIL-STD-331, Test Number C-3. Thirty-six fuzes shall be subjected to the 48 hour test. All test samples shall be disassembled and inspected per Paragraph 3 of Test Number C-3 to determine compliance with the requirements of 3.5.3."

PAGE 31

4.5.5, Transportation vibration/temperature; Delete "Test 404, procedure 2, specified in MIL-STD-331" and substitute "Test B-1, section 6.2, specified in MIL-STD-331".

4.5.6, Leak detection and sealant migration; Delete "MIL-STD-331, Test No. 118, Bubble Method," and substitute "MIL-STD-331, Test C-8".

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:34Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0826)

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:34Z
Check the source to verify that this is the current version before use.