MILITARY SPECIFICATION

FUZE, IMPACT, ATOMIC WEAPON: T53E2

This amendment forms a part of Military Specification MIL-F-50968A(PA) dated 6 December 1976.

PAGE 1

Delete "STANDARDS, FEDERAL, FED. STD. No. 356" and substitute "STANDARDS, MILITARY, MIL-STD-1188" (retain original title).

PAGE 3

Delete paragraph 3.5 (and Table II) and substitute:

"3.5 Output voltage.- The peak output voltage of the impact fuze, as measured during the initial pulse, shall be a minimum of 0.6 volt and shall be of positive polarity. The impact pulse applied to the fuze shall be 500 ± 25 gravities (g), peak amplitude, which will result in a maximum duration of the initial pulse of 200 microseconds as measured along the zero-voltage (reference) baseline on the measuring oscilloscope. Testing shall be as specified in 4.5.2."

PAGE 4

Delete paragraph 3.7 and substitute:

"3.7 Sensitivity.- The sensitivity of the impact fuze shall be as specified in Table III when subjected to a continuous sinusoidal vibration of 40 g ± 10 percent peak-to-peak at a frequency of 330 ± 20 hertz. In addition, the actual sensitivity value in millivolts (mv), for each fuze, shall be recorded (see 3.14). Testing shall be as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

TABLE III

Sensitivity (mv, peak-to-peak)	Test identification number (see 3.14) 1/
15 minimum	080001

1/ Not required during the following tests: high temperature, temperature shock, low temperature, humidity, and vibration."

PAGE 5

(a) Paragraph 3.14, line 4: Delete "Picatinny Arsenal" and substitute "US Army Armament Research and Development Command".
(b) Paragraph 3.14, line 5: Delete "SARPA-QA-N-A." and substitute "DRDAR-QAN-R."

PAGE 6

Line 6: Delete "3.5".

PAGE 7

Paragraph 4.3.2, line 8: Delete "acceptable" and substitute "acceptance".

PAGE 10

Paragraph 4.4.2.1.5, Major defect 101, line 5: Delete "FED. STD. No. 356" and substitute "MIL-STD-1188".

PAGE 13

(a) First line: Delete "three times" and substitute "once".
(b) Delete paragraph 4.5.4 and substitute:

"4.5.4 Sensitivity.- The impact fuze shall be mounted to a vibration machine with the fuze cover plate in the upper position. Each fuze mounting screw shall be torqued to a value of 25 ± 3 inch-pounds. The fuze shall be subjected to the vibrations specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.

in 3.7 along a vertical axis which is perpendicular to the fuze cover plate. The output of the fuze shall be measured across the fixed load, specified in 4.5.2, using an oscilloscope or other measuring device which has been approved by the Government for this purpose. The duration of this test is not significant, but it shall be long enough to ensure obtaining valid measurements. The fuze shall comply with the requirements of 3.7 during this test."

PAGE 15

Section 5 (Packaging): Delete references to FED. STD. No. 356 and substitute MIL-STD-1188.

PAGE 16

(a) Paragraph 6.1.2, line 1: Delete "3.5".
(b) Paragraph 6.3, line 3: Delete "Picatinny Arsenal" and substitute "US Army Armament Research and Development Command".
(c) Paragraph 6.3, line 4: Delete "SARPA-QA-T." and substitute "DRDAR-QAN-I."

Custodian:
Army-AR

(Project 1135-A244)

Preparing activity:
Army-AR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:45Z
Check the source to verify that this is the current version before use.