MILITARY SPECIFICATION

LAUNCHER, TRANSPORTER, BRIDGE: M48A5 or M60A1

TANK CHASSIS

This amendment forms a part of Military Specification MIL-L-52325C(ME), dated 6 December 1977 and is approved for use by the US Army Mobility Equipment Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, under Federal Specifications add:

"ppp-D-1055 - Barrier Material Waterproofed Flexible"

2.1, under Military Specifications delete:

"MIL-H-6083 - Hydraulic Fluid, Petroleum Base, for Preservation and Operation."

Substitute:

"MIL-C-16555 - Coating Compound, Strippable, Sprayable.
"MIL-H-46170 - Hydraulic Fluid, Rust Inhibited, Fire Resistant Synthetic Hydrocarbon Base."

PAGE 3

2.1, under Military Specifications delete:

"MIL-C-43760 - Cloth, Osnaburg, Cotton, Target, Olive Green 107, Mildew and Water Resistant Treated."

PAGE 8

3.7, line 7, (line 3 on page 8), delete "MIL-H-6083" and substitute "MIL-H-46170".

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:15Z
Check the source to verify that this is the current version before use.

PAGE 12

TABLE II, below item number 7, add:

Item No.	Description	Identification	Quantity	Remarks
8.	Grenade Launcher Kit, Smoke, M239	M48A5 OED 5705177 M60A1 OED 5705178	1	Contractor Installed"

PAGE 22

4.6.2.1, line 8, delete "MIL-H-6083", and substitute "MIL-H-46170".

PAGE 25

4.6.2.7.1 (b) (3), line 4 after "bridge"; delete remainder of paragraph and add new paragraph (4) as follows:

"(4) During one of the above launchings, the launcher shall be positioned so that the piston of the tongue cylinder is seated against the cylinder head. Hydraulic pressure shall then be applied to determine if the piston can be separated from the cylinder head."

PAGE 29

5.1.1.1.7 after "Engine and Exhaust Grills." delete:

"The engine and exhaust grills shall be given a protective cover consisting of osnaburg cloth conforming to MIL-C-43760 sprayed with a strippable compound conforming to MIL-C-16555, type II, class 1."

and substitute:

"Engine and exhaust grills shall be covered with barrier material conforming to PPP-D-1055, class E-2 secured in place with tape conforming to PPP-T-60, type IV."

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 5420-A329

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:15Z
Check the source to verify that this is the current version before use.