MILITARY SPECIFICATION

PROJECTILE, 105MM, TP-T, M489
METAL PARTS ASSEMBLY

This Amendment forms a part of Military Specification MIL-P-60811B (AR), dated 9 July 1984, and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1:

Delete: "MIL-C-60536 - Coating, Anodic, Hard, for Aluminum and Aluminum Alloys"

And substitute: "MIL-A-8625 - Anodic Coatings, for Aluminum and Aluminum Alloys".

PAGE 9

4.3.4, 4.3.4.1, 4.3.4.2, 4.3.4.3, and 4.3.4.4: Delete in their entirety and substitute:

"4.3.4 Abrasion resistance test. Two fin and base assemblies (or two fins and two bases) shall be subjected to the abrasion test in accordance with MIL-A-8625. If the actual parts cannot be used during this test, then four panels each, made in accordance with MIL-A-8625 and having the same alloy composition and heat treatment as the fin and base, shall be processed concurrently during the hard coating process and later be used for the abrasion test. If any components or test panel fails to meet the abrasion requirements, in accordance with MIL-A-8625, the first article will be rejected."

PAGE 23

4.4.2.7, Major defect 119: Delete "4.5.3.2" and substitute "4.4.3.2".

AMSC N/A FSC 1315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

PAGE 24

4.4.2.8, Major defect 117: Delete "4.5.3.2" and substitute "4.4.3.2".

PAGE 27

4.4.2.9, Major defect 105: Delete "4.5.3.2" and substitute "4.4.3.2".

PAGE 31

4.4.2.11:

Major defect 111: After "etching bath", add "(if applicable)".

Major Defect 112: After "mechanical abrasion", add "(if applicable)".

Note 1: Add "This inspection must be performed after any surface treatment operation is completed."

PAGE 41

4.4.3.2, 4.4.3.2.1, and 4.4.3.2.2: Delete in their entirety and substitute:

"4.4.3.2 Fin and base abrasion resistance test. One fin and base assembly (or set of components thereof) from each eight hours production or fraction thereof from the protective coating process shall be subjected to this test to determine compliance with MIL-A-8625. If the actual parts cannot be used during this test, then two test panels each, made in accordance with MIL-A-8625 and having the same alloy composition and heat treatment as the fin and base, shall be processed concurrently during the hard coating process and later be used for the abrasion test. Failure of any assembly, component, or test panel to comply with the abrasion requirement in accordance with MIL-A-8625 shall be cause for rejection of the product processed since the last acceptable test was performed."

PAGE 43

4.4.3.4:

Delete: "Adhesion testing." and substitute: "Adhesion testing (if applicable).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

At the end of the paragraph, add: "The torque test can be voided if the seals are to be mechanically abraded after the application of the etching bath."

4.4.3.5b: Change: "Increase in inside diameter" to "Increase in inside diameter or decrease in length."

PAGE 45

4.5.2.2: At the end, add: "Any test fixture used by the contractor must be approved by the govermment technical agency."

PAGE 46

4.5.3.2: Delete in its entirety.

PAGE 48

4.5.5: At the end, add "Any test fixture used by the contractor must be approved by the government technical agency."

PAGE 49

4.5.6: At the end, add "Any test fixture used by the contractor must be approved by the government technical agency."

PAGE 52

6.13: Delete "$SD = \frac{NX^2 - (X)^2}{N(N-1)}$"

And substitute:

"$SD = \sqrt{\frac{N\Sigma X^2 - (\Sigma X)^2}{N(N-1)}}$"

Custodian:
Army-AR

Preparing activity:
Army-Ar

(Project 1315-A785)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.