NOT MEASUREMENT SENSITIVE

MIL-T-62320C
3 October 1989
SUPERSEDING
MIL-T-62320B
19 October 1984

MILITARY SPECIFICATION

TRUCKS, VAN: SHOP, DIESEL AND GASOLINE ENGINE DRIVEN, 19,000 POUNDS GVW, 4X2 AND 4X4, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers diesel and gasoline engine driven, four-wheel, two-rear-wheel drive, and four-wheel, four-wheel drive, shop van trucks having a minimum gross vehicle weight (GVW) of 19,000 pounds for normal operating conditions. Vehicles procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. The vehicle shall be one of the following models as specified (see 6.2):

4x2 model - 4 wheels, 2 wheels driving
4x4 model - 4 wheels, 4 wheels driving.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC-2320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
VV-F-800	- Fuel Oil, Diesel.

MILITARY

*	MIL-T-5624	- Turbine Fuel, Aviation, Grades JP-4 and JP-5.
*	MIL-T-83133	- Turbine Fuel, Aviation, Kerosene Type, Grade JP-8.

STANDARDS

FEDERAL

FED-STD-297	- Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.
MS51335	- Pintle Assembly, Towing - 18,000 Lbs. Capacity, Manual Release.
MS75020	- Connector, Plug, Electrical - 12 Contact, Intervehicular, 28-Volt, Waterproof.
MS75021	- Connector, Receptacle, Electrical - 12 Contact, Intervehicular, 28 Volt, Waterproof.

* (Unless otherwise indicated, copies of federal and military specifications, standard, and handbooks are available from the Naval Publications and Form Center (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF DEFENSE

Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)
ASTM Standards.

A120	- Pipe, Steel, Black and Hot-dipped Zinc-Coated (Galvanized) Welded and Seamless, for Ordinary Uses (DoD adopted).

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standard Manual

(Application for copies of the European Tyre and Rim Technical Organisation publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 70	- National Electric Code.

(Application for copies of NFPA publications should be addressed to National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SAE, INC.

SAE Standards and Recommended Practices

J318	- Air Brake Gladhand Service (Control) and Emergency (Supply) Line Couplers - Trucks, Truck-Tractors, and Trailers (DOD adopted).
J537	- Storage Batteries.
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J588	- Turn Signal Lamps.
J589	- Turn Signal Switch.
J682	- Rear Wheel Splash and Stone Throw Protection (DOD adopted).
J688	- Truck Ability Prediction Procedure (DOD adopted).
J704	- Openings for Six- and Eight-Bolt Truck Transmission Mounted Power Take-Offs.
J706	- Rating of Winches.
J844	- Nonmetallic Air Brake System Tubing (DOD adopted).
J1067	- Seven-Conductor Jacketed Cable for Truck and Trailer Connectors.
J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies of SAE publications should be addressed to SAE Inc., 400 Commonwealth Drive, Warrendale. PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.

Year Book.

(Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.13, the vehicle, components, assemblies and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. Except as specified in 3.1.1 through 3.1.1.13 no removal, substitution or alteration of the chassis manufacturer's standard or optional chassis model components shall be made. All chassis items shall be as represented in the chassis manufacturer's technical data book. Special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of the invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, marking and data plates shall be in accordance with MIL-STD-1223. The exterior color and the identification markings shall be in accordance with the requirements of MIL-STD-1223 for the military service identified by the procuring activity (see 6.2). When specified (see 6.2), concealed markings shall be furnished.

3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.3 Drain plugs. Drain plugs installed in manual transmissions transfer case and rear axle shall be of the permanent magnet type.

3.1.1.4 Wood treatment. Wood shall be treated in accordance with MIL-STD-1223 (see 3.5.6).

* 3.1.1.5 Towing devices. Towing devices consisting of two hooks, loops eyes or pins or the chassis manufacturer’s standard single center mounted eye or pin shall be mounted on the front of the vehicle. All towing devices shall be frame rail mounted or reinforced back to each frame rail.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.1.1.6 Drive hubs. When specified for 4x4 model vehicles (see 6.2), manually operated drive hubs, for disengaging the front wheels from the power train, shall be provided, except for vehicles equipped with interaxle compensating devices between the front and rear axles (see 3.4.5.1.2).

3.1.1.7 Trailer towing package. A trailer towing package consisting of a pintle, safety chain attachment devices, a lighting receptacle, a trailer brake control system and associated reinforcements and wiring shall be installed on the rear of the vehicle. The pintle shall be of the rotating type conforming to MS51335-1. The pintle shall be installed on the chassis frame with reinforcements to transfer a vertical tongue load of not less than 1,800 pounds and a horizontal drawbar load of not less than 18,000 pounds directly to the chassis rails. The rearmost portion of the pintle shall be forward, but not more than 4 inches forward, of the rearmost part of the vehicle. Two trailer safety chain attachment devices, one adjacent to each side of the pintle, shall be provided. Each attachment device shall provide an ultimate strength at least equal to the GVW of the truck furnished. The attachment devices shall be capable of accommodating a standard grab hook (2-3/16 inches wide, 47/64 inch thick and 31/64-inch throat width) for a 3/8-inch chain. The lighting receptacle, conforming to SAE J560, with its conductors connected and color-coded as specified therein, shall be mounted in a readily accessible location near the pintle. The trailer brake control system shall conform to 3.4.11.2.

* 3.1.1.8 Trailer lighting cable. When specified (see 6.2), a trailer lighting cable, conforming to SAE J1067, shall be furnished. The cable shall be coiled and shall be not less than 110 inches long when fully extended. Both ends of the cable shall be equipped with a round plug conforming to SAE J560. The plugs shall be equipped with a grip for withdrawing from the connector sockets. The cable shall be packaged and stowed in the vehicle tool compartment.

* 3.1.1.9 Electrical trailer brake controller. When specified (see 6.2), an electric trailer brake controller, shall be provided. The controller shall be installed in the truck cab and wired through the SAE J560 lighting receptacle. The controller shall operate on the 12-volt electrical system of the vehicle and shall include load control, hand lever, and accessories.

* 3.1.1.10 Wheel splash and stone throw protection. Rigid splash shields ahead of the rear wheels and rubber mud flaps to the rear of the rear wheels, shall be furnished. Tilt cabs shall have rubber mud flaps to the rear of the front wheels. A metal strip not less than 1/8 inch thick and not less than one inch wide, extending the entire width of the mud flap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. As an alternate method of attaching the mud flaps, tabs or clips with minimum surface contact dimensions of 1 inch high by 1-1/4 inch wide by 3/32 inch thick shall be furnished at each bolt. All splash shield and mud flap installations, front and rear, shall conform to the rear wheel splash and stone throw protection provisions of SAE J682

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

* 3.1.1.11 Brushguard. Model 4x4 vehicles shall be equipped with a radiator and headlamp brushguard.

* 3.1.1.12 4x4 conversion. The chassis manufacturer's standard 4x2 truck chassis may be modified to provide all wheel drive conforming to the requirements specified herein if:

(a) The conversion axle manufacturer's engineering department specifically approves and certifies that all such modifications meet the design requirements and standards of the conversion axle manufacturer. Certification shall be based on both design analysis and proving ground test reports, which shall be made available to the engineering and quality assurance offices of the procuring activity.
(b) The chassis manufacturer's front axle before conversion has the same load rating as the conversion axle to be installed.
(c) Components used in the all wheel drive conversion are of current production.
(d) Components used in the all wheel drive conversion are approved for the conversion application by the component manufacturers.
(e) The converted vehicle is certified to conform to Federal Motor Vehicle Safety Standard No.121, by the intermediate or final manufacturer.
(f) Replacement headlights, if required to be added to meet the height requirements of Federal Motor Vehicle Safety Standard No. 108, are equivalent in mounting, protection, and range and precision of adjustment to the chassis manufacturer's original standard headlights.
(g) Unused headlight cavities are covered in a neat workmanlike manner, treated and painted to match the chassis cab color with treatment and painting equivalent to the chassis cab manufacturer's process for the remainder of the chassis cab. Cavities and their covers shall be rustproofed in accordance with 3.1.1.2.
(h) Complete installation drawings are available to the procuring activity.

* 3.1.1.13 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.2.2 Air pollution control. The vehicle shall comply with EPA Regulations governing Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

3.2.3 Sound level. The interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94. The vehicle exterior sound level shall conform to EPA Noise Emission Standards for Transportation Equipment, Medium and Heavy Trucks.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis and the cab with all attachments, accessories and equipment; the body; and a full complement of fuel, lubricants and coolant.

3.2.5 Gross vehicle weight. GVW shall consist of curb weight, operator weight (computed at 175 pounds), and a pay load to provide not less than the specified GVW. Vehicles with crew (four-door) cab shall have GVW computed with 525 pounds of payload in the rear seat.

3.2.6 Weight distribution. The distribution of GVW for the purpose of establishing suspension, axle and tire capacities shall be determined with the payload uniformly distributed over the load area.

3.2.7 Ratings. Vehicle ratings shall be manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the engineering office of the procuring activity. The minimum GVW rating shall be 19,000 pounds.

3.2.8 Overall width. The overall width of the vehicle, exclusive of tires and safety related items such as mirrors, lights and reflectors, shall be not more than 96 inches. The width over-the-tires shall be not more than 100 inches.

* 3.2.9 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.10 Asbestos. Asbestos materials shall not be used in any form in any part of the vehicle.

3.3 Performance. Vehicle shall meet the following performance requirements. Performance requirements for 4x4 model vehicles shall be met with front wheel drive disengaged and with front wheel driving hubs unlocked, except that vehicles equipped with interaxle compensating devices shall meet performance with front wheel drive engaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the vehicle loaded to the specified GVW.

3.3.1.1 High speed gradeability. The vehicle shall ascend a continuous grade of 1.5 percent at 50 miles per hour (mph). Gradeability requirements shall be met with the main transmission in direct drive and, when a multispeed axle is furnished, with the axle in high speed range. Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

* 3.3.1.2 Low speed. Low speed for vehicles equipped with a manual transmission shall be calculated with the engine operating at not less than 35 percent of the recommended governed speed, and shall provide not more than the vehicle speed (mph) specified in table I for the corresponding number of available forward speeds.

TABLE I. Vehicle low speed requirement.

Number of forward speeds	Maximum low speed (mph)	
	4x2 models	4x4 models
4 or 5	4.5	-
8	3.5	3.0
9 or 10	3.0	2.5

* 3.3.1.3 Maximum geared speed. The maximum geared speed at engine governed speed shall be not less than 58 mph for model 4x2 vehicles and 55 mph for model 4x4 vehicles. Conformance to geared speed specified shall be determined by calculations made in accordance with the following formula:

$$\text{Maximum geared speed (mph)} = \frac{\text{Governed speed (rpm)}}{\text{Total gear reduction x tire factor (see 6.3)}}$$

3.3.2 Service brakes. The service brakes shall control and hold the vehicle when loaded to its specified GVW on a 30 percent grade. The service brakes shall stop the vehicle, loaded to specified GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.4 Chassis components.

3.4.1 Engine. The engine furnished shall be the chassis manufacturer's standard or optional engine for the commercial model truck which meets or exceeds the requirements of this specification.

* 3.4.1.1 Diesel engine. Unless otherwise specified (see 3.4.1.2), the vehicle shall be equipped with a liquid cooled, compression ignition, two-stroke or four-stroke cycle diesel engine with not less than four cylinders for 4x2 model and not less than six cylinders for 4x4 model vehicle. Engine net horsepower used in performance prediction calculations shall be determined in

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

accordance with SAE J1349. The engine shall demonstrate the performance characteristic specified herein when using diesel fuel conforming to VV-F-800. In addition, when specified (see 6.2), the engine shall operate satisfactorily on grade JP-4 and grade JP-5 fuel conforming to MIL-T-5624 under emergency, short duration conditions and on grade JP-8 fuel conforming to MIL-T-83133 under normal condition. A power loss when operating on JP-4, JP-5 or JP-8 is acceptable.

* 3.4.1.2 Gasoline engine. When specified (see 6.2), the vehicle shall be equipped with a liquid cooled, internal combustion, four-stroke cycle gasoline engine with not less than six cylinders. The engine furnished shall provide the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at an engine speed of not more than the manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel when used in accordance with the operator's manual. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J1349. Unless otherwise specified or required by foreign laws, vehicles for overseas use shall be capable of accepting and operating on leaded gasoline.

3.4.1.3 Oil filter. A full-flow type oil filter shall be furnished.

3.4.1.4 Governor. An engine governor shall be furnished and set and sealed to limit the engine to maximum recommended operating speed.

* 3.1.1.5 Cooling. The cooling system shall maintain engine coolant at a temperature below the boiling point with the vehicle loaded to rated GVW and operated at an altitude of 10,000 feet above sea level or in an ambient air temperature of not lees than 125 degrees Fahrenheit (^{o}F). The cooling system shall include a surge tank or a coolant recovery reservoir of not less than two-quart capacity. On tilt cab vehicles, a radiator servicing access door shall be provided to allow verification of coolant level.

* 3.4.1.6 Coolant temperature control. Thermostatic control of engine coolant temperature shall be provided. On diesel engine driven vehicles, the control shall include complete thermostatic control of all coolant flow through the radiator.

* 3.4.17 Fan clutch. A fan clutch shall be provided. The fan clutch shall reduce the fan speed automatically when the fan is not required for engine cooling. The fan clutch shall be asbestos free.

* 3.4.1.8 Power plant heaters and fuel warmer. When specified (see 6.2), a coolant heater, an engine oil heater, and a fuel warmer (diesel engine driven vehicles only) shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 120-volt alternating current (ac) and shall be wired through a junction block, including fuse or circuit breaker, to a single, three-pronged (male),

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

weatherproof slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three-pronged (two power plus one ground) male connector at the other end. Electrical insulation of the connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation, and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) A coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. An engine thermostat with an operating range of 170°F to 195°F shall be installed
(b) An immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening
(c) The battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F
(d) A fuel warmer or preheater shall be provided on diesel engine driven vehicles to prevent clogging of fuel filters due to wax, crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of minus 40°F to an outlet temperature of plus 9°F, with a flow rate not less than the maximum fuel demand of the engine fuel system. A coolant shutoff valve shall be provided for the coolant inlet aide of the fuel warmer unit.

3.4.2 Electrical systems. The electrical systems shall be in accordance with Federal Motor Carrier Safety Regulations 393.27 through 393.31 and 393.33.

* 3.4.2.1 Starting system. For diesel engine driven vehicles, a 12- or 24-volt direct current (dc) starting system with a 12-volt dc lighting system, and with not less than a 60-ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system or glow plug. If an ether system is furnished in lieu of a glow plug, it shall be of the measured shot type. The measured shot type ether system shall be key operated or manually operated from the driver's compartment and shall be inoperative with the engine warm. Complete provisions for a replaceable ether reservoir of not less than 12 fluid ounces shall be furnished. A reservoir need not be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.4.2.2 Ignition system. For gasoline engine driven vehicles, an ignition system of 12-volt dc potential shall be furnished. An alternator of not less than a 40-ampere rated capacity and which provides not less than 16 amperes dc output at normal engine idle speed shall be furnished. When a converter type 24-volt system is provided for a trailer receptacle (see 3.4.2.6), an alternator of not less than 60-ampere rated capacity and which provides not less than 16 amperes dc output at normal engine idle speed shall be furnished.

* 3.4.2.3 Lighting. All vehicle lights, reflectors, and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26(d). Lights and reflectors shall not be mounted on the vertical surface of rub rails (unless recessed and fully protected) or mounted on vehicle bumpers.

* 3.4.2.4 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. Turn signal units shall be installed in accordance with SAE J588. Turn signal operating units shall have a visible and audible type flash indicator.

3.4.2.5 Batteries. Each battery shall be of 12-volt potential. The total reserve capacity rating and the total cold cranking rating at 0°F, both measured in accordance with SAE J537, shall be not less than that specified in table II. Batteries shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

TABLE II. Batteries

Engine type	Reserve capacity (minutes)	Cold cranking (amperes)
Diesel	320	1,200
Gasoline	100	450

3.4.2.6 Auxiliary 24-volt system with trailer receptacle. When specified (see 6.2) , an auxiliary 24-volt system with a trailer receptacle assembly shall be furnished. Either a converter type (see 3.4.2.6.1) or an alternator type (see 3.4.2.6.2) system meeting specified requirements shall be furnished. A trailer receptacle, conforming to MS75021-2 with cover assembly, shall be provided in an accessible location at the rear end of the vehicle. A twelve-conductor truck tractor lighting cable not less than 110 inches long, with both ends of the cable equipped with connectors conforming to MS76021-1 and MS76020-2, shall be furnished. The cable assembly shall be stowed in the vehicle. The 24-volt service lighting circuit shall be connected through the appropriate lighting controls to terminals B, D, E, J, and L of MS75021-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.4.2.6.1 Converter type 24-volt. system. The 12- to 24-volt converter(s) shall operate from the 12-volt battery supply (see 3.4.2.6). The output capacity shall be not less than 12 amperes.

3.4.2.6.2 Alternator type 24-volt system. The alternator type 24-volt system shall be separate from the 12-volt vehicle lighting and ignition system and shall include:

(a) Nominal 24-volt alternator with not less than a 25-ampere rated capacity and capable of providing not less than a 7-ampere dc output at normal engine idle speed
(b) Two 12-volt batteries with a combined capacity of at least 40 ampere-hours at a 20-hour rate or one 24-volt battery with a capacity of at least 20 ampere-hours at a 20-hour rate.
(c) Voltage regulating device
(d) An ammeter, mounted on the instrument panel.

3.4.2.7 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

* 3.4.3.1 Air cleaner. An air cleaner shall be furnished.

* 3.4.3.2 Fuel tank(s). The fuel tank(s) shall have a total capacity of not less than 50 gallons (43 gallons for vehicles destined for California). When more than one tank is furnished on diesel engine driven vehicles, means shall be provided to assure an equalized fuel level in both tanks. When more than one tank is furnished on gasoline engine driven vehicles, a selector valve connecting either tank to the engine fuel intake shall be provided and means shall be provided to monitor the fuel level of either tank from a single gage.

3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. Vertical mufflers capable of being reached easily by personnel entering or leaving either side of the cab shall be provided with a heat shield. Vertical exhaust systems shall be provided with a hinged rain cap.

3.4.5 Gear train.

3.4.5.1 Manually shifted transmission. Unless otherwise specified (see 3.4.5.3), a manually shifted transmission shall be provided on the vehicle. Input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine. The transmission shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

provided with power takeoff opening(s) conforming to SAE J704. The transmission shall provide for maximum ease of shifting in all speeds. Transmission and axle gear ratios shall be selected to provide the performance specified in 3.3.1 through 3.3.1.3.

3.4.5.1 Speeds. The vehicle shall be provided with not less than four forward speeds for 4x2 model vehicles and not less than 8 forward speeds for 4x4 model vehicles.

* 3.4.5.1.2 Transfer case. A transfer case shall be furnished in model 4x4. Unless the transfer case for is equipped with devices which compensate for differential torque and speeds between front and rear axles, the transfer case shall provide for driver selection of either two-wheel or four-wheel drive. When furnished, interaxle compensating devices shall provide for positive transfer of power to all driving axles. When a two-speed transfer case is furnished, the speedometer shall read accurate speed (mph) with the speed selector in high or low range.

3.4.5.2 Clutch. The clutch shall be the largest capacity clutch offered for the type of vehicle and engine furnished, with the clutch torque capacity exceeding the maximum delivered engine torque. The clutch lining shall be asbestos free.

3.4.5.3 Automatic or semiautomatic transmission. When specified (see 6.2), the vehicle shall be provided with an automatic or semiautomatic transmission. The transmission shall include a hydraulic torque converter and not less than four forward gear ratios. The normal driving range selector position shall provide not less than four gear ratios without movement of the selector. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

3.4.5.4 Power takeoff. When a power takeoff is furnished, it shall be of a rated capacity to operate powered equipment. Controls to operate the power takeoff shall be located in the truck cab accessible to the seated driver. A caution plate or decal reading "DO NOT OPERATE VEHICLE AT HIGHWAY SPEEDS WITH POWER TAKEOFF ENGAGED" shall be installed so as to be readily visible to the seated driver.

3.4.6 Driveline comments. Driveline components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction, in proportion to the number of driving axles furnished.

3.4.7. Frame. The chassis frame shall be the manufacturer's standard for the model vehicle furnished. Chassis frame rails shall not project beyond the rear end of the body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded to the specified GVW. When the suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic double-acting shock absorbers at the front wheels.

* 3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with the vehicle loaded to the specified GVW. The gear ratio shall provide the performance specified in 3.3.1 through 3.3.1.3. When specified (see 6.2), the wheelbearings and axle spindles shall be oil lubricated. Except for driving axles, the hubcaps shall have a window for visual determination of oil level. Provisions for venting or withstanding internal pressure buildup and for replenishing the oil supply shall be provided.

3.4.9.1 Two-speed axles. When specified for 4x2 model vehicles (see 6.2), a two-speed axle shall be furnished, equipped with electric, vacuum, or air shift, and provided with ratios which will permit proper gear splitting. The gear ratio shall provide the performance specified in 3.3.1 through 3.3.1.3.

3.4.9.2 Traction control. Model 4x4 vehicles and when specified (see 6.2), model 4x2 vehicles shall be provided with a traction control on the rear axle. The traction control shall actuate automatically to ensure that power is transmitted to the wheels having traction when the opposite wheel loses traction. Maximum traction capabilities shall be maintained at all times under each drive wheel for the life of the vehicle.

* 3.4.10 Wheels, rims, tires, and tubes. Unless wide base tires are specified, the vehicle shall be equipped with single front and dual rear wheels. Rims and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Multi-piece rims shall not be furnished. Rims and disc wheel sizes shall be the same for all wheels on each vehicle. Tire size and load range (ply rating) shall be the same for all tires on each vehicle. When specified (see 6.2), wide base type tires and wheels for the front and rear axles shall be provided in lieu of conventional front and dual rear wheels and tires. Wide base wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), disc type wheels shall be furnished.

* 3.4.10.1 Tires. Tires shall be tube or tubeless type, steel belted radial ply, or when specified (see 6.2), bias ply. The 4x2 model vehicles shall be equipped with highway tread tires. The 4x4 model vehicles shall be equipped with nondirectional mud and snow tread tires. Tires shall be of a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded to the specified GVW. Tires and tire size designation systems shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

* 3.4.10.2 Inner tubes. When tube type tires are specified in procurement documents. inner tubes shall be of heavy duty type and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

3.4.10.3 Carrier for spare tire assembly. When specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. The carrier design shall enable removal or mounting of the spare wheel assembly using only the tools specified in 3.4.16.1. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material.

3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished. When a spare tire assembly is specified (see 3.4.10.5), a spare wheel or rim shall be furnished.

3.4.10.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design and load range (ply rating) as the tires furnished on the vehicle.

* 3.4.11 Brakes. The brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.43 and 393.45 through 393.52. Brake linings shall be of nonasbestos material.

* 3.4.11.1 Air brakes. The vehicle shall be equipped with full-air brakes on all the wheels. The braking system, complete with all necessary components, shall include:

(a) Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 7-1/4 cubic feet per minute (cfm)
(b) Air storage reservoir(s), each tank equipped with drain, and with safety and check valves between compressor and last reservoir tank
(c) Foot control, suspended or treadle type
(d) Air control valves
(e) Air pressure gage, visible to the driver
(f) Low air pressure warning, visible and audible
(g) Service brake stoplamp switch
(h) Automatic moisture ejector
(i) Automatic slack adjusters on cam type brakes or internal self-adjusting brakes on wedge and disc type brakes (model 4x2 only).

* 3.4.11.1.1 Air dyer. A replaceable cartridge desiccant type air dryer shall be installed in the air brake system. The dryer shall have the capability of removing not less than 95 percent of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

moisture in the air being dried. The dryer shall have a pre-cooler and a filter to screen out oil and solid contaminants. The dryer shall have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

* 3.4.11.2 Trailer brake control system. In addition to the components specified in 3.4.11.1, a trailer brake control system shall be furnished (see 3.1.1.7). The trailer brake control system shall include:

(a) Identification of emergency and service lines
(b) Coincident control of trailer brakes with prime mover foot control
(c) Independent hand control for trailer brakes
(d) Prime mover protection valve with dash control and automatic breakaway feature
(e) Trailer stoplight control operable with foot brake and with hand control for trailer brakes
(f) Two SAE J844 coiled air hoses, not less than 110 inches long, with SAE J318 gladhand couplers on both ends of hoses. The hoses shall be packaged and stowed in the vehicle tool compartment for shipment
(g) Air connectors, for trailer with SAE J318 gladhand couplers mounted at the rear of the vehicle, located to prevent interference with the trailer
(h) Dummy gladhand couplers with chains
(i) Prime mover only parking brake valve to permit prime mover parking brakes to be applied while charging the trailer air brake system.

3.4.11.3 Brake controls for use from a towing vehicle. When specified (see 6.2), the vehicle shall be furnished with a system for controlling the brakes from a towing vehicle (wrecker). The installation shall be complete with air brake couplers, a relay emergency valve with no-bleed-back feature (except when spring applied emergency brake is furnished), and additional air lines and fittings. The service and emergency couplers shall be mounted on the front in a protected position providing for ready attachment of air hoses from a towing vehicle. The service and emergency couplers shall be identified and provided with dummy gladhand couplers with chains. The system shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

* 3.4.12 Cab. Unless otherwise specified, the chassis manufacturer shall furnish any type of his standard or optional full width cab. When specified (see 6.2), a cab with a forward tilting hood and fender assembly, including tilting and locking mechanism shall be furnished. Cab doors shall be equipped with locks, operable from inside the cab through mechanical linkage, with at least the curbside door equipped with an external, key operated lock. Drip rails shall be installed above the cab doors. When the front tires extend beyond the cab fenders, rubber fender extensions extending at least to the outside of the tire tread shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

* 3.4.12.1 Cab interior. Unless otherwise specified, the cab shall have an upholstered, full width, adjustable seat and back or individual, adjustable, driver's seat and individual passenger seat. When specified (see 6.2), an individual, adjustable, driver's seat and an individual passenger seat shall be provided. When specified (see 6.2), the driver's seat shall be the manufacturer's standard air ride suspension type. The color of the upholstery and the interior finish shall be compatible with the exterior color (see 3.1.1.1). White upholstery shall not be provided. Interior lighting shall be provided. Two pairs of seat belts shall be installed.

3.4.12.2 Crew cab. When specified (see 6.2), a four-door full width crew cab shall be furnished in lieu of the standard, full width cab. The cab shall be equipped with two upholstered, full width seats and backs. The front seat shall be adjustable. Fastenings and three pairs of seat belts shall be installed for both front and rear seats. Cab doors shall be equipped with locks operable from inside the cab through mechanical linkage, with both front doors equipped with external key operated lock. Cab doors shall have windows with crank operated window regulators. Interior lighting shall be provided. The cab roof shall be of-one piece construction; or, if welded, the roof shall give the appearance of one piece with weld seams being continuous, waterproof, and free of visible seams, bumps, or protrusions. Full length drip moldings shall be mounted above the doors. When a crew cab is furnished, the cab-to-axle dimension shall be measured from the back face of the crew cab.

3.4.12.2.1 Crew cab seat. spacing. With the front seat adjusted to the extreme forward position, there shall be not less than 30 inches, measured in a horizontal plane, between the front of the rear seat back and the rear of the front seat back. A kick-space height of not less than 2-3/4 inches shall be maintained between the floor and the rear of the front seat in all positions of adjustment. Leg room and space forward of the front seat shall be equivalent to that provided ahead of the seat in a two-door standard cab.

3.4.13 Steering. Power steering shall be furnished.

3.4.14 Windshield wipers and washers. The vehicle shall be equipped with dual windshield wipers and windshield washers. The windshield wipers shall be of the multispeed type, operated by either air or electric motor(s).

3.4.15 Bumper. Unless the bumper is an integral part of the vehicle cab, a channel type front bumper shall be provided except when a front mounted winch is furnished (see 3.4.22).

3.4.15.1 Rear end protection. The rear end of the vehicle shall be protected in accordance with Federal Motor Carrier Safety Regulation 393.86. A rear bumper shall be provided as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.4.16 Tool stowage. Stowage space of sufficient size to accommodate a vehicle jack, hand tools, antiskid chains and emergency reflective triangles shall be furnished for retaining equipment during vehicle operation. Stowage space for these tools may be furnished in the cab. When stowage space for these tools is located outside the cab, it shall be weatherproof and shall provide for locking with a padlock.

3.4.16.1 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, jack handle, and wheelnut wrench. The jack shall be of such closed height as to permit its location under an axle or other satisfactory lift point, at any wheel with a tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.17 Heater and defroster. A hot water heater shall be provided. The heater shall have fresh air intakes. Discharge outlets shall be provided to direct heated air to the floor and to the defroster louvers. The heater shall be complete with a blower and with mounted controls convenient to the driver.

3.4.18 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. The instruments shall be panel mounted.

* 3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key operated ignition switch
(b) Ammeter, charging indicator or voltmeter
(c) Fuel gage
(d) Oil pressure gage or red indicator warning light
(e) Engine coolant temperature gage or high coolant temperature or low coolant level red indicator warning light
(f) High coolant temperature or low coolant level alarm buzzer
(g) Speedometer with recording odometer
(h) Ash receptacle
(i) Dual sunvisors
(j) Front door mounted armrest on driver's side
(k) Driver's compartment ventilator other than window
(l) Tachometer (for diesel engine driven vehicles).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

When specified (see 6.2), an ammeter or voltmeter gage, an oil pressure gage, and a coolant temperature gage shall be provided in lieu of the indicators and buzzers specified above. When specified (see 6.2), an automatic engine shutdown system also shall be furnished. The system shall include an engine coolant temperature, engine coolant level and engine oil pressure red indicator warning light and alarm buzzer. The warning light and buzzer actuation shall preceed engine shutdown. The system shall permit engine restart and run for approximately 30 seconds following automatic shutdown. Also, engine oil pressure and engine coolant temperature gages shall be provided with the automatic engine shutdown system.

3.4.20 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the combination type having flat and convex areas. The flat portion shall have not less than 50 square inches of reflective area. The convex portion shall have not less than 20 square inches of reflective area. The mirrors shall have not less than two supports.

3.4.21 Horn. The manufacturer's standard electric horn shall be furnished. When specified (see 6.2), in addition, an air operated horn shall be furnished.

*. 3.4.22 Front mounted winch. When specified (see 6.2), a winch assembly, mounted on the front of the vehicle and powered by the manufacturer’s standard power takeoff or powered hydraulically, shall be provided. The winch shall conform to SAE J706. The winch shall be of the single drum type and shall have one forward and one reverse speed. All winch controls shall be mounted inside the cab. Winch controls shall be located to provide no interference with the entry or exit of the driver. The winch shall have a rated single line pull capacity of not less than 20,000 pounds pull on the bare drum. The winch line speed on the bare drum shall be between 15 and 30 feet per minute at an engine speed equal to 35 percent of engine governed speed. The winch shall be wound with not less than 185 feet of 5/8-inch diameter, preformed, 6x37, improved plow steel, wire strand core cable and shall be equipped with end chain and hook. An integral, adjustable, automatic safety brake shall be provided. The winch shall be equipped with a roller guide. Angles of the winch drive line U-joints shall be not greater than 16-1/2 degrees.

3.4.22.1 Winch drum guard. A winch drum guard shall be furnished. The guard shall confine the cable to the area between the drum flanges. The guard shall consist of not less than 1/4-inch vertical side plates, conforming to the outside radius of the drum flanges. Six bare, 3/8 inch by 1-1/4 inches, shall be welded to the vertical side plates. Three bars shall be located on the top and spaced equally on the bottom radius. The vertical distance between the vertical side plates and the drum flanges shall be not greater than half the specified cable diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.4.22.2 Front bumper. When a front mounted winch is specified, the bumper shall be mounted forward of the winch. The open area on either side of the winch shall be covered with a combination step plate and gravel guard. The bumper shall be either a channel (see 3.4.15) or pipe type. When a pipe type front bumper is furnished, the nominal diameter shall be not less than 3 inches, and the wall thickness shall be not less than that specified in Schedule 40 of ASTM A120. The pipe type front bumper shall have half-round ball ends.

3.4.22.3 Combination step plate and gravel guard. When a front mounted winch is specified, a combination step plate and gravel guard shall be furnished. The step plate shall be fabricated of not less than 14 gage (0.0747 inch) steel tread plate exclusive of projections. The step plate shall be secured to the front bumper and shall be not less than 1/4 inch and not more than 3/8 inch from the chassis sheet metal. The step plate shall be capable of supporting 300 pounds per square foot. The step plate shall not deflect more than 1/8 inch under the loads imposed.

3.4.23 Engine hour meter. When specified (see 6.2), an engine hour meter having a totalizing mechanism of not less than 9,999 hours shall be furnished for the chassis engine to register accurately the number of hours of operating time. The meter shall be of rugged construction to ensure continuous trouble-free performance under severe operating conditions. The engine hour meter shall be mounted on the cab instrument panel or in the engine compartment in a readable location.

3.4.24 Back-up alarm. When specified (see 6.2), the vehicle shall be provided with an audible, pulsating, signaling device (electrical or mechanical) to caution personnel when the vehicle is in reverse gear operation.

3.5 Body. The body shall be constructed of sheet metal having minimum gages specified for carbon steel. High tensile steel utilized may be two gages lighter weight in accordance with US Standard gages. Aluminum alloys of equal strength may be substituted, and lightweight aluminum alloy roof panels may be utilized as specified in 3.5.3.

3.5.1 Body dimensions. The vehicle shall have a rear-of-cab to rear axle dimension of not less than 100 inches. The cab-to-axle dimension specified may be reduced not more than 2 inches when the vehicle is furnished with a tilt cab (see 3.4.12). Loadspace dimensions shall be as specified in table III.

TABLE III. Dimensions.

Dimension	Inside - minimum (inches)	Outside - maximum (inches)
Length	162	171
Width	84	96
Height	76	132 (overall)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.5.2 Body framing. Body framing shall be of all-steel welded construction, braced at all points of stress. There shall be not less than 10 full-width crossmembers, including the ends, of full-channel or I-beam steel construction, attached to the longitudinal sills by welds. Angle gussets (when used), crossmembers, longitudinal sills, and welded reinforcements (when used) shall be joined by weld for not less than 50 percent of the length of the contact edge(s). Spacing of crossmembers shall be equal, ahead of, and to the rear of the wheels. Longitudinal sills shall be constructed from structural steel channels or reinforced, formed channels. Formed channel sills shall be reinforced within the sill, at each crossmember or body mounting point, with formed channel reinforcements. The crossmember, angle gussets, formed longitudinal sills, and reinforcements shall be not less than 10 gage (0.1345 inch) steel. Side and front rails (out-rails) shall be not less than 12 gage (0.1046 inch) steel. Design of the subframe shall permit low floor height, provide tire chain clearance, and shall permit vehicle operation at speeds up to 55 mph over improved roads when loaded with an evenly distributed payload to the rated GVW, without evidence of permanent deformation. Side, front and rear post construction shall be not less than 14 gage (0.0747 inch) pressed steel. Bodies shall have at least 10 posts per side with not less than five posts at the front and four at the rear with two of the rear posts spaced to support the rear doors. The front structure shall be capable of withstanding a horizontal static load equal to 0.4 times the payload capacity of the vehicle without permanent distortion.

3.5.3 Body exterior. Roof assembly shall be standard for the vehicle, and shall be constructed to ensure drainage. Roof design shall include roof support bows of not less than 16 gage (0.0598 inch) steel, and spacing shall be that of side posts; the roof panels shall be not less than 22 gage (0.0299 inch) steel, or 0.032 inch aluminum alloy. Body side panels shall be stretcher level sheet steel or equivalent flat, of not less than 20 gage (0.0359 inch). All roof and body seams and joints shall be waterproof and all body and roof corners and body roof edges shall be rounded with a maximum radius of 6 inches. When the perimeter of the roof is furnished with extrusions, square type roof corners and posts in lieu of round radius corners are acceptable. Replaceable rub rails of not less than 12 gage (0.1046 inch) steel shall be provided along each side of body. Full length drip molding shall be mounted above all doors and windows that open.

3.5.4 Van body wind deflection. Unless a wind deflector is specified, an aerodynamically streamlined body front shall be incorporated into the design of the body to direct airflow around the sides and over the top of the van body. The construction shall be integral with the van body front wall, sidewalls and roof, giving a curved front radius. When specified (see 6.2), a wind deflector fairing shall be attached to the upper front face of the van body. The deflector shall have an aerodynamic fairing shape to direct airflow around the sides and over the top of the van body. The deflector fairing shall have a rounded nose with a convex profile in both side and top

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

views, forming a smooth compound curved surface blending into the rectangular body cross-section. The nose of the fairing shall project forward sufficiently to achieve a significant drag reduction at low yaw angles, and shall have a large enough radius to produce minimal flow separation at yaw angles of up to 20 degrees. In no case shall the forward portion of the fairing be less than 22 inches from the front face of the van body. The lower edge of the fairing shall be located as required to minimize drag due to turbulent airflow from the cab. The fairing construction material shall be molded fiberglass. Design operational limits shall include forward vehicle speeds of 60 mph during wind gusts of 60 mph from any direction.

3.5.5 Body interior. The complete interior of the body sides, top, back and front shall be insulated (see 3.5.5.1) and paneled. Inside paneling for sides, front, rear (including doors), and top shall be steel of not less than 22 gage (0.0299 inch) or 0.032 inch embossed aluminum. The van body shall be free from leakage when exposed to an overhead water spray test.

3.5.5.1 Insulation. Insulation shall provide resistance to the transfer of heat equivalent to the protection afforded by a l-inch thick batt having a thermal conductivity of 0.24 Btu/sq. ft./deg. F/hr./l-in. thickness in normal ambient air temperatures. Insulation shall be either flexible or batt type, fibrous or cellular material having a moisture absorption capacity of less than 2 percent by weight and shall be asbestos free. Materials shall be odorless and fire retardent. The insulation shall not breed nor promote the growth of fungus and shall not cause nor accelerate corrosion of steel, copper, or aluminum. The insulation shall be cemented to the inner side of external walls and provided with means to retain the insulation under all operating conditions. Cement shall be waterproof and the resulting bond shall provide shear strength sufficient to prevent a sag of the insulation when the assembled van is operated at speeds up to 55 mph over improved roads. All insulation, to a maximum practicable extent, shall be installed prior to the closing of spaces in the body sides, front and rear panels, ends, doors, upright body members, roof, roof bows, and other parts.

3.5.6 Floorboards. The floorboards shall run the full length of the body except in those areas occupied by wheel plates. If wheel plates are furnished, wheel plates shall be flush with the floor. Flooring shall be of hardwood or dense southern yellow pine not less than 1-1/8 inches thick (finished dimension) with ship-lapped or tongue-in-groove joints, installed and bolted to the cross-sills. Two-piece boards shall be lap-jointed at a crossmember and bolted down. The key board shall be one-piece. Wood parts shall be treated in accordance with 3.1.1.4.

3.5.7 Windows. Each van body shall be equipped with eight windows (four on each side), excluding those placed in the rear doors. The windows shall be of the operating type. The bottoms of the eight window frames shall be not less than 40 inches from the floor. The window openings shall be framed between the exterior and interior panels with wood or metal to form a seal around the cutout for the window.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.5.7.1 Operating (side) windows. The sash for side windows shall be approximately 21 inches wide and 24 inches high, with double-pane glazing, hinged at the top, and with regulators to permit selection of fixed positions. Each side window shall be set in an all-metal frame, sealed to exclude air and moisture. All window frames shall have sufficient strength to support any body side post cut during installation. An insect screen as specified in 3.5.7.1.3 shall be provided inside each side window.

3.5.7.1.1 Double panes. Each window shall have two panes of safety window glass. Panes shall be assembled in the sash frame, including air space of not less than 3/16 inch, shall be sealed to exclude moisture, condensation or frost, and shall withstand altitude changes from sea level to 10,000 feet above sea level.

3.5.7.1.2 Window regulators. Each side window shall have a regulator operable from within the van body, to provide opening positions for at least 22-1/2 and 45 degrees. Cranking, telescoping, or folding window regulators to minimize the projection within the van shall be furnished.

3.5.7.1.3 Insect screens. Each side window shall be furnished with an inside insect screen fitted in the window opening. The wire cloth shall be 16 mesh.

3.5.8 Double rear doors. The body shall be provided with a main door and an auxiliary door at the rear. The rear doors shall be side hung on heavy duty, strap type hinges, to provide a clear opening width of not less than 52 inches. A door check shall be provided on each door, arranged to hold the door at 115-degree and 180-degree open positions. Each rear door shall be equipped with a fixed type window measuring not less than 10 inches wide and 10 inches high, permanently set in frames, centered in the upper portion of the door. Glazing shall be of double-pane construction, as specified in 3.5.7.1.1.

3.5.8.1 Main rear doors. The main rear door shall be located on the curb (right) side and shall provide an opening of not less than 32 inches wide and 72 inches high. An operating mechanism for the main door shall include slide bolts of ceiling and floor-wedge type, a center case, and inside and outside handles. A means for locking the main door from the outside shall be furnished.

3.5.8.2 Auxiliary rear door. The auxiliary rear door shall be located on the street (left) side and shall provide an opening of not less than 20 inches wide and 72 inches high. Locking bolts shall be provided at the top and bottom and shall be operable only from the inside of the body.

3.5.9 Electrical system. Each vehicle body shall be provided with separate 12-volt dc and 120-volt ac systems for interior electrical devices and power connections. The cable and conduit required for electrical devices inside the body shall be installed inside the side and roof panels to

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

permit the use of lamps and outlets of the flush mounted type. All wiring shall be fastened or clipped at points of bending and shall be protected against chafing and damage.

* 3.5.9.1 Alternating current system. A 120-volt ac system for interior electrical devices shall be furnished and shall conform to the requirements of NFPA No.70 (National Electrical Code). The system shall be complete and shall include a panel enclosure with not less than six circuit breakers. a junction box. receptacles with ground fault circuit interrupters, power supply and other equipment as specified herein.

* 3.5.9.1.1 Outside receptacle. A weatherproof, heavy duty, receptacle with a hinged, spring-loaded, gasketed cover shall be mounted on the outside of the body front wall, not more than 6 feet above the ground, near the curb (right) side. The receptacle shall be rated at 120 volt with a capacity of not less than 60 amperes. A matching cable plug with a self-locking device shall be furnished.

* 3.5.9.1.2 Interior receptacles. Four 120-volt, 20-ampere rated, duplex receptacles with ground fault circuit interrupters shall be furnished and connected to the ac system at the junction box. Each receptacle shall be on a separate circuit and shall be protected by a separate 20-ampere circuit breaker. Two receptacles shall be placed on each side wall at a height of approximately 48 inches from the floor. The two receptacles on each side shall be equally spaced approximately 42 inches from the vertical centerline of the side wall. All receptacles and their respective circuit breakers shall be appropriately labeled for identification.

* 3.5.9.2 Direct current system. A power supply shall be furnished to convert the 120-volt ac (see 3.5.9.1) to 12 volts dc. The power supply shall have sufficient output capacity to operate the exhaust fan specified in 3.5.9.2.1 and the domelights (dc) specified in 3.5.9.3.1. The power supply shall be mounted in a single housing and shall be installed on the front wall within the van body.

3.5.9.2.1 Exhaust fan. A 12-volt dc exhaust fan with a capacity of not less than 220 cubic feet per minute shall be furnished and mounted inside the van body on the streetside of the rear wall. A selector switch shall be provided to connect the fan to either the vehicle chassis 12-volt system or the dc system specified in 3.5.9.2. The fan selector switch shall be appropriately labeled and installed on the power supply housing. The exhaust fan shall be provided with a shroud or other means for ensuring personnel safety.

3.5.9.3 Interior lighting. Interior lighting shall be provided by eight domelights arranged as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.5.9.3.1 Domelights (dc). Two 12-volt domelights shall be connected to the vehicle chassis electrical system. A single switch to control both lights shall be located inside the body and adjacent to the streetside rear door. The switch shall be appropriately labeled. In addition, a separate switch shall be provided on one of the domelights to control these lights. Dome lights shall be located centrally along the longitudinal axis and 18 inches from the front and rear walls.

* 3.5.9.3.2 Domelights (ac). Six 120-volt domelights shall be connected to the ac system. Not less than two switches, each protected by a separate 20-ampere circuit breaker, shall be provided for the domelights and shall be appropriately labeled. Switches shall be located inside the body and adjacent to the road street (left side) rear door. Three domelights shall be located approximately 18 inches inward from each interior side wall and approximately equally spaced between the front and rear walls.

3.5.10 Detachable access ladder. A detachable access ladder of the flatstep type and of lightweight metal construction shall be provided for use by personnel in entering and leaving the van body. Ladder steps shall be self-cleaning with an antiskid surface. The ladder shall support a static load of 350 pounds centrally located on any single step without failure. The ladder side members shall be designed to provide not less than a 30-degree slope from the vertical and to eliminate tripping hazards. The top step of the ladder shall be not more than 1 inch below the bottom edge of the rear door. The top of the ladder and the lower frame of the rear main door shall include a means for securing the ladder when in use. Stowage for the ladder shall be furnished on the outside of the body, accessible from the ground, at the rear of the vehicle.

3.5.11 Rear bumper. Rear bumperettes shall be provided.

3.5.12 Space heater. When specified (see 6.2), a gasoline-fired space heater or when specified, (see 6.2), a diesel fuel fired space heater shall be installed at the front of the van body interior. A separate fuel tank shall be furnished and shall provide for full operation of the heater for not less than 8 hours. An identification plate shall be permanently attached and located near the fuel tanks and shall indicate the type of fuel to be furnished. The plate shall conform to composition A (class l or 2) or composition C of MIL-P-514. The heater shall have a capacity to maintain the van body interior at 70°F in an ambient temperature of minus 10°F. The heater shall be provided with a high and low heat selector switch, a thermostatically controlled on-off switch or an infinitely variable switch to control van body interior temperature. The heater and installation shall conform to Federal Motor Carrier Safety Regulation 393.77.

3.6.13 Body mounting. The body shall be secured with U-bolts, twin studs, brackets, or J-bolts, and shall include wood breaker strips.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.5.13.1 U-bolts or twin Studs. When U-bolts or twin studs are used, there shall be not less than three U-bolts or twin studs per side, with each having a 9/16-inch minimum body diameter and 5/8-inch minimum thread diameter. Tie plates shall be at least 1/2 inch thick. The vehicle chassis frame shall be braced using wood blocks at each mounting point, unless the mounting point is located at a full-depth frame crossmember. Blocks shall incorporate a keeper strap or groove for the mounting bolt and shall be of a width and thickness to assure retention. Two tie-back straps shall be provided, one bolted to each side of the rear portion of the body subframe, to maintain body alinement on the vehicle chassis. Forward body mounting bolts shall be located to the rear of the tapered portion of the breaker strips (see 3.5.13.4).

3.5.13.2 Brackets. When brackets are used, they shall be bolted to the web of the chassis frame rails. The body mounting brackets shall provide a means of drawing down the body on the chassis rails, and provisions shall be made to prevent lateral shifting of the breaker strips. When additional holes are required to secure the mounting brackets to the chassis frame rails, they shall be located within the area of the rail which is designated as being safe for drilling in accordance with the chassis manufacturer's body builder's layouts. Attachments shall neither interfere with nor obstruct existing chassis components.

3.5.13.3 J-bolts. When J-bolts are used, there shall be not less than 7 J-bolts per side, each not less than 3/8 inch in diameter. J-bolts shall encircle the lower chassis frame flange. Two tie-back straps, as specified in 3.5.13.1, shall be provided. The forward J-bolts shall be located to the rear of the tapered portion of the breaker strips (see 3.5.13.4). Provisions shall be made to prevent lateral shifting of the breaker strips.

* 3.5.13.4 Breaker strips. A hardwood or dense southern yellow pine breaker strip, of not less than 3/4 inch finished thickness, shall be installed between the longitudinal sills and the vehicle chassis frame. The minimum thickness specified shall be increased as may be required to provide adequate tire chain-to-body clearance. Breaker strips shall have a taper of not less than 1/2 inch in 16 to 18 inches at the forward end.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of lights; adjustment of the engine and brake systems; filling and charging of the battery; alinement of the front wheels; inflation of all tires; complete lubrication of chassis, engine, and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of the cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examination and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility of compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine the curb weight and distribution of the curb weight on front and rear axles. The total imposed loading on front and rear axles shall be computed by the contractor and verified by the Government, using

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

the curb weight, the operator weight at 175 pounds and the payload required to provide the specified GVW. The calculated imposed loads on the front and rear axles shall be compared to the suspension, axle and tire load capacity ratings to determine if these components are of adequate capacity to meet contractual requirements.

* 4.3.2 Road test.

4.3.2.1 Road test model 4x2. The first production vehicle, for model 4x2, shall be examined and road tested (less payload) by the contractor to assure that the vehicle will operate in accordance with contractual requirements. The road test shall be for not less than 10 miles at speeds up to 50 mph.

4.3.2.2 Road test model 4x4. The first production vehicle, for models built to all wheel drive (model 4x4) while on the chassis manufacture's production line, shall be road tested by the contractor without payload. The road test shall be for not less than 10 miles at speeds up to 55 mph. The vehicle, for all wheel drive models qualifying under 3.1.1.12, shall be road tested with and without payload. Payload shall be distributed first, so that the front axle is loaded to GAWR and the vehicle is loaded to GVW and second, with the rear axle loaded to GAWR and the vehicle loaded to GVW. The road test for each of the three conditions shall be for not less than 30 miles at speeds up to 50 mph over highways and gravel roads and for not less than 5 miles at speeds up to 15 mph over cross country terrain with ground and grade requiring all wheel drive. During the loaded and empty portions of the road test, the brakes shall be applied firmly, bringing the vehicle to a sudden stop not less than 5 times during each portion of the road test. During the road test, the front and rear suspension of the drivetrain shall be periodically inspected for interference and contact with other vehicle components. Abnormal contact of the drivetrain or suspension components with other components shall be cause for rejection. Front spring bumpers shall not make contact with frame stops except under the most extreme cross country conditions. Operational or mechanical failures of vehicle components during the road test shall be cause for rejection. Failure includes permanent deformation as well as breakage.

* 4.3.3 Truck body treatment and painting. The certification regarding the body cleaning, treating, prime painting and salt spray resistance testing, as required by MIL-STD-1223, shall be made to Government representatives at the first production vehicle inspection.

4.3.4 Wood treatment certification. Manufacturer's records acceptable to the Government shall be furnished to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

5. PREPARATION FOR DELIVERY

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6 NOTES

6.1 Intended use. The vehicle covered by this specification is intended for general nontactical use by the Government in transporting personnel or cargo.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Model of vehicle required (see 1.2).
* (c) Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(d) Identification of appropriate service for painting and marking (see 3.1.1.1).
(e) Concealed markings, if required (see 3.1.1.1).
(f) Rustproofing, if required (see 3.1.1.2).
(g) Tropical rustproofing, if required (see 3.1.1.2).
(h) Drive hubs, if required for 4x4 model vehicles (see 3.1.1.6).
(i) Lighting cable, if required (see 3.1.1.8).
(j) Electric trailer brake controller, if required (see 3.1.1.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

* (k) Satisfactory operation on JP-4, JP-5 and JP-8 fuels, if required (see 3.4.1.1).
(l) Gasoline engine, if required (see 3.4.1.2).
* (m) Power plant heaters, if required (see 3.4.1.8).
(n) If a battery heater is not required (see 3.4.1.8).
(o) Auxiliary 24-volt system with trailer receptacle assembly, if required (see 3.4.2.6).
(p) Automatic or semiautomatic transmission, if required (see 3.4.5.3).
* (q) Oil lubricated wheelbearings and axle spindles if required (see 3.4.9)
(r) Two-speed axle for 4x2 model vehicles, if required (see 3.4.9.1).
(s) Traction control, if required for model 4x2 (see 3.4.9.2).
(t) Wide base tires and wheels in lieu of duals, if required (see 3.4.10).
(u) Disc type wheels, if required (see 3.4.10).
(v) Bias ply tires, if required (see 3.4.10.1).
(w) Spare tire carrier, if required (see 3.4.10.3).
(x) Spare wheel or rim, if required (see 3.4.10.4).
(y) Spare tire assembly, if required (see 3.4.10.5).
(z) Brake controls for use from a towing vehicle, if required (see 3.4.11.3).
(aa) Tilting hood and fender assembly, if required (see 3.4.12).
(ab) Individual driver and passenger seats, if required (see 3.4.12.1).
(ac) Air ride driver's seat, if required (see 3.4.12.1)
(ad) A crew cab, if required (see 3.4.12.2).
(ae) Tools, if required (see 3.4.16.1).
* (af) Gages if required in lieu of indicators (see 3.4.19).
* (ag) Automatic engine shutdown system, if required (see 3.4.19).
(ah) Air operated horn, if required (see 3.4.21).
(ai) Front mounted winch, if required (see 3.4.22).
(aj) Engine hour meter, if required (see 3.4.23).
(ak) Back-up alarm, if required (see 3.4.24).
(al) Body wind deflector fairing, if required (see 3.5.4).
(am) Gasoline-fired space heater, if required (see 3.5.12).
(an) Diesel fuel fired space heater, if required (see 3.5.12).

* 6.3 Performance prediction. SAE Truck Ability Prediction Procedure computations and computations for low speed and maximum geared speed will be required by the contractor. The SAE Work Sheet Item 1 should include vehicle model number, engine model number, and vehicle type and class. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry, air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE Truck Ability Prediction Procedure Tables:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00
Table 3	- Rolling Factor. 1.613
Table 4	- Area Factor. 0.173
Table 5	- Velocity Factor. 250.0
Table 6	- Altitude Factor. 1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, tabulated 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, factors shall be extrapolated.
Table 8	- Grade Factor. 0.75
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

* 6.4 Subject term (key word) listing.

Air pollution control
Auxiliary rear door
Electrical system 120-Vac/12-Vdc
Exhaust fan
Insulation
Space heater
Truck, van, shop
Van body wind deflection
Windows
Window regulators.

6.5 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the previous issue.

Custodians:
Army - AT
Air Force - 99

Review activity:
Air Force - 84

Preparing activity:
Army - AT

Project No. 2320-0420

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:31Z
Check the source to verify that this is the current version before use.