INCH-POUND
MIL-M-38510/206C
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION

Inactive for new design as of 24 July 1995

MICROCIRCUITS, DIGITAL, 4096-BIT SCHOTTKY, BIPOLAR, PROGRAMMABLE READ-ONLY MEMORY (PROM), MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/206C, dated 10 September 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add case outline "U" to paragraph 1.2.3 to read as follows:

1.2.3 Case outlines. The case outlines are as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
E	GDIP1-T16 or CDIP2-T16	16	dual-in-line
F	GDFP2-F16 or CDFP3-F16	16	flat pack
V	GDIP1-T18 or CDIP2-T18	18	dual-in-line
Y	See figure 1	24	square chip carrier
Z	See figure 1	18	flat pack
U	GDFP2-F18	18	flat pack

PAGE 2

Paragraph 1.3, Absolute maximum ratings, change Thermal resistance to read as follows:

Thermal resistance, junction-to-case (Θ_{JC}) 1/:
Cases E, F, V, and U - See MIL-STD-1835

PAGE 3

Change paragraph 3.2.4 to read as follows:

3.2.4 Case outlines. The case outlines shall be in accordance with MIL-STD-1835 and 1.2.3 herein.

PAGE 7

For FIGURE 2. Terminal connections. under Device types 01, 02 and 04 change as follows:

Delete Cases V and Z and replace with Case V, Z and U

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:48Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - AR, MI, SM
Navy - AS, SH, CG, MC
Air Force - 19, 99

Preparing activity:
DLA-CC

(Project 5962-1866)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:48Z
Check the source to verify that this is the current version before use.