NNN-T-698
February 20, 1963
SUPERSEDING
Fed. Spec. GG-T-696b
April 28, 1960

FEDERAL SPECIFICATION

TRIPOD, LABORATORY APPARATUS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers tripods suitable for ordinary laboratory use.

1.2 Classification.

1.2.1 *Types and sizes.* Laboratory tripods covered by this specification shall be of the following styles and diameters, as specified (see 6.1).

Style A—Plain ring.

(*Outside diameter*)

Inches
3-5/8
5
6
8
10

Style B—Concentric ring.

(*Outside diameter*)

Inches
5
6
8
10

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

QQ-I-666—Iron Castings, Malleable.
QQ-I-686—Iron, Wrought (Refined); Bars.
UU-T-111—Tape; Paper, Gummed (Sealing and Securing).
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636—Box, Fiberboard.
PPP-B-676—Boxes, Set-Up, Paperboard.
PPP-C-843—Cushioning Material, Cellulosic

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specifications:

MIL-B-121—Barrier Material, Greaseproofed, Waterproofed, Flexible.

MIL-C-16173—Corrosion Preventive Compound, Solvent Cutback, Cold-Application.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Uniform Freight Classification Rules.

(Application for copies should be addressed to Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

National Bureau of Standards publication:

Handbook H28—Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington 25, D. C.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 *Rings.* The rings shall be made of ungalvanized malleable iron conforming to the requirements of grade I or II of QQ-I-666.

3.1.2 *Legs.* The legs shall be made of coppered steel or of wrought iron conforming to the requirements of grade C of QQ-I-686.

3.2 Design and dimensions.

3.2.1 *Rings.* The rings shall have a flat level top with a 1/4-inch±1/32-inch inset flange along the inner border. Inset flange is not required on 3-5/8-inch size. The under surface of the outer ring only shall be provided with 3 equally spaced threaded bosses 0.038±0.002 inch from the outer edge. The bosses shall be bored and tapped from the underside to accommodate the threaded detachable legs. Each boss shall have at least 5 complete threads. Dimensions shall conform to the requirements of table I.

3.2.2 *Legs.* The legs shall be round and threaded in accordance with Screw-Thread Standards for Federal Services, National Coarse Thread Series, Handbook H28 for a minimum of 6 threads to fit into those in the rings. Legs shall extend from bosses at such an angle to insure dependable stability. Dimensions shall conform to the requirements of table I.

3.3 Finish. Rings and legs of style A tripod shall have a blacked baked enamel, grey hammertone or other suitable finish. Style B tripod rings shall have a grey or black baked enamel or other suitable finish. Style B tripod legs shall have a cadmium, copper, or zinc-coated or other suitable finish.

3.4 Marking. Each tripod shall be legibly and permanently marked with the name or registered trademark of the manufacturer.

3.5 Workmanship. Tripods shall be symmetrically made and smoothly finished. They

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

TABLE I.—*Dimensions of rings and legs*

Style	Outside diameter of ring	Inside diameter of ring	Inside diameter of smallest ring	Overall height	Diameter of leg	Number of loose rings
	Inch	*Inch*	*Inch*	*Inch*	*Inch*	
A	3 5/8	2 1/2	—	5 1/2*	5/16	—
	5	3	—	9	5/16	—
	6	4 1/2	—	9	5/16	—
	8	6	—	9	5/16	—
	10	8	—	9	5/16	—
B	5	—	2	9	5/16	1
	6	—	2	9	5/16	2
	8	—	2	9	5/16	3
	10	—	2	9	5/16	4

Tolerance on dimensions ± 1/16 inch.

* Tolerance on overall height style A, 3-5/8 inch diameter ± 1/2 inch.

shall be free from defects (scratches, nicks, cuts) or contamination (grease or oil) which impair their serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES.

4.1 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to insure that supplies and services conform to prescribed requirements.

4.2 **Special provisions.**

4.2.1 *Alternative inspection (including testing) procedures.* The supplier may utilize any alternative inspection procedure which will assure equal or better quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 *Supplemental evidence.* The supplier shall present objective evidence as required by the Government representative that all requirements of section 3 and of section 5 have been met.

4.3 **Lotting.** A lot of tripods shall consist of those tripods of the same style and diameter made by one manufacturer and offered for shipment at one time.

4.4 **Sampling for nondestructive examination.** Sampling shall be conducted in accordance with MIL-STD-105.

4.5 **Examination.** Sample tripods and level A and level B preparation for delivery requirements shall be examined in accordance with the classification of defects and with MIL-STD-105.

4.5.1 *Classification of defects.*

4.5.1.1 *Tripods.*

Categories	*Defects*
Critical:	None defined
Major:	*AQL 4.0 percent defective*
101	Bosses not evenly spaced
102	Tripods unstable
103	Dimensions incorrect
104	Defects, (scratches, cuts, nicks)
105	Contamination (grease or oil)
106	Marking missing, illegible, incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

4.5.1.2 Levels A and B preparation for delivery (section 5).

Categories	*Defects*
Critical:	None defined
Major:	*AQL 2.5 percent defective*
101	Unit, intermediate, or shipping container not as specified
102	Number of tripods per intermediate container not as specified
103	Unlike tripods packaged per intermediate or shipping container
104	Closure of unit, intermediate, or shipping container not as specified
105	Unit, intermediate, or shipping container damaged
106	Cushioning material not as specified
107	Marking of unit, intermediate, or shipping container illegible, incorrect, or incomplete

5. PREPARATION FOR DELIVERY

For civil agency procurement, the definitions and applications of the levels of packaging and packing shall be in accordance with Fed. Std. No. 102.

5.1 **Packaging and preservation.** Packaging and preservation shall be level A or C, as specified (see 6.1).

5.1.1 *Level A.*

5.1.1.1 *Unit packaging.* Each disassembled tripod shall be packaged in an appropriate size box conforming to PPP-B-566, style I or II, type and class optional or PPP-B-676, type, class, and style optional. Unpainted threaded areas of legs and rings shall be preserved with a light application of preservative conforming to grade I of MIL-C-16173. Legs and rings shall be individually wrapped with barrier material conforming to type III, grade A, class 2 of MIL-B-121. The box shall be provided with fiberboard blocking or sufficient cushioning material conforming to type II, class B, of PPP-C-843 to prevent shifting of contents. Box closure shall be secured with tape conforming to UU-T-111.

5.1.1.2 *Intermediate packaging.* The number of unit packages specified (see 6.1) shall be intermediately packaged in a fiberboard box conforming to type I, class 1, style RSC of PPP-B-636. Each intermediate package shall contain only one style and diameter tripod. Box closure shall be in accordance with the appendix of the box specification.

5.1.2 *Level C.* Tripods shall be packaged in accordance with the manufacturer's commercial practice suitable for shipment from the supply source to the first receiving activity for immediate use.

5.2 **Packing.** Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 *Level A.* Tripods shall be packed in a box conforming to PPP-B-601, overseas type or PPP-B-621, class 2. As far as practical exterior containers shall be of uniform size and shape, be of minimum cube and tare, and contain identical quantities of like items. Gross weight shall not exceed the weight limitations of the applicable box specification and appendix thereto. Containers shall be closed and strapped in accordance with the applicable box specification and appendix thereto.

5.2.2 *Level B.* Tripods shall be packed in accordance with 5.2.1 except that shipping containers shall conform to PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, type I or II, class 1, style RSC, minimum bursting strength 275 pounds per square inch.

5.2.3 *Level C.* Tripods shall be packed to insure carrier acceptance and safe delivery at first domestic destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 **Marking.**

5.3.1 *Civil agencies.* In addition to any special marking required by the contract or order, marking shall be in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

5.3.2 *Military agencies.* In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Level of packaging and packing required.

(*c*) Style and diameter of tripod required.

(*d*) Number of unit packages per intermediate package required.

6.2 Military use. Items procured under this specification for military use are to be limited to the variety shown on the applicable military standard or military supply standard. Personnel of the military departments are requested to refer to those documents for guidance.

6.3 Transportation description. Transportation description applicable to this item is:

Tripods, NOIBN, steel, knocked-down flat.

Carload minimum weight 30,000 pounds.

Tripods, not otherwise indexed, steel, knocked-down flat.

Motor volume minimum weight 30,000 pounds.

6.4 Supersession data.

Superseded specification

GG-T-696b	NNN-T-698
Type I	None
Type II	Style A
—	3 5/8
Size 1	5
Size 2	6
—	8
—	10
None	Style B
	5
	6
	8
	10

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY CUSTODIANS:

Army—MU

Navy—Md

Air Force—DAY

OTHER INTERESTS:

Army—M O

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.