INCH-POUND

MIL-R-83725/3E
AMENDMENT 1
22 November 2000

MILITARY SPECIFICATION SHEET

RELAYS, VACUUM, SPDT, DC, 8 AMPERES

This amendment forms a part of MIL-R-83725/3E, dated 26 November 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, flange mount configuration, delete the ".70" relay actuator casing dimension and substitute ".75".

FIGURE 1, flange mount configuration, delete the ".63" coil lead length dimension and substitute ".25".

FIGURE 1, flange mount configuration, delete the "1.60" relay body length dimension and substitute "1.65".

PAGE 2

FIGURE 1, flangeless configuration, delete the ".73" relay actuator casing dimension and substitute ".78".

FIGURE 1, flangeless configuration, delete the ".63" coil lead length dimension and substitute ".25".

FIGURE 1, flangeless configuration, delete the "1.60" relay body length dimension and substitute "1.65".

Custodians:
Army-CR
Navy-AS
Air Force - 11
DLA - CC

Review Activities:
Navy-OS

Preparing activity:
DLA - CC

(Project 5945-1121-01)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:25Z
Check the source to verify that this is the current version before use.