NOT MEASUREMENT SENSITIVE

MIL-L-11484/148B
14 January 1994
SUPERSEDING
MIL-L-11484/148A
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, MERITORIOUS SERVICE MEDAL, U.S. PUBLIC HEALTH SERVICE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.



MATERIAL: Gilding Medal

DIMENSIONS:
HEIGHT (Overall): 9/64 inch (0.36 cm) (REF)
WIDTH (Overall): 21/32 inch (1.67 cm) (REF)
THICKNESS (At Edge): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)

FINISH: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:00Z
Check the source to verify that this is the current version before use.

2. Enameled areas shall be as indicated. The colors shall conform to the TIOH color chip numbers listed below or the standard sample.

COLOR	CHIP NO.
Maroon	6
Dark Blue	20
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH

Review activities:
DLA - CT

User activities:
Other - USPHS

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:00Z
Check the source to verify that this is the current version before use.