NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/149B
27 September 1996
SUPERSEDING
MIL-L-11484/149A
14 January 1994

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, DEFENSE INTELLIGENCE DIRECTOR'S AWARD,
DEFENSE INTELLIGENCE AGENCY

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Overall): 25/32 inch (1.98 cm) (REF)
WIDTH (Overall): 11/16 inch (1.75 cm) (REF)
THICKNESS (At Thickest Point): 0.110 inch ± 0.010 inch (0.274 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:01Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
DIA - DI

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0858)


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:01Z
Check the source to verify that this is the current version before use.