NOT MEASUREMENT SENSITIVE

MIL-L-11484/150A
29 January 1991
SUPERSEDING
MIL-L-11484/150
12 December 1986

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, FEDERAL SERVICE AND RETIRED, OPM

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation:

MATERIAL: Red brass

DIMENSIONS:
HEIGHT: 5/8 inch (1.59 cm) (REF)
THICKNESS: .075 inch ± .010 inch (0.190 cm ± 0.025 cm)

FINISH: Gold plated, sating finish, highlights polished.

NOTES:
1. The attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.
2. Each lapel button shall be mounted and centered on a sulfite board 0.030 inch (0.076 cm) in thickness (minimum) and approximately 3-3/4 inches (9.53 cm) in length by 2-1/4 inches (5.72 cm) wide. The face of the sulfite board shall be covered with cobalt blue flock. The mounted sulfite board shall be placed in a rigid hinged plastic box having a transparent lid and opaque white bottom section. The box shall have two plastic hinges and catches and shall be approximately 3 inches (7.62 cm) in length and 1-1/4 inches (3.18 cm) wide and 3/4 inch (1.91 cm) in overall depth.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0567)

User activity:
Other - GSA

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:01Z
Check the source to verify that this is the current version before use.