NOT MEASUREMENT SENSITIVE

MIL-L-11484/150B
14 January 1994
SUPERSEDING
MIL-L-11484/150A
29 January 1991

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, FEDERAL SERVICE AND RETIRED, OFFICE OF PERSONNEL MANAGEMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

FINISH: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS: 0.075 inch ± 0.005 inch (0.191 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T17:01Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball type clutch or pin and catch as specified by the contracting officer. When a prong with pick and flat ball type clutch is specified, the prong shall be centered on the reverse side and fused or soldered to the lapel button. When a pin and catch is specified, the pin shall be mounted on the vertical center line with the catch on the bottom of the lapel button.

3. For packaging, each finished lapel button shall be mounted and centered on a sulfite board with a minimum thickness of 0.030 inch (0.076 cm) and approximately 3-3/4 inches (9.53 cm) in length by 2-1/4 inches (5.72 cm) wide. The face of the sulfite board shall be covered with cobalt blue flock. The mounted sulfite board shall be placed in a rigid hinged plastic box having a transparent lid and opaque white bottom section. The box shall have two plastic hinges and catches and shall be approximately 3 inches (7.62 cm) in length and 1-1/4 inches (3.18 cm) wide and 3/4 inch (1.91 cm) in overall depth.

Custodians:
Army - IH

Review activities:
DLA - CT

User activities:
Other- GSA

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil - Downloaded: 2026-10-17T17:01Z
Check the source to verify that this is the current version before use.