INCH-POUND

MS3120G
29 April 2009
SUPERSEDING
MS3120F
6 June 2003


DETAIL SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, CRIMP TYPE, WALL MOUNTING, FLANGE, NO. 4 HOLES, BAYONET COUPLING, SERIES 1, CLASSES E, F AND P

Inactive for new design after 5 September 1975.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-26482.



STYLE P (PIN INSERT)

FIGURE 1. Receptacle, dimensions, classes E, F and P.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.




FIGURE 1. Receptacle, dimensions, classes E, F and P – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.

Shell size	A dia +.001 -.005 OD	B +.006 -.002 bay pin dia	C dia +.000 -.016 over bay pins	D dia +.005 -.001 ID	H +.000 -.020 socket insert location
8	.473	.078	.563	.362	.025
10	.590		.680	.490	
12	.750		.859	.607	
14	.875		.984	.732	
16	1.000		1.108	.857	
18	1.125		1.233	.962	
20	1.250		1.358	1.087	.087
22	1.375		1.483	1.212	
24	1.500	.125	1.610	1.337	

Shell size	I max insert dia	J ±.010 packing location	JJ +.000 -.020 pin insert location	K +.016 thick mounting flange	M +.031 -.000 mounting flange location
8	.285	.382 (9.70)	.332 (8.43)	.062 (1.57)	.431 (10.95)
10	.402				
12	.516				
14	.641				
16	.766				
18	.855				
20	.980	.444 (11.28)	.394 (10.01)	.094 (2.39)	.556 (14.12)
22	1.105				
24	1.229				.589 (14.96)

FIGURE 1. Receptacle, dimensions, classes E, F and P – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.


Shell size	Q +.005 -.006 dia over keyways	R (TP) mounting holes	S max length side	T ±.005 dia mounting holes	U +.010 -.020 pin contact location
8	.412	.594	.828	.120 (3.05)	.085 (2.16)
10	.540	.719	.954		
12	.689	.812	1.047		
14	.814	.906	1.141		
16	.939	.969	1.234		
18	1.039	1.062	1.326		
20	1.164	1.156	1.453		.147 (3.73)
22	1.289	1.250	1.578		
24	1.414	1.375	1.703	.147 (3.73)	

Shell size	W (TP) bay pin location	Z +.000 -.078 socket contact spring location (see note 2)	V V class 2A accessory thread	EE min edge dist
8	.100 (2.54)	.153 (3.89)	7/16-28	.035 (0.89)
10			9/16-24	.035 (0.89)
12			11/16-24	
14			13/16-20	
16			15/16-20	
18			1-1/16-18	
20		.215 (5.46)	1-3/16-18	.050 (1.27)
22			1-5/16-18	
24	.109 (2.77)		1-7/16-18	

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Distance between end of shell and the point at which a gage pin having the same basic diameter as the mating contact and a square face first engages socket contact spring.
3. Packing material shall meet the requirements of ASTM-D2000.
4. True position (TP) tolerances specified are in accordance with ASME Y14.5M.

FIGURE 1. Receptacle, dimensions, classes E, F and P – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.




Shell size	HH max ID gasket	P max
8	.329 (8.36)	.087 (2.21)
10	.457 (11.61)	
12	.564 (14.33)	
14	.689 (17.50)	
16	.814 (20.68)	
18	.907 (23.04)	
20	1.039 (26.39)	.212 (5.38)
22	1.164 (29.57)	
24	1.289 (32.74)	

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Intermateability dimensions shall be in accordance with MIL-DTL-26482.

FIGURE 2. Panel dimensions, classes E, F and P.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.




Shell size	L max over-all length	X dia min ID	Y dia max OD
8	1.552 (39.42)	.259 (6.58)	.608 (15.44)
10		.359 (9.12)	.734 (18.64)
12		.469 (11.91)	.858 (21.79)
14		.589 (14.96)	.984 (24.99)
16		.717 (18.21)	1.110 (28.19)
18		.779 (19.79)	1.234 (31.34)
20	1.709 (43.41)	.901 (22.89)	1.360 (34.54)
22		1.009 (25.63)	1.484 (37.69)
24		1.123 (28.52)	1.610 (40.89)


NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Intermateability dimensions shall be in accordance with MIL-DTL-26482.

FIGURE 3. Receptacle, dimensions, class E.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.



Bushing installed



Bushing removed

FIGURE 4. Receptacle, dimensions, class F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.


Shell size	L max over-all length	X dla min open	Y max	V max closed
8	2.422 (61.52)	.234 (5.94)	.828 (21.03)	.187 (4.75)
10		.297 (7.54)	.891 (22.63)	.187 (4.75)
12		.422 (10.72)	1.016 (25.81)	.281 (7.14)
14		.547 (13.89)	1.141 (28.98)	.325 (8.26)
16	2.537 (64.44)	.609 (15.47)	1.203 (30.56)	.356 (9.04)
18		.734 (18.64)	1.469 (37.31)	.456 (11.58)
20	2.824 (71.73)			.519 (13.18)
22		.922 (23.42)	1.656 (42.06)	
24	2.900 (73.66)	.984 (24.99)	1.750 (44.45)	.657 (16.69)

Shell size	N free dia (see note 4)	ZZ screw threads	YZ lock washers NASM35338 or NASM35333
8	.125 (3.18)	6-32 UNC	NASM35338 -98 or -41 NASM35333 -105 or -37
10	.188 (4.78)		
12	.312 (7.92)		
14	.375 (9.53)		
16	.500 (12.70)		
18	.625 (15.88)	8-32 UNC	NASM35338 -99 or -42 NASM35333 -106 or-38
20	.625 (15.88)		
22	.750 (19.05)		
24	.800 (20.32)		

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Intermateability dimensions shall be in accordance with MIL-DTL-26482.
3. Use MS3420 bushing if reduced opening is required.
4. Lockwashers may be captivated.

FIGURE 4. Receptacle, dimensions, class F – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.



Shell size	L max over-all length	X dia min ID	Y dia max OD	PP min
8	1.675 (42.55)	.317 (8.05)	.608 (15.44)	.250 (6.35)
10		.434 (11.02)	.734 (18.64)	
12		.548 (13.92)	.858 (21.79)	
14		.673 (17.09)	.984 (24.99)	
16		.798 (20.27)	1.110 (28.19)	
18		.899 (22.83)	1.234 (31.34)	
20	1.963 (49.86)	1.024 (26.01)	1.360 (34.54)	
22	1.963 (49.86)	1.149 (29.18)	1.484 (37.69)	
24	2.025 (51.44)	1.274 (32.36)	1.610 (40.89)	

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Intermateability dimensions shall be in accordance with MIL-DTL-26482.

FIGURE 5. Receptacle, dimensions, class P – Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figures 1 through 5.
Connector mating: This connector mates with MS3121 and MS3126.
Insert arrangement shall be in accordance with MIL-STD-1669.
Sealing member: Bonded to vitreous insert.
Packing material shall meet the requirements of ASTM-D2000.
Finishes: A finish designator shall not be included in the PIN when finish W is required.
See MIL-DTL-26482 for available finishes D, T and Z for classes E, F and P.
Material:

a. Shell - aluminum alloy.
b. Bayonet pins (B dia) - stainless steel, passivated.

Part or Identifying Number (PIN) example:



Note: No finish designator is used when finish W is required (finish W is the default finish).

Changes from previous issue: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents: In addition to MIL-DTL-26482, this document references the following:

MIL-STD-1669
MS3121
MS3126
SAE-AS39029/31
SAE-AS39029/32
ASME Y14.5M
ASTM D2000
NASM35333
NASM35338

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2007-181)

Review activities:
Army - CR4, MI
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.