

FED. SUP. CLASS.
5305





ACCEPTABLE CUP POINT DESIGNS

			#2 (.080)	#4 (.112)	#6 (.138)	#8 (.164)	#10 (.190)
D	Nominal Size						
B	Threads Per Inch		56NC-3A	40NC-3A	32NC-3A	32NC-3A	24NC-3A
J	Width of Socket Across Flat	MAX	.0355	.051	.0635	.0791	.0947
		MIN	.035	.050	.0625	.0781	.0937
C	Diameter of Point	MAX	.047	.061	.074	.087	.102
		MIN	.039	.051	.064	.076	.088
T	Key Engagement	MIN	.028	.040	.050	.062	.075

L Length	Tolerance	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN
1/8		1		9		20		33			
3/16		2		10		21		34		46	
1/4		3		11		22		35		47	
5/16	± 1-1/2% of L with a minimum of ± .010 in.			12		23		36		48	
3/8				13		24		37		49	
7/16				14		25		38		50	
1/2				15		26		39		51	
5/8				16		27		40		52	
3/4						28		41		53	
7/8						29		42		54	
1						30		43		55	
1-1/4										56	

KEY ENGAGEMENT: THESE DIMENSIONS APPLY TO SCREWS ONE DIAMETER IN LENGTH OR LONGER. FOR SCREWS SHORTER THAN ONE DIAMETER IN LENGTH, SOCKET TO BE AS DEEP AS PRACTICABLE.
MATERIAL: STEEL, HIGH-GRADE ALLOY, IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
HARDNESS: SETSCREWS SHALL BE HARDENED BY HEAT TREATMENT TO A HARDNESS OF ROCKWELL C45 TO 53.
PROTECTIVE COATING: CADMIUM PLATED, IN ACCORDANCE WITH SPECIFICATION QQ-P-416, TYPE II, CLASS 3.
ZINC PLATED, IN ACCORDANCE WITH SPECIFICATION QQ-Z-325, TYPE II, CLASS 3.
THREADS: THE THREADS SHALL BE IN ACCORDANCE WITH SCREW-THREAD STANDARDS FOR FEDERAL SERVICES HANDBOOK H-28.
DIMENSIONS: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
PART NUMBER: THE MS PART NUMBER CONSISTS OF THE MS NUMBER, PLUS THE DASH NUMBER. EXAMPLE: MS51017-1.
NOTES: (1) REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
(2) THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

APPROVED 7 MAY 1958 REVISED

THIS DOCUMENT HAS BEEN PROMULGATED BY THE DEPARTMENT OF DEFENSE AS THE MILITARY STANDARD TO LIMIT THE SELECTION OF THE ITEM, PRODUCT, OR DESIGN COVERED HEREIN IN ENGINEERING, DESIGN, AND PROCUREMENT. THIS STANDARD SHALL BECOME EFFECTIVE NOT LATER THAN 90 DAYS AFTER THE LATEST DATE OF APPROVAL SHOWN.

CUSTODIANS	OTHER INT.
A - ORD	A- CESIGT
N - SHIPS	N- AMCOR
AF - USAF	AF-

MILITARY STANDARD

SETSCREW, HEXAGON SOCKET, CUP POINT, ALLOY STEEL, CADMIUM OR ZINC, NC-3A AND UNC-3A

MS51017

PROCUREMENT SPECIFICATION: FF-S-103
SUPERSEDES:
SHEET 1 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:53Z
Check the source to verify that this is the current version before use.

DD FORM 1 OCT 52 672-1

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

FED. SUP. CLASS.
5305

D Nominal Size	1/4	5/16	3/8	7/16	1/2
B Threads Per Inch	20UNC-3A	18UNC-3A	16UNC-3A	14UNC-3A	13UNC-3A
J Width of Socket Across Flat, Max	.127	.1582	.1895	.2207	.2520
J Width of Socket Across Flat, Min	.125	.1562	.1875	.2187	.2500
C Diameter of Point, Max	.132	.172	.212	.252	.291
C Diameter of Point, Min	.118	.156	.194	.232	.270
T Key Engagement, Min	.100	.125	.150	.175	.200

L Length	Tolerance	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN
3/16	± 1-1/2% of L with a minimum of ± .010 in.	62									
1/4		63		81		99					
5/16		64		82		100					
3/8		65		83		101		118		135	
7/16		66		84		102		119		136	
1/2		67		85		103		120		137	
5/8		68		86		104		121		138	
3/4		69		87		105		122		139	
7/8		70		88		106		123		140	
1		71		89		107		124		141	
1-1/4		72		90		108		125		142	
1-1/2		73		91		109		126		143	
1-3/4		74		92		110		127		144	
2		75		93		111		128		145	
2-1/2	± 1/32					112		129		146	
3										147	

D Nominal Size	5/8	3/4	7/8	1
B Threads Per Inch	11UNC-3A	10UNC-3A	9UNC-3A	8UNC-3A
J Width of Socket Across Flat, Max	.3155	.378	.503	.5655
J Width of Socket Across Flat, Min	.3125	.375	.500	.5625
C Diameter of Point, Max	.371	.450	.530	.609
C Diameter of Point, Min	.347	.425	.502	.579
T Key Engagement, Min	.250	.300	.400	.450

L Length	Tolerance	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN	Dash No.	FIIN
1/2	± 1-1/2% of L with a minimum of ± .010 in.	153									
5/8		154		169							
3/4		155		170							
7/8		156		171		184					
1		157		172		185		197			
1-1/4		158		173		186		198			
1-1/2		159		174		187		199			
1-3/4		160		175		188		200			
2		161		176		189		201			
2-1/2	± 1/32	162		177		190		202			
3		163		178		191		203			

NOTE: FOR MATERIAL, PROTECTIVE COATING AND OTHER PERTINENT DATA, SEE SHEET 1.

APPROVED 7 MAY 1958 REVISED

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

CUSTODIANS: A - ORD; N - SHIPS; AF - USAF
OTHER INT.: A-CESIGT; N-AMCOR; AF-
PROCUREMENT SPECIFICATION: FF- S-103

MILITARY STANDARD

SETSCREW, HEXAGON SOCKET, CUP POINT, ALLOY STEEL, CADMIUM OR ZINC, NC-3A AND UNC-3A

SUPERSEDES:

MS51017

SHEET 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:53Z
Check the source to verify that this is the current version before use.