INCH-POUND


MIL-DTL-55302/143C
7 March 2005
SUPERSEDING
MIL-C-55302/143B
17 November 1988

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE WITH SOCKET CONTACTS, 3 KEYING GUIDES, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.



Inches	mm	Inches	mm
.050	1.27	.252	6.40
.100	2.54	.300	7.62
.122	3.10	.305	7.45
.153	3.89	.317	8.05
.200	5.08		
.248	6.30		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

FIGURE 1. Connector, plug (.100 inch spacing).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Arrangements and characteristics.

Contact arrangement	No of contacts	Dimensions (inches)	
		A MAX	B ± .006 (0.15)
M55302/143A	72	4.516 (114.70)	4.200 (106.68)
M55302/143B	84	5.114 (129.90)	4.800 (121.92)
M55302/143C	96	5.717 (145.20)	5.400 (137.16)




FIGURE 2. Recommended hole patterns.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Inches	mm
.002	0.05
.004	0.10
.031	0.79
.050	1.27
.087	2.21
.100	2.54
.110	2.79
.116	2.95
.118	3.00
.126	3.20
.150	3.81
.160	4.06
.200	5.08
.250	6.35
.300	7.62

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Metric equivalents are in parentheses.

FIGURE 2. Recommended hole patterns – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.





FIGURE 3. Contact arrangements and keying arrangements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




Inches	mm	Inches	mm
.003	0.08	.100	2.54
.008	0.20	.109	2.77
.011	0.28	.156	3.96
.018	0.46	.183	4.65
.020	0.51	.191	4.85
.022	0.56	.200	5.08
.023	0.58	.220	5.59
.063	1.60	.380	9.65
.069	1.75	.547	13.89


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Contact accepts no. 22 AWG wire.
5. Contact, crimp type, accepts no 22-26 AWG wires.
6. Contact with .025 (0.64 mm) wrappost.

FIGURE 4. Connector terminations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.



72 AND 84 CONTACTS
FIXED MOUNT



72, 84, AND 96 CONTACTS
FLOATING MOUNT

Inches	mm	Inches	mm
.004	0.10	.375	9.53
.005	0.13	1.93	49.02
.079	2.01	2.10	53.34
.116	2.95	2.23	56.64
.118	3.00	2.40	60.96
.126	3.20	2.53	64.26
.202	5.13	2.70	68.58

Number of Contacts	72	84	96
W minimum	1.93	2.23	2.53
X	2.10	2.40	2.70

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Floating mount panel thickness .085 (2.15 mm) maximum.

FIGURE 5. Recommended panel cutouts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1 through 5.

Contact identification: See figure 3.

Contact retention: 4 pounds minimum for each contact.

Contact engagement: 0.7 ounce minimum, 3.6 ounces maximum.

Contact separation: 0.5 ounce minimum.

Measured using test pins and procedures defined in MIL-DTL-55302/142.

Contact resistance: Shall not exceed 12 milliohms.

Dielectric withstanding voltage:

Sea level: 1,000 V rms, 60 Hz.

High altitude: 300 V rms, 60 Hz.

Current rating, maximum: 3.0 amperes.

Keying socket: Two hexagonal keyed guides provide 36 polarizing positions. Keys are constructed in accordance with M55302/154. Connectors are supplied with hex pins in the “1” and “A” positions, except for 1/4-turn locking styles, which are keyed in “F” and “6” positions. When required, connectors can be easily keyed to the desired position by using a standard wrench or screwdriver.

Crimping tools (for subparts 4 and 6):

Basic tool: M22520/2-01.

Positioner: M22520/2-36.

Hood types: See MIL-DTL-55302/155.

Mounting hardware: See MIL-DTL-55302/154.


Mating connectors: Shall conform to MIL-DTL-55302/141.

Oversize pin exclusion test: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): Consists of the letter M, the basic number of the specification sheet, and a dash number compiled as follows:

Example:



Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/141
MIL-DTL-55302/142
MIL-DTL-55302/154
MIL-DTL-55302/155

CONCLUDING MATERIAL

Review activities:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5935-4488-000)

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, OS, MC, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.