MIL-I-60476A(MI)
17 August 1979
Superseding
MIL-I-60476(MU)
15 July 1967

MILITARY SPECIFICATION

IGNITER, MARK 125 MOD 5, LOADING

ASSEMBLING AND PACKING

This specification is approved for use by the US Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense,

1. SCOPE

1.1 Scope. This specification covers the quality assurance provisions and special requirements not covered by the drawings for the type of igniter designated MARK 125 MOD 5.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-223	Power, Black
MIL-A-2550	Ammunition and Special Weapons, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Missile Command, ATTN: DRSMI-ESD(R&D), Redstone Arsenal, AL 35809, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

MIL-S-14977 - Squib, Mark 1 Mod 0 For 2.75 Inch Rocket

MIL-I-45607 - Inspection Equipment, Supply and Maintenance of.

MIL-I-60455 - Igniter, Mark 125 Mod 5, Parts for.

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

Navy

457888- Igniter MK125 MOD 5 Loaded Assembly
LD 267523 - Container MK 8, MOD 0

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with drawings and specifications specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

3.1.1 Charge. The charge shall consist of the proper ratio by weight of black powder, (80 + 2%), and coated magnesium powder (20 + 2%) evenly-blended. The igniter-charge weight shall be between 8.5 and 10.5 grams, Inclusive.

* 3.1.2 Moisture content. The moisture content of the black powder, as loaded, shall be 0.5% maximum.

* 3.2 Parts. The parts shall comply with all requirements specified in MIL-I-60455 MARK 125 MOD 5, Parts For.

* 3.2.1 S uib. The squib shall comply withall requirements specified in MIL-S-14977, Squib MARK 1 MOD O, For 2.75 Inch Rocket.

3.3 Igniter assembly. No powder grains shall be present at the contact surfaces of the cover and case before crimping. The completed Igniter assembly shall not evidence, on any external surface, any trace of explosive composition or extraneous material affecting use, safety, or appearance. A suitable shorting device or method shall be applied to the bare ends of the lead wires before storage and shipping.

* 3.4 Igniter functioning. The igniters, when subjected to a direct current (D.C.) firing current of 1.5 ± 0.15 amperes at the specified temperatures, shall function with no indication of ejects. Each Igniter shall function within the time spectfied in 4.3.3.5.

3.5 Transporation vibration. The igniters, after being subjected to conditions simulating those encountered in transportation and service, shall be airtight, have proper electrical continuity, and insulation resistance, and shall function at the three temperatures specified.

* 3.6 Airtightness. The igniter, after being vibrated and checked for electrical continuity, and insulation resistance, shall be subjected to the airtightness test and shall show no evidence of air leakage at normal room temperature of 70°F ± 10°F (21°C ± 5.5°C).

3.7 Workmanship Loading and assembling shall be accomplished in accordance with best practices. All parts shall be free of any foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches which do not expose base material. All required marking shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

3.8 First article inspection. This specification makes provisions for first article inspection. Requirements for the submissior of first article samples by the contractor shall be specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or Purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the Inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 in order to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.7 Submission of product At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the Information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units product inspected.

co Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of' the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.1.2 Government verification. Using the contractor's written quality assurance procedure, this detailed specification, the applicable drawings and other-contractual documents as a guide, the Government Inspector shall verify at unscheduled intervals, all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 First Article Inspection

*

4.2.1 First article sample. The contractor shall submit a first article sample of ninety (90) loaded assemblies and forty-five (45) unloaded assemblies to the Government for testing in accordance with the provisions of 4.2.2. All parts and materials shall be the same as will be used in production and shall be obtained from the same source of supply. Prior to submission, the sample shall be Inspected by the contractor to the degree necessary to assure that it conforms to the requirements of the contract. A first article sample or portion thereof, as directed by the contracting office, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect production uniformity as determined by the Government.

4.2.2. Inspections to be performed. Assemblies and components will be submitted by the Government to any or all of the examinations or tests specified in 4.3.2 and 4.3.3 of this-specification and any or all of the drawings.

4.2.3 Rejection If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article sample or portion thereof. Until a first article sample is accepted, the contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions for production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation. The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and Inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, specification or revision thereof. Changes to either the process, specification or drawing not affection safety, performance, interchangeability, or storage, as determined by the Government inspector, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168. Each loaded igniter lot shall consist of:

a. Parts from three lots or less from one interfix from one manufacturer.

b. Squibs from one interfix from one manufacturer.

Unless otherwise approved by the contracting officer, the inspection lot size of major assemblies or end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest quantity contractually scheduled for delivery during any month of the contract period, but never less than 1201 assemblies. Inspection lots for components or subassemblies, other than the items of delivery shall be homogeneous and of a size convenient to the contractor.

* 4.3.2 Examination. Sampling plans and procedures for the following classifications of defects shall be in accordance with MIL-STD-105 except that inspection for critical defects when listed, shall be 100 percent. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Once agreement has been reached as to which method will be used (Group or Individual) that method will be used for all of the classification of defects (CD's) listed in this specification. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.3.2.1 Igniter MK 125 MOD 5 loaded assembly (see dwg 457888).

Categories	Defects	Method of Inspection	Code No.
Critical:			
	1. Lead Wire ends not short circuited.	Visual	01006
	2. Presence of complete coined area	Visual	01007
Major:	AQL 0.65 percent		
	101. Cover crimp not continuous or not uniform	Visual	01001
	102. Evidence of scalloping or fractures on cover	Visual	01002
	103. Dip finish incomplete.	Visual	01003
* Minor:	AQL 1.5 percent		
	201. Marking missing, misleading, or unidentifiable	Visual	01004
*	202. Bare straight wire, length, min	Gage	01005
	203. Evidence of poor workmanship (see 3.7). .	Visual	01008

4.3.2.2 Igniter case and squib assembly (see dwg 457890 covering a detail of dwg 457888)

* Categories	Defects	Method of Inspection	Code No.
Major	AQL 0.65 percent		
	101. Distance, max, end of squib lead insulation in case and adjacent end of terminal tube	Gage	02002
	102. Lead wires soldered incorrectly	Visual	02003
	103. Insulating compound coating improper . . .	Visual	02004
	104. Insulating sleeves assembled improperly.	Visual	02005
*	105. Presence of insulating compound on coin or within periphery of the coin on Inside or outside of case	Visual	02006
*	106. Any portion of squib positioned over any portion of coined area of case	Visual	02008
* Minor:	AQL 0.65 percent		
	201. Evidence of poor workmanship (see 3.7). .	Visual	02007

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.3.2.3 Insulating sleeve (see dwg 1127334 covering a detail of dwg 457888

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
* Minor:	AQL 1.0 percent		
* 201.	length	Gage	03001
202.	Evidence of poor workmanship (see 3.7).	Visual	03002

4.3.2.4 Insulating sleeve (see dwg 1127337 covering a detail of dwg 457888).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
* Minor:	AQL 1.0 percent		
* 201.	Length	Gage	04001
202.	Evidence of poor workmanship (see 3.7).	Visual	04002

4.3.3 Testing

* 4.3.3.1 Electrical circuit and continuity test (see dwg 457888) - Major defect - Code No.01009 Each lot of igniters shall be tested as specified In 4.4.1 using equipment accordance with 4.3.4. The sampling plan for this test shall be in accordance with MIL-STD-105 using an AQL of 0.15 percent. If the sample fails the AQL reject level, the lot shall be rejected.

* 4.3.3.2 Insulation Breakdown Test (see dwg 457888) - Major defect - Code No, 01010. Using the acceptable samples from 4.3.3.1 test the igniters as specified In 4.4.2 using equipment in accordance with 4.3.4. An AQL of 0.15 percent applies. If the sample fails the AQL reject level, the lot shall be rejected. Samples from this test returned to the lot shall have the lead wire ends short circuited and verified by the Government representative prior to return to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.3.3.3 Transportation Vibration Test (see 3.5) Major defect - Lode No. 05001. Ninety acceptable igniters shall be randomly selected from the sample tested in para 4.3.3.1 and 4.3.3.2. This test shall be performed on every lot. The sample shall be tested as specified in 4.4.3 using equipment in accordance with 4.3.4. The selected igniters shall be numbered consecutively and their respective electrical circuit resistance and insulation breakdown determined before testing. Those vibrated and accepted, numbered 1-90, inclusive, shall be used for the Air Tightness Test (see 4.3.3.4) and the Functioning Test (see 4.3.3.5). For acceptance of the lot after vibration, no igniter circuit shall be found to fall outside the resistance limits of 0.7 ohms to 1.3 ohms, inclusive, and the electrical resistance between connected lead wires and any portion of the bared metal of the igniter case and cover shall be not less than 50,000 ohms, and no igniter shall have fired. Prior to subjection to the igniter functioning test, the samples shall be subjected to the airtightness test.

4.3.3.4 Airtightness Test (see 3.6) Major defect-code No. 06001. The iqniters, after meeting the requirements of the vibration test (see 4.3.3.3) shall be subjected to an airtightness test as specified in 4.4.4 using equipment in accordance with 4.3.4. The samples for this test shall be those samples chosen for vibration in para 4.3.3.3. Maximum allowable rejects is one.

* 4.3.3.5 Igniter Functioning Test (see 3.4) Major defect - code No. 07001. Igniters, after the vibration and airtightness tests, shall be subjected to the igniter functioning test as specified in 4.4.5 using equipment in accordance with 4.3.4. Those igniters previously passing the airtightness test shall be used for this test. All igniters shall fire. If one igniter fails to fire, the lot shall be rejected. For the purpose of assessment of the lot any igniter which exceeds 40 milliseconds shall cause rejection of the lot. The Mean Upper Limit of samples at all temperatures when computed individually shall be twenty-two (22) milliseconds. The Quality Index shall be calculated as described in MIL-STD-414 for each temperature. An estimate of Lot Percent Defective for any temperature as determined from Table B5 of MIL-STD-414 greater than 3.91 shall cause rejection of the lot. Evidence of ejecta from three or more igniters fired during this test shall reject the lot. After functioning, material missing from the igniter case shall be considered evidence of ejects. One or more failures of the squib face to an area equivalent to a circle with a diameter of O.10 inches (2.54 millimeters (min)) shall reject the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

* 4.3.3.6 Igniter Charge Weight Test (see 3.1.1) - Major Defect-Code No. 08001. Two samples per 2 hours of igniter production shall be tested for the proper weight of charge as specified in 4.4.6 (prior to canning) using equipment in accordance with 4.3.4. Any one weight not within tolerance limits specified shall cause the preceding 2 hours production to be rejected.

4.3.3.7 Igniter Charge Composition Test (see dwg. 457784) Major defect - Code No. 09001. Two samples per 8 hours of igniter production shall tested for the proper composition of the charge, as specified in 4.4.7 using equipment in accordance with 4.3.4. Any percentage exceeding those specified shall cause the preceeding 8 hours production to be rejected.

* 4.3,3.8 Moisture content determination, Two sample igniters from each four hours of production shall be tested for moisture content as specified in 3,1.2. The test shall be performed as specified in 4.4.8. Any igniter found to have black powder with excessive moisture will cause rejection of all igniters manufactured since the last test sample having proper moisture content.

* 4.3.4 Inspection equipment. The contractor shall design inspection equipment in accordance with instructions in 6,3.

* 4.3,4.1 Government rights to documentation. Inspection equipment drawings provided and revised in accordance with the requirements of this specification may be used by DoD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and wherever inspection equipment drawings are needed,

* 4.3.4.2 Supply and maintenance. Supply and maintenance of the inspection equipment shall be in accordance with MIL-I-45607.

4.3.4.3 Government use of contractor’s inspection equipment. The contractor shall make availa to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test methods and procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.4.1 Electrical Circuit and Continuity Test (see 4.3.3.1). The e actrical circuit of the igniter between the lead wires shall be continuous and shall be within the resistance limits of 0.70 ohms and 1.30 ohms inclusive. The equipment used in measuring the igniter electrical continuity and resistance shall not subject the igniter firing circuit to more than 25 (twenty-five) milliamperes,

4.4.2 Insulation Breakdown Test (see 4.3.3.2). The resistance between the connected lead wires, and any portion of the bare metal exposed on the igniter case or cover, shall not be less than 50,000 ohms.

* 4.4.3 Vibration Test (see 4.3.3.3) . All sample igniters shall be secured in suitable fixtures and subjected to a vibration of 2200 (twenty-two hundred) cycles per minute (CPM) for (40) forty minutes using a vertical amplitude of .031 inch ±.002 inch (0,7874 mm ±0.0508 mm) peak-to-peak. After vibration, the electrical resistance and Insulation breakdown resistance of each igniter shall be measured and recorded. For the purpose of testing and identifying the igniters for use in subsequent testing, the igniter shall be positioned and tested as follows:

IGNITER FUNCTIONING (see 4.3.3.5)

Axis Vertical- Insulated Terminal Down	1-10	31-40	61-70
Axis Vertical- Insulated Terminal Up	11-20	41-50	71-80
Axis horizontal-Insulated Terminal Up	21-30	51-60	81-90

4.4.4 Airtightness Test (see 4.3.3.4). This test consists of Placing the igniters in a pressure vessel connected to a source of Controlled air, water, or similar medium, and controlled to decrease the pressure at the igniter by 5 pounds per square inch (psi) (3,515.7 kg/meter $(m)^2$) when submerged In water. The air space above the water shall be evacuated by ap roximately 5 psi (3,515.7 kg/m2) below ambient for a minimum time of (5) five seconds. A wetting agent is permitted to lessen the adhesion of bubbles to the igniters. All such bubbles shall be eliminated before applying pressure, and assessing the igniters under test. A formation of bubbles on the igniter surface, or a steady flow of bubbles indicate air leakage. There shall be no evidence that water has entered the igniters. The igniters must be safe and operable following this test, and must be thoroughly dried for use in subsequent testing (see 4.4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

* 4.4.5 Igniter Functioning Test (see 4.3.3.5. Those igniters previously selected and accepted shall be temperature conditioned as follows:

	CONDITIONING TEMPERATURE		
	-65°F (-53.9°c)	+115°F (46.1°C)	+165°F (73.9°C)
Igniter Serial Number	1-10 11-20 21-30*	31-40 41-50 51-60*	61-70 71-80 81-90*

* In the event of 29 units at any temperature, Table B5 of MIL-STD-414 shall be read using sample size 30. Each igniter selected shall be conditioned to assume a uniform temperature throughout its entire mass at the time of firing. Minimum conditioning time shall be eight hours. Maximum conditioning time shall be twenty-four hours. During the last three hours of conditioning, the cabinet temperature shall be maintained within three degrees of the specified temperature. Any igniter not fired within five minutes shall be returned to the applicable conditioning cabinet for not less than one hour. Any igniter left out of the cabinet over five minutes before firing shall be placed at ambient temperature for not less than (12) twelve hours before reconditioning to the specified temperature. A direct current (DC) power supply shall provide a firing pulse of 1.5 ±0.15 amperes to the igniter circuit. The temperature and the functioning time shall be recorded for each igniter. Firing of the entire sample shall be completed regardless of when the rejection number occurs. Functioning time is that overall elapsed time between closing of the electrical firing circuit and the time when the igniter coined surface ruptures. The methods and apparatus used for this test shall be approved by the procuring activity.

4.4.6 Igniter Charge Weightiest (see 4.3.3.6). Igniter charge blend weight shall be determined by an average of duplicate weighings of the test samples, utilizing a calibrated analytical balance. Weighings should agree within ±0.1 grams of each other.

* 4.4.7 Igniter Charge Composition Test (see 4.3.3.7).

* 4.4.7.1 Charge Composition by Potassium Nitrate.

* 4.4.7.1.1 Percent Potassium Nitrate in Black Powder. A precisely known sample weight of black powder from thee lot of black powder used in the Igniters being tested) for approximately ten (10) grams shall be analyzed according to MIL-P-223 procedure 4.4.4.1.1. The percent potassium nitrate In the black powder shall be calculated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

4.4.7.1.2 Charge Composition. The full charge load from two (2) Igniters will be accurately weighted and individually analyzed for potassium nitrate composition according to MIL-P-223 Procedure 4.4.4.1.1 with the following modification: Extraction of the potassium nitrate will be performed with hot (55°-60°C) water and not brought to a boil as described in MIL-P-223. (Bolling water must be avoided as it reacts with the magnesium and leads to anomalous results.) Using the potassium nitrate content of black powder obtained in 4.4.7.1.1, the total black powder content of the igniter charge is then calculated. The magnesium content of the charge shall be taken as the difference between black powder content and total charge weight,

* 4.4.7.2 Charge Composition by Magnesium (alternate method).

* 4.4.7.2.1 Magnesium in Coated Magnesium. Determine the magnesium content in the lot of coated magnesium used in the production of the igntters being tested by the procedure described in 4.4.7.2.2 substituting a 2 gram sample of coated magnesium for the igniter charge load.

* 4.4.7.2.2 Charge Composition (alternate method). The full charge load from two (2) igniters shall be accurately weighed and individually analyzed for magnesium by the following procedure.

* Quantitatively transfer the full charge load from one igniter to a 1 Iiter volumetric flask. Add 50 milliliters concentrated hydrochloric acid, mix well and heat gently on a steam bath until all the magnesium is in solution. Add 300 milliliters of distilled water, mix, cool to room temperature, then dilute to 1 liter volume and mix well. Filter the solution through paper discarding the first 25 milliliters collecting about 100 milliliters. Transfer quantitatively by pipet 25.O milliliters of this solution to a 100 milliliters beaker, add 10 milliliters of pH 10 buffer (To 68 grams ammonium chloride add 570 milliliters concentrated ammonium hydroxide, then dilute to 1 liter with distilled water), then add 5 drops of Eriochrome Black T (EBT) indicator solution (dissolve 0.5 grams of EBT in 5 grams of hydroxylamine hydrochloride, then add 100 milliliters of alcohol) mix well. Titrate the mixture with standardized 0,1 N Ethylenediaminetetraaoetlc acid to the calorimetric end point. Calculate the percent coated magnesium in the igniter using the results of 4.4.7.2.1, above, for the percent magnesium in coated magnesium.

The black powder content shall be taken as the difference between the full charge and the amount of magnesium present.

* 4.4.8 Moisture content of black powder determination. Moisture content shall be in accordance with the method described in MIL-P-223. (The contractor may, with the approval of the Government Inspector, use some of the same charge samples used for igniter charge composition test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

* 5. PACKAGING

* 5.1 Packaging and packing of loaded igniters. Packaging and packing of loaded igniters for shipping shall consist of placing 336 igniters in Igniter Container Mark 8, Mod 0, BUORD LD267523.

5.2 Markin The exterior of each shipping container shall be correctly and legibly marked in accordance with MIL-STD-129 and I.C.C. regulations.

60 NOTES

6.1 Ordering data. Procurement documents should specify the follwing:

a. Title, number and date of this specification.

b. Data cards. Data cards shall be prepared for each lot in accordance with the information specified MIL-STD-1167.

* 6.2 Inspection code numbers. The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. All submitted designs shall contain a reference to the applicable 5 digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. These code numbers are used to correlate the characteristics with the inspections listed in this specification. They shall also be cited as referenced on drawings of equipment designs submitted by the contractor (see 6.3.1).

* 6.3 Contractor design. Special calibration and test equipment necessary to accomplish the requirements as stated herein may be designed and manufactured by the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibrating instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted Contractor designs shall conform to DOD-D-1000, LEVEL 2.

* 6.3.1 Submission of contractor design. All submitted designs shall contain a reference to the applicable paragraphs of this specification, and test equipment shall be approved by the Procuring Activity prior to

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

submission of first article sample. Partial submission of design is permissible. However, the completion date for design review will be based on the date of the final submission. Design review at the Procuring Activity will be accomplished approximately 30 days after receipt.

* 6.4 Submission of first articles samples. Instruction as to the location for the evaluation of the first article sample shall be obtained from the Contracting Officer. All inquiries should be forwarded to the address specified in the contract.

* 6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the past previous issue.

Custodian:
Army- MI

Preparing activity:
Army-MI

Project No. 1340-A468

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-I-60476A(MI) IGNITER, MARK 125 MOD 5, LOADING ASSEMBLING AND PACKING

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A GIVE PARAGRAPH NUMBER AND WORDING

   B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.

FOLD

Commander
US Army Missile Command
ATTN: DRSMI-ESD(R&D)
Redstone Arsenal, AL 35809

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

Commander
US Army Missile Command
ATTN: DRSMI-ESD (R&D)
Redstone Arsenal , AL 35809

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:38Z
Check the source to verify that this is the current version before use.