MIL-B-3060E(AR)
AMENDMENT 2
30 April 1986
SUPERSEDING
AMENDMENT 1
23 April 1985

MILITARY SPECIFICATION

BOXES, SMALL ARMS AMMUNITION: M19A1 and M2A1

This Amendment forms a part of Military Specification MIL-B-3060E(AR), dated 12 December 1979, and is approved for use within the US Army Armaments Munitions and Chemical Command and is available for use by all Deparments and Agencies of the Department of Defense.

PAGE 4

3.6 Delete in its entirety and substitute the following:

"Airtightness of box assembly. The assembled box shall withstand, without leakage, an air pressure differential of three pounds per square inch (psi) for 15 seconds."

* 3.6 Delete in its entirety and substitute the following:

"Airtightness of box assembly. The assembled box shall not release more than 4 bubbles of air when subjected to an air pressure differential of three (3) pounds per square inch (psi)."

PAGE 13

4.5.4 Delete in its entirety and substitute the following:

"Airtightness of box assembly. The container shall be conditioned to a temperature of 70°F ± 2°F and ambient pressure prior to testing. The assembled container shall be tested for leakage by immersing the closed box under water, to a depth of at least 1 inch below the surface of the water, in a vacumm vessel. A wetting agent may be used to minimize air bubbles clinging to the exterior surface. The air pressure in the vessel shall be lowered to 3 pounds per square inch below ambient pressure. Observation for leakage of air from the interior of the box assembly shall be made for a minimum of 15 seconds after reduction of pressure differential.".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:08Z
Check the source to verify that this is the current version before use.

* 4.5.4 Delete in its entirety and substitute the following:

"Airtightness of box assembly. The container shall be conditioned to a temperature of 70°F ± 2°F and ambient pressure prior to testing. The containers shall be tested in accordance with 4.5.5.1 or with Government approval 4.5.5.2 (see 6.6). A wetting agent may be used to minimize air bubbles clinging to the exterior surface.".

* Add the following paragraph:

"4.5.5.1 Vacuum method. The assembled container shall be tested for leakage by immersing the closed box, in a vacuum vessel, to a depth of at least one inch below the surface of the water. The air pressure in the vessel shall be lowered to 3 psi below ambient pressure. Observation for leakage of air from the interior of the box assembly shall be made during the period lowering pressure and for a minimum of 15 seconds after reduction of pressure differential.".

* Add the following paragraph:

"4.5.5.2 Hot water method. The assembled container shall be tested for leakage by immersing the closed container to a depth of one inch below the surface of the water. The temperature of the water and the length of time of immersion shall be that which will assure an increase in pressure to a minimum of 3 psi above ambient pressure (see 6.6). Observation for air leakage from the interior of the box assembly shall be made during the period of pressure build up and for a minimum of 15 seconds after the 3 psi pressure differential has been reached.".

PAGE 17

* Add the following paragraph:

"6.6 Hot water method for airtightness. The hot water test procedure for each container shall be submitted to Commander, ARDEC, ATTN: AMSMC-QAF-S(D), Dover, NJ 07801-5001 for approval. The test procedure shall include water temperature, immersion time, the data to support time and periodic verification procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:08Z
Check the source to verify that this is the current version before use.

* The margins of this amendment are marked with asterisks or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautions to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A721)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:08Z
Check the source to verify that this is the current version before use.