MIL-R-3075E
11 June 1982
SUPERSEDING
MIL-R-3075D
29 August 1973

MILITARY SPECIFICATION

ROLLERS, MOTORIZED, ROAD, DIESEL- OR

GASOLINE-ENGINE-DRIVEN, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers the minimum requirements for methods, materials, and procedures for the preservation, packing, and marking of road rollers, diesel- or gasoline-engine driven.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a apart of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-378	- Plastic Sheet and Strip, Thin Gauge, Polyolefin.
QQ-S-781	- Strapping, Steel, and Seals.
TT-P-664	- Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
UU-T-81	- Tags, Shipping and Stock.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AREA PACK

NO DELIVERABLE DATA REQUIRED BY THIS DOCUMENT.

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:11Z
Check the source to verify that this is the current version before use.

PPP-B-1055	- Barrier Material, Waterproofed, Flexible.
PPP-P-40	- Packaging and Packing of Hand Tools.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-R-196	- Repair Parts Accessories, and Kits, Mechanical, Packaging of.
MIL-L-2105	- Lubricating Oil, Gear, Multi-Purpose.
MIL-C-5501	- Cap and Plug, Protective, Dust and Moisture Seal.
MIL-E-10062	- Engines: Preparation for Shipment and Storage of.
MIL-T-22085	- Tape, Pressure-Sensitive, Adhesive, Preservation and Sealing.
MIL-B-22191	- Barrier Material, Transparent, Flexible, Heat Sealable.
MIL-P-46093	- Primer Coating, Synthetic (For Brake Drums).
MIL-A-46153	- Antifreeze, Ethylene Glycol, Inhibited, Heavy Duty, Single Package.
MIL-B-46176	- Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative.

STANDARDS

MILITARY

MIL-STD-129	- Marking For Shipment and Storage.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 202640-16T16:11Z
Check the source to verify that this is the currentversion before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups using Federal agencies.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 6.5).

3.2 Preproduction pack. Unless otherwise specified (see 6.2), the contractor shall furnish a preproduction pack for examination within the time frame specified (see 6.2), to prove, prior to starting production packaging, that the applied preservation, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The preproduction pack may be accomplished utilizing either the preproduction roller or a production roller. If the preproduction model roller is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by Government to facilitate comparison between the preproduction roller and the production roller.

3.3 Preservation. Preservation shall be level A, level B, or commercial, as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Disassembly. Disassembly shall be the minimum necessary to safeguard parts vulnerable to damage, pilferage, and loss. The extent of further disassembly shall be confined to the removal of protruding parts that would otherwise increase cubage; however, disassembly shall be limited to those parts that can be removed and reinstalled without special tools. Removed bolts, nuts, pins, screws, and washers shall be reinstalled in mating parts and secured to prevent their loss. Keys removed shall be secured to the keyway of the primary component or shaft. The extent of further disassembly shall be confined to that required by the transportability requirements of the end item specification.

3.3.1.2 Matchmarking. Parts removed and mating parts on the rollers and attachments shall be matchmarked when necessary to facilitate reassembly. Removed parts and mating parts shall be identified by cloth shipping tags conforming to UU-T-81, type A, style optional, and the marked tag attached to mating parts. The information on the cloth tags shall be applied with waterproof ink.

Source: https://assist.dla.mil -- Downloaded: 20260-16T16:11Z
Check the source to verify that this is the current version before use.

3.3.1.3 Preservatives. Preservatives identified herein by "P" numbers shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

3.3.1.4 Unprotected surfaces. Unprotected exterior metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 and not specifically specified herein or in the end item specification shall be coated as specified in the following paragraphs.

3.3.1.4.1 Unfinshed (not machined) surfaces. Unfinished exterior metal surfaces shall be coated with type P-1 preservative.

3.3.1.4.2 Machined surfaces. Exposed machined surfaces shall be coated with type P-6 or P-11 preservative and wrapped or covered, as applicable, with barrier material conforming to MIL-B-121, type I or II, grade A, class 2 or MIL-B-22191, type II. The material shall be secured in place with tape conforming to MIL-T-22085, type II.

3.3.1.5 Engines. Engines, engine components, and engine accessories shall be preserved in accordance with the level A requirements of MIL-E-10062, type I, method I.

3.3.1.5.1 Cooling system. Engines with liquid cooling systems shall be preserved by the water and antifreeze procedure specified in MIL-E-10062, except the antifreeze shall conform to MIL-A-46153.

3.3.1.6 Exposed gears. Exposed gears shall be coated with type P-1 preservative or with primer conforming to TT-P-664 or MIL-P-46093.

3.3.1.7 Enclosed gears. Gears operating on lubricating oil (SAE 10, 30 or 50) shall have the housing filled to the operating level with type P-10 preservative, type I, grade 10, 30, or 50 as applicable and tagged to indicate: "The preservative oil is adequate for operation. Do not drain until the first required lubrication change." Gears operating on gear lubricant (SAE 80 or 90) shall be filled to the operating level with lubricant conforming to MIL-L-2105, grade as applicable, and tagged to indicate: "The lubricant is good for operation. Do not drain until the first required lubrication change." Gears not operating on lubricating oil (SAE 10, 30, or 50) or lubricant (SAE 80 or 90) shall be filled to the operating level with the approved lubricant required for operation. The gear housings shall be tagged to indicate: "The housing is filled to the operating level with the applicable type lubricant. Do not drain prior to the first required lubrication change." The tags shall conform to UU-T-81, type A. Information on the tags shall be applied with waterproof ink. The tags shall be attached in a conspicuous location.

3.3.1.8 Automatic transmissions and torque converters. The housings shall be filled to the operating level with the lubricant required for operation. The transmissions and torque converters shall be operated at sufficient engine speed to insure coating of all interior surfaces and parts with the lubricant. Openings into the housings shall be sealed with tape conforming to MIL-T-22085, type II. A tag shall be attached to the control level indicating: "The housing

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

is filled to the operating level with the approved lubricant and is good for operation. Do not operate engine until the tape has been removed from the openings." The tag shall conform to UU-T-81, type A. The information on the tag shall be applied with waterproof ink.

3.3.1.9 Disc-type clutches. With the cover plates removed and the clutch engaged, all accessible metal interior components of the clutch shall be sprayed with a thin film of primer conforming to TT-P-664 or primer conforming to MIL-P-46093. When specified (see 6.2), the clutch shall be disassembled sufficently to permit the application of a continuous thin film (max. 0.75 mil) of the same primer to friction surfaces of the pressure plates. Clutch control mechanisms not enclosed shall be coated with type P-1 preservative. After being sprayed, spring-loaded-type clutches shall have the clutch pedal secured in a partially disengaged position to eliminate contact between the disc facings and pressure plates. Snap-over-center and toggle-in-type clutches shall be completely disengaged. Cover plates shall be reinstalled.

3.3.1.10 Exposed drive chains. Exposed drive chains shall be coated with enough type P-3 or P-9 preservative to insure penetration of the preservative to the inner surfaces of the rollers, pins, and bushings. After the excess preservative has drained, the entire chain and the unpainted surfaces of the sprocket shall be coated with type P-1 preservative.

3.3.1.11 Enclosed chains. Enclosed chains and chain housings shall be preserved and tagged as specified in 3.3.1.7 for enclosed gears.

3.3.1.12 Drive belts and pulleys. Drive belts shall be removed or released from tension. Removed belts shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3. Unpainted faces of pulley grooves shall be coated with primer conforming to TT-P-664 or primer conforming to MIL-P-46093. A tag conforming to UU-T-81, type A, shall be attached in a conspicuous location indicating: "Belts have been removed or released from tension. Install or tension as applicable, prior to operation." The information on the tag shall be applied with waterproof ink.

3.3.1.13 Drive shafts and universal joints. Unpainted surfaces of drive shafts and universal joints shall be coated with type P-1 preservative. Dust boots, if furnished, shall be reinstalled.

3.3.1.14 Flywheel and starter drives. When specified (see 6.2), flywheel ring gears and starter drive mechanisms shall be coated with type P-10 preservative, type I, grade 30.

3.3.1.15 Winterization system. Interior surfaces of the tanks, pumps, piping and burners requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-10 preservative, type I, grade 30. The threaded surfaces of fill caps and drain plugs shall be coated with the preservative and reinstalled.

Source: https://assist.dla.mil -- Downloaded: 20260-16T16:11Z
Check the source to verify that this is the current version before use.

3.3.1.16 Hydraulic systems (except hydraulic brakes or steering systems). The hydraulic fluid supply tanks shall be filled to the operating level with hydraulic fluid required for operation. The pistons shall be retracted as far as practicable into the cylinders and secured. When the pistons cannot be fully retracted, the exposed portions of the piston rods (ramshafts) shall be coated with type P-6 or P-11 preservative and the coated surfaces wrapped or covered with barrier-material conforming to MIL-B-121, type II, grade A, class 2, extending the wraps approximately 2 inches onto the ram cylinders. The wraps shall be secured in place with tape conforming to MIL-T-22085, type II. When the pistons can be fully retracted, any remaining uncoated surfaces of the piston rods shall be coated with type P-1 preservative, with no wrapping required. The hydraulic control valves shall be secured in the neutral position and preserved as specified herein for piston rods. Hoses shall not be disconnected. Any unpainted exterior metal surfaces of the system, requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative. A tag conforming to UU-T-81, type A, shall be attached to the control lever indicating: "The hydraulic supply tank is filled to the operating level with fluid required for operation. Do not drain." Waterproof ink shall be used for printing the information on the tag.

3.3.1.17 Brakes.

3.3.1.17.1 General. Exterior, unpainted, untreated, and threaded surfaces of cables, clevises, and linkages of service and parking brakes, requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative. When specified (see 6.2), metal surfaces enclosed within brake drums (such as adjusting wedges, pins, eccentrics, cam levers, linkage, anchors, retracting springs) and the brake surfaces of the brake drums shall be sprayed with a continuous film of primer conforming to TT-P-664 or primer conforming to MIL-P-46093. The film shall be a minimum of 0.50 mil to a maximum of 0.75 mil thick as determined by an elcometer. Primer material containing lumps or skin, that will not return to a homogenous mixture upon stirring, shall not be used. The film shall be thoroughly dry prior to reinstalling the brake drums. A warning tag conforming to UU-T-81, type A, shall be securely attached in a conspicuous location in the operator's compartment, indicating: "Brake drums and components preserved. Do not apply brakes when roller is being moved. Towing shall be accomplished by use of a rigid towbar or similar arrangement until this roller is issued to the user." Waterproof ink shall be used for the information marking on the tag. Note: Interior surfaces of brake drums shall not be preserved when the roller design incorporates a planetary drive with the wheel brake assembly and the surfaces are inaccessible by simply removing the brake drum.

3.3.1.17.2 Hydraulic brakes and steering systems.

3.3.1.17.2.1 Operating on nonpetroleum base hydraulic fluid. The complete hydraulic system of brakes and steering systems that operate on nonpetroleum base hydraulic fluids shall be filled to the operating level with preservative fluid conforming to MIL-B-46176 and the system actuated to insure coating of all interior surfaces with preservative. A tag conforming to UU-T-81, type A, shall be attached to the controls indicating: "This systems is filled with preservative fluid and is good for indefinite storage and for operation in

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

ambient temperatures lower than minus 10° F, the system shall be drained and refilled to the operating level with the hydraulic fluid required for operation." Waterproof ink shall be used for printing the information on the tag.

3.3.1.17.2.2 Operating on petroleum base hydraulic fluid. The complete hydraulic system of brakes and steering systems that operate on petroleum base fluid shall be filled to the operating level with the fluid required for operation and the system actuated to insure coating of all interior surfaces with the fluid. A tag conforming to UU-T-81, type A, shall be attached to the system controls indicating: "This system is filled with the approved operating fluid." Waterproof ink shall be used for printing the information on the tag.

3.3.1.17.3 Air-actuated brake system. The air-actuated brake systems shall be drained. Interior surfaces of the air-supply tanks shall be fogged with type P-10 preservative, type I, grade 30. Excess preservative oil shall be drained. Threaded openings and the threads of drain plugs shall be coated with the preservative oil specified herein. The drain plugs shall be reinstalled. Air line filters shall be drained and closed. The exhaust ports of relay emergency, quick-release, and relay valves not equipped with exhaust check valves shall be closed by inserting caps or plugs as applicable conforming to MIL-C-5501 or by sealing the ports with tape conforming to MIL-T-22085, type II. Tags conforming to UU-T-81, type A, shall be attached to the valves and service lines indicating: "The plugs, caps, or tape must be removed from the exhaust ports and valves before this roller is placed in operation." Waterproof ink shall be used for printing the information on the tags.

3.3.1.18 Electrical components. Openings in sockets, coupling plugs, and switches shall be sealed with tape conforming to MIL-T-22085, type II.

3.3.1.19 Trouble lights, lamps, reflectors, and mirrors. Trouble lights, lamps, reflectors, and mirrors, if removed, shall be individually preserved in accordance with MIL-P-116, method III, using boxes conforming to PPP-B-636, W5c, or W6c, style optional. Lamps, reflectors and mirrors not removed shall be covered with barrier material conforming to MIL-B-121, type II, grade A, class 2. The barrier material shall be secured in place with tape conforming to MIL-T-22085, type II.

3.3.1.20 Gear shifts and control levers. Unpainted metal surfaces of handles and levers shall be coated with type P-1 preservative. Composition and rubber handgrips, when not protected by a full cab, shall be removed if practical and preserved in accordance with MIL-P-116, method IC-1 or IC-3. When the handgrips are left in place of an unprotected cab, they shall be wrapped with barrier material conforming to PPP-B-1055, class E-2, or black polyethylene conforming to L-P-378 (6 mil) and the wrap secured with tape conforming to MIL-T-22085, type II.

3.3.1.21 Seat backs, arm rests, and cushions. Seat backs, arm rests and cushions when not protected by a full cab, shall be removed if practical and individually wrapped with barrier material conforming to PPP-B-1055, class E-2 or black polyethylene conforming to L-P-378 (6 mil) and the wrap secured with tape conforming to MIL-T-22085, type II. When seat backs, arm rests, and cushions are left in place they shall be wrapped or covered with the barrier material specified herein and the wrap or cover secured in place with tape specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

3.3.1.22 Instrument panels. Instruments, meters, and gages not protected by a metal cover or by the roller cab shall have the instrument glass or gage glass covered with barrier material conforming to MIL-B-121, type II, grade A, class 2, over which a fitted piece of hardboard or 1/4-inch-thick plywood shall be placed and secured with tape conforming to MIL-T-22085, type II.

3.3.1.23 Rolls, water ballast, and sprinkler system. The rolls and the ballast tanks shall be drained and allowed to dry, after which the interior surfaces shall be fogged with type P-10 preservative, type I, grade 30. The sprinkler system shall be flushed with the preservative specified herein. Threads of the filler plugs, caps, and drain plugs shall also be coated with the preservative specified herein and then reinstalled.

3.3.1.24 Hose. Each length of hose, if detached from the roller, shall be coiled and the coil secured with not less than three equally spaced ties of cotton tape or twine. Threads and fittings requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative.

3.3.1.25 Windshield wiper arms and blades. Windshield wiper arms and blades shall be removed and preserved in accordance with MIL-P-116, method IC-1 or IC-3. The preserved wiper arms and blades shall be placed in the toolbox. The exposed wiper shaft shall be coated with type P-1 preservative.

3.3.1.26 Locks, keys, and key openings. Interiors of locks shall be coated with powdered graphite. The locks shall be operated to insure penetration of the graphite. Openings into locks (except padlocks) shall be sealed with tape conforming to MIL-T-22085, type II. Switch keys, cab door keys, and padlocks with keys shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3. The preserved keys and padlocks with keys for each roller shall be placed in the toolbox. A tag shall be attached in a conspicuous location in the operator's compartment indicating: "The keys for the roller are in the toolbox." For rollers without cabs the information on the tags shall be applied with a waterproof ink.

3.3.1.27 Rubber tires. Tires mounted on the wheels (road tires) of the roller shall be inflated to 10 pounds above pressure value recommended for maximum load. Tires mounted on rims (spare tires) shall be inflated to two-thirds of the specified operating pressure.

3.3.1.28 Fire extinguishers. Unpainted exterior metal surfaces of fire extinguishers requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. Fire extinguishers enclosed with full cabs shall be secured in their mounting brackets. Fire extinguishers not enclosed within a full cab shall be individually placed in a box conforming to PPP-B-636, class weather-resistant. Blocking and cushioning shall be provided within the box to prevent movement or damage. Boxes shall be sealed in accordance with the appendix to the box specification, method V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

3.3.1.29 Maintenenace tools. Maintenance tools shall be preserved in accordance with the level A preservation and packaging requirements of PPP-P-40.

3.3.1.30 Technical publications. Technical publications for each roller shall be preserved together in accordance with MIL-P-116, method IC-1 or IC-3.

3.3.1.31 Repair parts. Unless otherwise specified, the preservative application criteria and applicable method(s) of preservation of MIL-P-116 shall be used to preserve repair parts. When specified (see 6.2), the repair parts shall be preserved in accordance with the level A requirements of MIL-R-196, or when parts are not specifically covered in MIL-R-196, an applicable submethod of preservation of MIL-P-116 shall be used.

3.3.1.32 Other components. Other components not specifically mentioned herein requiring protection from corrosion of physical or mechanical damage shall be preserved as specified for components of similar design and construction.

3.3.1.33 Consolidation. Padlocks and keys shall be placed in the toolbox; other loose components requiring the protection of a container to prevent pilferage, damage, or loss such as repair parts, tools, publications, lamps, reflectors, mirrors, handgrips, seat backs, arm rests, cushions, wiper arms and blades, loose hose, fire extinguishers, etc., shall be consolidated together in boxes. The tool box shall be utilized in so far as space permits and the lid closed and secured. The remainder of the components that will not fit in the toolbox shall be consolidated in a minimum number of boxes conforming to PPP-B-601, overseas type, style I or J or in boxes conforming to PPP-B-621, class 2, style optional. The number, size, weight, and configuration of the boxes shall be determined by the available space and convenience for securing the boxes on the roller.

3.3.2 Level B.

3.3.2.1 Disassembly. Disassembly shall be as specified in 3.3.1.1 for level A.

3.3.2.2 Matchmarking. Matchmarking shall be as specified in 3.3.1.2 for level A.

3.3.2.3 Preservatives. Preservatives identified herein by "P" numbers shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

3.3.2.4 Unprotected surfaces. Unprotected exterior metal surfaces requiring application of a contact preservative in accordance with MIL-P-116 shall be coated with preservative as specified in 3.3.1.4.

3.3.2.5 Engines. Engines and engine accessories including cooling systems shall be preserved as specified in 3.3.1.5 for level A.

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:11Z
Check the source to verify that this is the current version before use.

3.3.2.6 Enclosed gears and chains. The housings shall be filled to the operating level with the applicable type lubricant required by the lubricating order for operation and tagged to indicate that the housings are filled with the required amount of operating oil. The tags shall be secured in a conspicuous location.

3.3.2.7 Automatic transmissions and torque converters. The housings shall be filled to the operating level with the applicable type lubricant required by the lubricating order for operation and tagged to indicate that the housings are filled with the required amount of operating oil. The tags shall be secured in a conspicuous location.

3.3.2.8 Disc-type clutches. Spring-loaded type clutches shall have the control secured in a partially disengaged position. Snap-over-center and toggle-in type clutches shall be completely disengaged.

3.3.2.9 Exposed drive chains. Exposed drive chains shall be coated with type P-3 or P-9 preservative.

3.3.2.10 Drivebelts. Drivebelts shall be released from tension and tagged as indicated in 3.3.1.12 for level A.

3.3.2.11 Winterization system. The winterization systems shall be preserved as specified in 3.3.1.15 for level A.

3.3.2.12 Hydraulic systems (including hydraulic brakes and steering). The hydraulic fluid supply tanks or resevoirs shall be filled with the hydraulic fluid required for operation and the systems shall be tagged to indicate the supply tanks or reservoirs are filled with the hydraulic fluid required for operation.

3.3.2.13 Air-actuated brake systems. Air-actuated brake system shall be preserved as specified in 3.3.1.17.3 for level A.

3.3.2.14 Trouble lights, lamps, reflectors, and mirrors. Trouble lights, lamps, reflectors, and mirrors if removed from the roller shall be preserved as specified in 3.3.1.19, level A.

3.3.2.15 Seat backs, arm rests, and cushions. Seat backs, arm rests, and cushions shall be protected as specified in 3.3.1.21 for level A.

3.3.2.16 Instrument panel. Instruments and gage glasses not protected by a metal cover or by the roller cab shall be protected as specified in 3.3.1.22 for level A.

3.3.2.17 Windshield wiper arms and blades. Windshield wiper arms and blades shall be removed and placed in the toolbox.

3.3.2.18 Rubber tires. Tires shall be inflated as specified in 3.3.1.27 for level A.

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:11Z
Check the source to verify that this is the currentversion before use.

3.3.2.19 Fire extinguishers. Fire extinguishers enclosed within the cab shall be secured in the mounting brackets. Fire extinguishers not enclosed within the cab shall be individually placed in a close-fitting box conforming to PPP-B-636, class domestic variety and grade as applicable to the weight involved.

3.3.2.20 Maintenance tools, technical publications, and repair parts. Maintenance tools, technical publications, and repair parts shall be preserved as specified for level A.

3.3.2.21 Consolidation. Consolidation shall be as specified for level A, except boxes shall be domestic type or class.

3.3.3 Commercial. Each complete roller with repair parts, maintenance tools, and technical publications (except for engine and engine accessories [see 3.3.3.1]) shall be preserved in accordance with MIL-STD-1188.

3.3.3.1 Engine. Liquid cooling systems shall be filled with a fresh clean solution of 50 percent water and 50 percent antifreeze conforming to MIL-A-46153. A tag shall be attached indicating the temperature to which the cooling system can be subjected to before damage. All lubrication reservoirs, sumps and hydraulic fluid supply tanks or reservoirs shall be filled to the operating level with the lubricant or fluid designated for use in the temperature range at the shipping destination. A tag or tags, as applicable, shall be attached in a conspicuous location indicating which lubricant or fluid has been used.

3.3.3.2 Tool box. The tool box lid shall be closed and secured to prevent pilferage.

3.4 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

3.4.1 Level A. The rollers preserved as specified in 3.3 shall be prepared for mobile (unboxed) shipment as follows.

3.4.1.1 Components and consolidated containers. Preserved and unpreserved components and consolidated containers shall be secured on the roller with appropriate size strapping conforming to QQ-S-781, class 1, type I or IV, finish B. Straps shall be properly tensioned and sealed. Arrangement and location on the roller shall be such as not to increase cubage or interfere with lifting or mobility of the roller. Wheels shall be free to rotate.

3.4.1.2 Scarifiers. Scarifiers shall be raised to their maximum height and shall be locked in that position. Hydraulically operated scarifiers shall be additionally secured by tying to the roller frame with wire rope, size as applicable secured with wire rope clips or with strapping conforming to QQ-S-781, class 1, type I or IV, finish B, size as applicable.

3.4.1.3 Engine housings. Engine housing doors shall be closed and secured. Louvers and other small openings shall be sealed with tape conforming to MIL-T-22085, type II. Engines not completely enclosed with housings shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

covered with a shroud of barrier-material conforming to PPP-B-1055, E-2 and the shroud secured in place with tape specified herein. When specified (see 6.2), radiator fronts shall be covered with barrier-material specified herein and the barrier-material secured in place with tape specified herein.

3.4.1.4 Cabs. Cab windows and doors shall be closed. When specified (see 6.2), windshield and window glass shall be protected from breakage by covering each glass surface with a fitted piece of hardboard, or with 1/4-inch thick plywood, or with a sheet metal panel, secured in place with bolts or with steel strapping conforming to QQ-S-781, class 1, type I or IV, finish B, size as applicable. There shall be not less than 1-inch clearance between the panels and the glass. The panels shall be painted the same color as the cab. Small openings into the cab shall be sealed with tape conforming to MIL-T-22085, type II.

3.4.2 Level B. The roller, components, repair parts, tools, and publications preserved as specified in 3.3, shall be prepared for mobile (unboxed) shipment as specified for level A, except as follows: Strapping shall not be required to be finish B. Except when overseas shipment is involved, sealing of openings into engine housings and shrouding of engines shall not be required.

3.4.3 Commercial. The roller, components, repair parts, tools, and publications preserved as specified in 3.3 shall be prepared for mobile (unboxed) shipment in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

3.5 Marking.

3.5.1 Military. Marking for military levels of protection (level A or B), shall be in accordance with MIL-STD-129.

3.5.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

3.6 Depreservation guides. Two depreservation guides shall be prepared and placed in waterproof envelopes marked "Depreservative Guide." One of the guides shall be secured to the steering wheel or steering controls of the roller. The other copy shall be placed in the roller toolbox. Unless otherwise specified (see 6.2), "DA Form 2258 - Depreservation Guide for Vehicles and Equipment" shall be used.

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the roller by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract the contractor may use his own or any other facilities suitable for the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials used are manufacturered, examined, and tested in accordance with reference specification and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.4.3. Examination shall be in three stages as specified in 4.4.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages.

(a) The first stage shall include inspection of procedures, containers, materials, methods, and marking prior to enclosing the loose components in consolidated containers.
(b) The second stage shall include inspection of the marking and closure of the consolidated containers.
(c) The third stage shall include inspection of the procedure and methods, materials, and marking of the complete mobile (unboxed) roller as prepared for shipment. This stage shall include arrangement of consolidated containers and components required to be secured to the roller for shipment.

4.4.2 Unit of product. For the purpose of inspection a complete unit prepared for any applicable inspection stage shall be considered a unit of product.

4.4.3 Examination. Each roller shall be examined in accordance with the inspection stages (see 4.4.1) for the following defects. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:11Z
Check the source to verify that this is the currentversion before use.

TABLE I Defects.

Major	Defects	Level A	Level B	Level Commercial
101.	Materials, methods, and containers, not as specified. Each incorrect material, each incorrect method, and each incorrect container shall constitute one defect, (see 3.1, 3.3, 3.4).	X	X	X
102.	Disassembly not as specified, (see 3.3.1.1, 3.3.2.1).	X	X	
103.	Matchmarking not as specified, (see 3.3.1.2, 3.3.2.2).	X	X	
104.	Information on tags not applied with waterproof ink, (see 3.3.1.2, 3.3.1.7, 3.3.1.8, 3.3.1.12, 3.3.1.16, 3.3.1.17.2.1 3.3.1.17.2.2, 3.3.1.17.3, 3.3.1.26,			
105.	Unprotected surfaces not coated with preservative as specified (see 3.3.1.4, 3.3.2.4).	X	X	
106.	Coated surfaces not wrapped or covered as specified, (see 3.3.1.4.2, 3.3.2.4).	X	X	
107.	Engines and engine components not preserved as specified (see 3.3.1.5, 3.3.2.5, 3.3.3.1).	X	X	X
108.	Exposed gears not coated with preservative or with primer as specified (see 3.3.1.6).	X		
109.	Enclosed gear housing not filled with preservative oils or with operational lubricant as specified and the housings not tagged as specified (see 3.3.1.7, 3.3.2.6).	X	X	
110.	Automatic transmissions and torque converters not filled with operational lubricant and the control levers not tagged as specified (see 3.3.1.8, 3.3.2.7).	X	X	
111.	Accessible interior metal surfaces of clutches not coated with primer as specified (see 3.3.1.9).	X		
112.	Clutches not completely disengaged or completely disengaged as applicable (see 3.3.1.9, 3.3.2.8).	X	X	
113.	Exposed drive chains not coated with preservative as specified (see 3.3.1.10, 3.3.2.9).	X	X	

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:11Z
Check the source to verify that this is the current version before use.

TABLE I Defects. (Con't)

Major	Defects	Level A	Level B Commercial
114.	Enclosed chain housings not filled with preservative oil or not filled with operational lubricant as applicable and the housings not tagged as specified (see 3.3.1.11, 3.3.2.6).	X	X
115.	Drive belts not removed or released from tension as specified and not tagged as specified (see 3.3.1.12, 3.3.2.10).	X	X
116.	Unpainted surfaces of pulley grooves not coated with primer as specified (see 3.3.1.12).	X	
117.	Drive shafts and universal joints not coated with preservative as specified and dust boots not reinstalled as specified (see 3.3.1.13).	X	
118.	Winterization system components not preserved as specified (see 3.3.1.15, 3.3.2.11).	X	X
119.	Hydraulic systems not filled with fluid as specified (see 3.3.1.16, 3.3.2.12).	X	X
120.	Exposed portions of hydraulic piston rods not preserved as specified and the preserved surfaces not wrapped when required (see 3.3.1.16).	X	
121.	Hydraulic systems not tagged as specified (see 3.3.1.16, 3.3.2.12).	X	X
122.	Surfaces of brake components enclosed within brake drums and the braking sufaces of brake drums not coated with primer when specified (see 3.3.1.17.1).	X	
123.	Exterior surfaces of brakes not coated with preservative as specified (see 3.3.1.17.1).	X	
124.	Tag not attached to indicate brakes have been preserved (see 3.3.1.17.1, 3.3.1.17.2.1, 3.3.1.17.2.2, 3.3.2.13).	X	X
125.	Hydraulic brake systems operating on nonpetroleum base fluid not filled with preservative fluid as specified (see 3.3.1.17.1, 3.3.1.17.2.1, 3.3.1.17.2.2, 3.3.2.12).	X	X
126.	Hydraulic brake systems operating on petroleum base fluid not filled to the operating level with the fluid required for operation (see 3.3.1.17.2.2, 3.3.2.12).	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

TABLE I Defects. (Con't)

Major	Defects	Level		
		A	B	Commercial
127.	Air-actuated brake system supply tank not fogged with preservative oil as specified, excess preservative not drained, ports and valves not sealed and tagged as specified (see 3.3.1.17.3, 3.3.2.13).	X	X	
128.	Openings into electrical sockets, coupling plugs, and switches not sealed as specified (see 3.3.1.18).	X		
129.	Trouble lights, lamps, reflectors, and rear vision mirrors not preserved or not covered as applicable (see 3.3.1.19, 3.3.2.14).	X	X	
130.	Composition or rubber handgrips not preserved or not wrapped as applicable (see 3.3.1.20).	X		
131.	Seat backs, armrests, and cushions not wrapped or not covered as specified (see 3.3.1.21, 3.3.2.15).	X	X	
132.	Instrument panels not protected as specified (see 3.3.1.22, 3.3.2.16).	X	X	
133.	Rolls, water ballast and sprinkler system not preserved as specified (see 3.3.1.23).	X		
134.	Loose hose not coiled and secured as specified (see 3.3.1.24).	X		
135.	Windshield wiper arms and blades not removed, preserved and placed in toolbox as specified (see 3.3.1.25, 3.3.2.17).	X	X	
136.	Interior of locks not coated with graphite and openings into locks not sealed as specified (see 3.3.1.26).	X		
137.	Key and padlocks not placed in toolbox as specified (see 3.3.1.26).	X		
138.	Tag not attached within operators compartment to indicate location of keys (see 3.3.1.26).	X		
139.	Rubber tires not inflated as specified (see 3.3.1.27, 3.3.2.18).	X	X	
140.	Unpainted exterior surfaces of fire extinguishers not coated with preservative, if required (see 3.3.1.28).	X		
141.	Fire extinguishers not placed in box as specified, if required (see 3.3.1.28) or secured in mounting brackets (see 3.3.2.19).	X	X	

Source: https://assist.dla.mil -- Downloaded: 202610-16T16:11Z
Check the source to verify that this is the current version before use.

TABLE I Defects. (Con't)

Major	Defects	Level A	Level B	Level Commercial
142.	Maintenance tools not preserved in accordance with the reference document (see 3.3.1.29, 3.3.2.20).	X	X	
143.	Technical publications not preserved as specified (see 3.3.1.30, 3.3.2.20).	X	X	
144.	Repair parts not preserved in accordance with the referenced document (see 3.3.1.31, 3.3.2.20).	X	X	
145.	Consolidation not as specified (see 3.3.1.33, 3.3.2.21).	X	X	
146.	Toolbox lids not secured to prevent pilferage (see 3.3.1.33, 3.3.2.21, 3.3.3.2).	X	X	X
147.	Components and consolidated containers not secured on the roller in the manner specified (see 3.4.1.1, 3.4.2.).	X	X	
148.	Strapping not as specified (see 3.4.1.1, 3.4.1.2, 3.4.1.4, 3.4.2).	X	X	
149.	Scarifiers not positioned, not locked, and not secured as specified (see 3.4.1.2, 3.4.2).	X	X	
150.	Engines not protected by a shroud when not fully enclosed (see 3.4.1.3).	X		
151.	Radiator fronts not covered as specified, when required (see 3.4.1.3).	X		
152.	Windshields and window glass not protected as specified when required (see 3.4.1.4, 3.4.2).	X	X	
153.	Marking missing, illegible, incomplete, incorrect (see 3.5).	X	X	X
154.	Depreservation guides not prepared and stowed as specified (see 3.6).	X	X	X

5. PACKAGING

(This section not applicable to this specification).

6. NOTES

6.1 Intended use. It is intended that the requirements of this specification be used for reference in Section 5 of equipment specifications, for direct reference in contract or orders, and can be used as a guide in the preparation of packaging data sheets covering preservation, packing, and marking of motorized road rollers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a preproduction pack is not required (see 3.2).
(c) Time frame required for submission of preproduction pack (see 3.2).
(d) Degree of preservation and degree of packing required (see 3.3 and 3.4).
(e) When friction surfaces of clutch pressure plates are to be preserved (see 3.3.1.9).
(f) When flywheel ring gears and starter drive mechanism are to be preserved (see 3.3.1.14).
(g) When brake components enclosed within brake drums and the braking surfaces of brake drums are to be preserved (see 3.3.1.17.1).
(h) Applicable document to be used for preserving repair parts (see 3.3.1.31).
(i) When radiator fronts are to be protected (see 3.4.1.3).
(j) When windshields and window glass are to be protected (see 3.4.1.4).
(k) When other than DA Form 2258 is to be used (see 3.6).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the rollers and components in accordance with this specification.

6.4 Depreservation guides. The contracting officer should arrange to furnish the necessary copies of DA Form 2258, when requested by the contractor (see 3.6).


6.5 Recycled materials. It is encouraged that recycled materials be used, when practical as long as they meet the requirements of this specification (see 3.1).

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activity:
Army - SM

Preparing activity:
Army - ME

Project PACK-0651



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-R-3075E Rollers, Motorized, Road, Diesel-or Gasoline-Engine-Driven, Packaging Of

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-16T16:11Z
Check the source to verify that this is the current version before use.