MILITARY SPECIFICATION

HEATER, VEHICULAR COMPARTMENT: MULTIFUEL BURNING 24 VOLT, DC
30,000 BTU/HR

This amendment forms a part of limited coordination military specification MIL-H-0046792B(AT), 6 February 1984, and is approved for use by US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.4.2, delete paragraph in its entirety and substitute:

"3.4.2 Current. At 24 Vdc, maximum current drawn from the power source shall be 12 amperes (amps) starting and 8 amps running when the preheaters are not activated. The current draw is increased by 5 amps maximum when the preheaters are activated (approx. 45°F) (see 4.6.2)."

PAGE 5

3.4.6, under the column heading Discharge rate:

a. Change phrase pertaining to 115 scfm so as to read "115 standard cubic feet per minute (scfm), minimum; 130 scfm, nominal."
b. Change phrase pertaining to 80 scfm to read "80 scfm, minimum; 94 scfm, nominal."

PAGE 6

3.4.13, delete subparagraph d. in its entirety and substitute:

"d. Replacement of the burner assembly if required, but no more frequently than once per sample during the test procedure."

FSC 2540

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:57Z
Check the source to verify that this is the current version before use.

PAGE 7

3.4.14.6, delete in its entirety and substitute:

"3.4.14.6 Vibration. The heater shall start and operate as specified herein during and after sinusoidal vibration in accordance with figure 1, for a period of 80 minutes minimum (including up to four resonance dwells of 13-1/3 minutes each) in each of three mutually perpendicular axes. Input to be measured at the interface of the heater and support bracket (see 4.6.14.6)."

PAGE 9

4.3, change subparagraph c. Relative humidity tolerance from "± 30 percent" to "± 40 percent".

PAGE 13

4.6.5, delete definition for Cp (in the formula) in its entirety and substitute "Cp = Specific heat of air (average) as corrected for temperature and moisture content".

4.6.6, delete paragraph in its entirety and substitute:

"4.6.6 Air discharge rate test. To determine conformance to 3.4.6 measure the ventilating air discharge velocity with 24 Vdc input and back pressures as specified in 3.4.6 utilizing AMCA Standard 210-74 (pitot traverse in outlet duct or a venturi complying with ASME Power Test Code 19.5.4 - 1959). The back pressure may be controlled by using either variable or fixed restrictions sized on a nominal heater under nominal ambient conditions run at 24 Vdc input in the high heat range. The air discharge rate shall be calculated using the methods defined in AMCA Standard for 24 Vdc. Unrestricted air flow measurements are not required during 100% acceptance testing."

4.6.7, add at end of paragraph: "This test is to be conducted at room ambient temperature only (73° ± 18°F)."

PAGE 14

4.6.12, add at end of last sentence: "except each first article test sample and control test sample shall be retested at the completion of all other testing. No leakage shall be permitted".

4.6.14.1, delete "minimum of 12 hours." from second sentence and substitute: "minimum of 24 hours."

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:57Z
Check the source to verify that this is the current version before use.

4.6.14.2, delete paragraph in its entirety and substitute:

"4.6.14.2 Storage temperature test. This test is conducted in conjunction with 4.6.14.1 and 4.6.14.1.1."

4.6.14.3, change "...(omitting step 8)." to "...(omitting steps 4 and 8)."

4.6.14.6, insert the following sentence before the last sentence of the paragraph:

"The total cycling time per axis shall be 80 minutes including the resonance dwell time accumulated."

Custodian:
Army - At

Review activities:
Air Force - 99
DLA - GS

Preparing activity:
Army - AT

(Project No. 2540-A333)

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:57Z
Check the source to verify that this is the current version before use.