MIL-S-46777/2
10 March 1981

MILITARY SPECIFICATION SHEET

SEMITRAILER, DUMP, COMMERCIAL SIZE 12

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the dump semitrailer described herein shall consist of this document and the latest issue of Specification MIL-S-46777.

REQUIREMENTS:

1. The size 12 dump semitrailer shall be equipped with a single axle and as specified in table I.

TABLE I. Weights and Dimensions.

		Size 12
Mfgr's Rated GVWR		Min. 32,000 lb.
Payload.		Min. 24,000 lb.
Axle Weight Limit.		
(a) Single Axle Rear Suspension		Max. 18,000 lb.
(b) Multiple Axle Rear Suspension (each axle)		----------
Overall Length.	(OAL) L108	Max. 250 in.
Overall Width.	(OAW) W103	Max. 98 in.
Overall Height.	(OAH) H153	Max. 150 in.
Ground Clearance.	(GC) H156	Min. 9.5 in.
Front Support clearance. Radius	(LWC) L498T	Min. 82 in.
Swing Radius.	(SR) L497T	Max. 52.2 in.
Body:		
Struck Capacity.	(SAE J741)	Min. 8 cu. yd.
Heaped Capacity.	(SAE J741)	Min. 10 cu. yd.
Length of Body.		Min. 16 cu. ft.
TBEA Hoist Classification.		Min. 80

Custodian:
Army – ME

Review activity:
Army – AT

User activities:
Army – CE
Navy – MC, YD

Preparing activity:
Army – ME

Project 2330-0745-2

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:54Z
Check the source to verify that this is the current version before use.