MIL-S-46777/4
10 March 1981

MILITARY SPECIFICATION SHEET

SEMITRAILER, DUMP, COMMERCIAL SIZE 25

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the dump semitrailer described herein shall consist of this document and the latest issue of Specification MIL-S-46777.

REQUIREMENTS:

1. The size 25 dump semitrailer shall be as specified herein and in table I.

2. Unless otherwise specified by the procuring activity, the size 25 semitrailer shall be equipped with a tridem (3-axle) rear running gear.

TABLE I. Weights and Dimensions.

		Size 25
Mfgr's Rated GVWR.		Min. 65,000 lb.
Payload.		Min. 50,000 lb.
Axle Weight Limit.		
(a) Single Axle Rear Suspension		--------
(b) Multiple Axle Rear Suspension (each axle)		Max. 16,000 lb.
Overall Length.	(OAL) L108	Max. 480 in.
Overall Width.	(OAW) W103	Max. 98 in.
Overall Height.	(OAH) H153	Max. 150 in.
Ground Clearance.	(GC) H156	Min. 9.5 in.
Front Support Clearance.	(LWC) L498T	Min. 90 in.
Body:		
Struck Capacity.	(SAE J741)	Min. 40 cu. yd.
Heaped Capacity	(SAE J741)	Min. 48 cu. yd.
Length of Body.		Min. 30 ft.
TBEA Hoist Classification.		Min. 100

Custodian:
Army - ME

Review activity:
Army - AT

User activities:
Army - CE
Navy - MC, YD

Preparing activity:
Army - ME

Project 2330-0745-4

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:54Z
Check the source to verify that this is the current version before use.