METRIC
DOD-D-64015A (AR)
AMENDMENT 1
2 FEBRUARY 1989

MILITARY SPECIFICATION SHEET

DIETHYLENE GLYCOL DINITRATE (DEGDN) (FOR USE IN AMMUNITION)

This amendment forms a part of Military Specification DOD-D-64015A (AR), dated 21 November 1986, and is approved for use within the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
3	3
4	Reprinted without change
5	Reprinted without change
6	6
7	7

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1315-AB53)

Distribution Statement A: Approved for public release; distribution unlimited.

FSC-1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3.0 REQUIREMENTS

3.1 Manufacture. - Diethylene Glycol conforming with MIL-D-23296 shall be used in the manufacture of DEGDN.

3.2 Material. - The explosive shall be DEGDN conforming with the following requirements.

3.2.1 Nitrogen. - The nitrogen content shall be 14.1 percent minimum to 14.53 percent maximum when determined in accordance with 4.5.1.

3.2.2 Moisture. - The moisture content shall be 0.75 percent maximum when determined in accordance with 4.5.2.

3.2.3 Alkalinity. - The alkalinity content, calculated as sodium carbonate (Na_2CO_3), shall not exceed .004 percent when determined in accordance with 4.5.3.

3.2.4 Acidity. - The acidity content, calculated as sulfuric acid (H_2SO_4), shall not exceed .01 percent when determined in accordance with 4.5.3.

3.2.5 Stability. - The DEGDN shall not change the color of standard potassium iodide starch paper in less than ten (10) minutes at 82.2°C when determined in accordance with 4.5.4.

3.3 First article. - When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3).

*3.4 Workmanship. - All material shall be manufactured in the best workmanlike manner. The material shall be free of any contaminants. The cleaning method shall not be injurious to the manufacturing equipment nor become a contaminant to the material.

4.0 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. - The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

a) First article inspection
b) Quality conformance inspection

4.3 First article inspection.

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of approximately 100 grams, or as otherwise specified by the Contracting Officer of DEGDN obtained by sampling as described in 4.4.3.1. The sample shall be obtained from a production lot which has been produced by the contractor using the same production processes, procedures, equipment and materials which will be used in fulfilling the contract. All materials shall be obtained from the same sources of supply as will be used in regular production.

4.3.2 Inspections to be performed. - The sample will be subjected by the Government (see Table I) to any or all of the examinations or tests specified in 4.5.

Table I. First Article Tests.

Test	Requirement	Test Method
Nitrogen Content	3.2.1	4.5.1
Moisture Content	3.2.2	4.5.2
Alkalinity	3.2.3	4.5.3
Acidity	3.2.4	4.5.3
Stability	3.2.5	4.5.4
Workmanship	3.4	Visual

4.3.3 Rejection. - See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Lot formation. - A lot shall consist of one or more batches of DEGDN produced by one manufacturer, in accordance with the same specification, or same specification revision, under one continuous set of operating conditions. Each lot shall consist of that quantity of DEGDN that has been subjected to the same unit chemical or physical mixing process intended to make the final product homogeneous (see MIL-A-48078).

4.4.2 Examination. - The examinations listed in Table II shall be performed on inspection lots as defined in 4.4.1. If the sample fails to comply with any of the requirements, the batch of the lot shall be rejected.

4.4.3 Testing. - PRECAUTION: This specification covers sampling and testing of toxic and hazardous materials. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing the DEGDN. (See 6.3.)

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

4.4.3.1 Sampling. - The DEGDN shall be sampled in accordance with established procedures of the manufacturing agency. A representative sample of approximately 60 ml shall be removed from each batch of the lot. The DEGDN shall be transferred to a rubber bottle fitted with a stopper (see 6.3) and the sample shall be properly identified. The sample shall be tested in accordance with the applicable methods given in 4.5. If the sample fails to meet any of the test requirements, the batch of the lot shall be rejected. MIL-STD-105 shall apply for defect classification given in Table II.

4.4.3.2 Inspection equipment. - For the performance of all tests and examinations specified, commercial inspection equipment should be employed. The contractor shall have available, and utilize correctly, this equipment and is charged with the responsibility of assuring that proper calibration procedures are followed. Government approval of all inspection equipment is required prior to its use for acceptance purposes.

4.4.3.3 Tests.

Table II. Lot Acceptance Tests.

Test/Examination	Requirement	Defect Classification
Nitrogen	3.2.1	Major
Moisture	3.2.2	Major 1/
Alkalinity	3.2.3	Major
Acidity	3.2.4	Major
Stability	3.2.5	Critical
Workmanship	3.4	Minor
1/ When the DEGDN is used at the point of manufacture in the production of propellant by the water slurry method or by the water emulsion method, the moisture requirement shall not apply.		

4.5. Test methods and procedures. - All tests given in this section shall be performed using prescribed procedures for replicate determinations given in standard analytical chemistry textbooks. Also, unless otherwise specified herein, all chemicals shall be Reagent Grade or ACS Grade in accordance with MIL-STD-1218.

4.5.1 Nitrogen. - The nitrogen shall be determined in accordance with Method 209.3 of Standard MIL-STD-286 or equivalent Method T 209.11.

4.5.2 Moisture. - The moisture shall be determined in accordance with Method 101.5 of Standard MIL-STD-286.

4.5.3 Acidity or alkalinity. - The acidity or alkalinity shall be determined in accordance with Method 107.1 of Standard MIL-STD-286 using tolulene as the solvent.

4.5.4 Determination of stability. - The stability shall be determined in accordance with MIL-N-246, paragraph 4.3.4.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

5.0 PACKAGING

5.1 Preservation, packing and packaging. - Diethylene Glycol Dinitrate is classed as a "Forbidden Explosive" in Code of Federal Regulations, Title 49, parts 100-199, for the Transportation of Explosives and Other Articles by Freight. For shipment by public highways see CFR, Title 49, Section 173.51 and Special Permit No. 5704 of the Department of Transportation (DOT) Hazardous Materials Regulations.

5.2 Marking. - The marking of interior packages and exterior shipping containers shall be in accordance with instructions contained in Special Permit No. 5704, Interstate Commerce Commission Regulations and in accordance with Standard MIL-STD-129.

6.0 NOTES

6.1 Intended use. - The DEGDN of this specification is intended for use as a propellant ingredient.

6.2 Ordering data. - See MIL-A-48078.

6.3 Toxicity. - The DEGDN may cause dilation of blood vessels, headache, nausea, sinuses, and reduce blood pressure. Extreme exposures resulting from inhalation, skin contact or ingestion may result in central nervous system depression, coma, and respiratory paralysis. Drinking of any quantity of the liquids must be avoided. Severe headache shortly after exposure may diminish after development of tolerance. Ventilation should be used to reduce the inhalation hazard. Protective gloves and aprons are helpful in avoiding skin contact. Frequent washing in soap and water will minimize skin absorption. Alcohol or other solvents should not be used on the skin. The threshold limit value ceiling is 0.2 ppm.

*6.4 Submission of inspection equipment designs for approval. (See MIL-A-48078.) - Submit equipment designs, as required to Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I-(D), Picatinny Arsenal, New Jersey 07806-5000.

*6.5 Equivalent test methods. - Prior approval of the Contracting Officer is required for use of an equivalent test method. A description of the proposed method should be submitted through the Contracting Officer to: Commander, ARDEC, ATTN: AMSMC-QAR-(D), Picatinny Arsenal, New Jersey 07806-5000. This description should include but not be limited to the procedures used, the accuracy and precision of the method currently used versus the proposed method, test data to demonstrate the accuracy and precision and drawings of any special equipment required.

Supersedes page 6 dated 21 November 1986.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

6.6 Contract data requirements. - One copy of all description sheets and firing records required by this specification shall be forwarded to:

Commander
U.S. Army Armament Research, Development and Engineering Center
U.S. Army Armament Munitions and Chemical Command
ATTN: AMSMC-QAR-R(D)
AMSMC-LCA-G(D)
*Picatinny Arsenal, NJ 07806-5000

Commander
U.S. Army Armament Munitions and Chemical Command
ATTN: AMSMC-QAD(R)
Rock Island, IL 61299.

6.7 Keywords. -
Ammunition
Cartridge
Cannon
Diethylene Glycol Dinitrate (DEGDN)
Tank

6.8 The margins of this standard are marked with asterisks to indicate where significant changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations.

Custodian
Army-AR

Preparing Activity
Army-AR

Project Number: 1315-AB53

Supersedes page 7 dated 21 November 1986.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.