MIL-A-55680A (AV)
AMENDMENT 2
25 November 1981
SUPERSEDING
AMENDMENT 1
26 January 1973

MILITARY SPECIFICATION

ANTENNA AT-1108( )/ARC

Page 1

2.1: Delete "MIL-E-5272 Environmental Testing, Aeronautical Associated Equipment For".

Page 2

3.5.3: Add "according to contract" to the end of line 1.

Page 4

3.11: Change "Specification MIL-E-5272" to "MIL-STD-810".

3.11.1b Change "+71°C" to "+85°C".

Page 5

3.12.2: Change "2.0:1.0" to "3.0:1.0".

3.12.5: Change "20 db" to "40 db".

3.12.6: Change "2.0:1.0" to "3.0:1.0".

Page 10

4.7: Change "MIL-E-5272" to "MIL-STD-810" and change "Five (5) percent" to "fifty (50) percent".

4.7.1: Change "Procedure I of Specification MIL-E-5272" to "Method 504.1 of MIL-STD-810 for Category 5 equipment". Delete Step 5. Change next to last sentence to read as follows: "Any type of chamber of adequate size to hold the specified ground plane will suffice for this test since only possible changes in the VSWR are sought"

4.7.2: Change "Procedure I of Specification MIL-E-5272" to "Method 507.1, Procedure II of MIL-STD-810".

4.7.3: Change "Procedure XII of Specification MIL-E-5272" to "Method 514.1, Category b.1, Procedure I, Part 1 of MIL-STD-810. Add "Curve B shall be used from 5 to 33 Hertz. Curve D shall be used from 33 to 500 Hertz".

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:53Z
Check the source to verify that this is the current version before use.

4.7.4: Change "Procedure II of Specification MIL-E-5272" to "Method 506.1, Procedure I, of MIL-STD-810".

4.7.5: Change "Procedure I of Specification MIL-E-5272" to "Method 510.1 of MIL-STD-810".

Page 11

4.7.6: Change "Procedure V of Specification MIL-E-5272" to "Procedure III Method 516.2 of MIL-STD-810".

4.7.7: Change "Procedure III of Specification MIL-E-5272" to Procedure II, Method 513.2 of MIL-STD-810".

4.7.8: Change "Method 509" to "Method 509.1".

4.8.5: Delete entire paragraph and replace with the following:

4.8.5: Isolation, bands. - Under standard test conditions mount the antenna on the 4 ft ground plane and feed a signal to the VHF connector and measure the resultant signal from the UHF connector, then feed a signal to the UHF connector and measure the resultant signal from the VHF connector, (the cable loss shall be determined at each test frequency when recording the isolation between the feed connectors). These measurements shall be made at standard test frequencies to determine compliance with 3.12.5.

CUSTODIAN:

Army - AV

Preparing Activity

Army - AV

Project No. 5821 A156

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:53Z
Check the source to verify that this is the current version before use.