MILITARY SPECIFICATION
BONDING OF PRECISION MIRRORS
(Glass-to-Metal)

This amendment forms a part of Military Specification MIL-B-50772(MU), dated 24 March 1972 and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 3.1.4: Delete and substitute the following:

"3.1.4 Spacers.- Unless otherwise specified on the drawing or other documents (see 6.2), spacers used to control bonding thickness shall be 1/4" ± 1/64" diameter by 0.025" ± 0.002" thick cellulose acetate in accordance with L-P-504."

Paragraph 3.2.2: Delete and substitute the following:

"3.2.2 Bond configuration.- The bond area shall be located as shown on the applicable assembly drawing."

Paragraph 3.2.4.2: Delete entire paragraph and the caution note and substitute the following:

"3.2.4.2 Adhesive application.- Place the mirror in the fixture with the surface to be bonded facing up. "Puddle" the adhesive at the location(s) specified on the assembly drawing. A sufficient, but not excessive, quantity of adhesive should be deposited such that when the metal mounting bracket is placed in position, a bond of the required area and thickness will be formed."

Paragraph 3.2.4.3: Delete entirely.

Paragraph 3.2.4.4: Delete and substitute the following:

"3.2.4.4 Metal component positioning and application of pressure.- Carefully locate the metal component on the adhesive puddles in the proper position as shown on the applicable drawing. Slowly and evenly apply pressure to the back of the metal component so that the adhesive flows out to form the specified bond area and the metal component bottoms on the spacers to yield the specified bond thickness. Maintain a moderate pressure not greater than 5PSI on the assembly during the oven cure."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:37Z
Check the source to verify that this is the current version before use.

Paragraph 6.1 Intended use: Delete the third sentence and substitute the following:

"This bonding method is also generally applicable to all bonded mirror assemblies."

Paragraph 6.2: Delete and substitute the following:

"6.2 Ordering data.- Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

a. Title, number and date of this specification.

b. Spacer size (see 3.1.4).

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 12GP-A039Y

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:37Z
Check the source to verify that this is the currentversion before use.