MIL-C-60537(MU)
AMENDMENT 2
7 November 1967
SUPERSEDING
AMENDMENT 1
3 April 1967

MILITARY SPECIFICATION
CARTRIDGE, GRENADE: 5.56MM, XM195

This amendment forms a part of Military Specification MIL-C-60537(MU) dated 23 August 1966.

* Paragraph 3.4, Line 2: Delete "5 pounds per square inch" and substitute "2 pounds per square inch".

* Paragraph 3.5, Line 1: Delete the words "The sample cartridges fired in a horizontal position and" and substitute "The sample cartridges conditioned for a minimum of 4 hours and fired in a horizontal position".

Paragraph 4.3.3.1, Table II under Test: After Function and Casualty, delete footnote mark "5/" and substitute "4/"; after Primer Sensitivity, delete footnote mark "6/" and substitute "5/".

* Paragraph 4.3.3.1, Table II: Delete footnote 5/ and substitute:

"5/ Prior to assembly into cartridges, a sample of primers from each primer lot shall be inserted into cartridge cases and tested for sensitivity. The cartridge cases for this test shall be taken from regular production. The test samples shall consist of the number of primed cartridge cases required for performance of a complete run-down test wherein fifty primers are tested at each height. If the average critical height ($\overline{H}$) plus three standard deviations (3 sigma) exceeds 12 inches, or if the average critical height ($\overline{H}$) minus three standard deviations (3 sigma) is less than 3 inches, the lot of primers shall be rejected subject to performance of a second complete run-down test wherein one hundred primers are tested at each height. Failure of the second sample to comply with the above criteria shall be cause for rejection of the lot of primers."

Paragraph 4.3.3.2, Table III, under Defects:

Defect No. 2, Change "Primer Lead" to read "Primer Leak".

After Defect No. 3, Case Casualties add footnote mark "2/".

FSC 1330

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.

* Page 8, Paragraph 4.4.1: Delete and substitute:

"4.4.1 Residual stress (mercurous nitrate).- The test shall be conducted in accordance with AMSMU-P715-501FA1, paragraph 8.4.2, except that the entire test sample shall be used in lieu of one-half the test sample."

* Paragraph 4.4.6, Delete and substitute:

"4.4.6 Primer sensitivity.- The primers shall be inserted into the cartridge cases to the depth specified on Drawing C10534926. The test shall be conducted in accordance with AMSMU-P715-501FA1."

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1330-A162

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.