INCH-POUND

MIL-D-48435A (AR)
AMENDMENT 1
27 August 1992

MILITARY SPECIFICATION

DISTRIBUTION BOX: 10548533

This amendment forms a part of MIL-D-48435A (AR), dated 16 May 1990, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

"12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete in its entirety and substitute the following:

"3.3.1 Vibration. The distribution box shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

3.3.3, 3.3.3.1 and 3.3.3.2: Delete in their entirety and substitute the following:

"3.3.3 Altitude operating. The distribution box shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

PAGE 4

3.4.1: Delete in its entirety.

3.5.1: Delete in its entirety and substitute the following:

"3.5.1 DC input voltage isolation. With the Distribution Box Mode switch (S1) set to NORMAL and the Maintenance switch (S4) set to ON, the ratio of forward and reverse bias requirements between pins J3-c and J3-V, and J3-p and J3-V shall be 200 or greater."

PAGE 5

3.5.2, first sentence: Change "+24.3" to "+24.0".

3.5.3:

First sentence: Change "+24.3" to "+24.0".

Last sentence (bottom of page): Delete "There...SELECT))." in its entirety.

PAGE 6

3.7: Delete in its entirety and substitute the following:

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 11

4.7.1.1: Delete first sentence in its entirety and substitute the following:

"This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.2, first sentence: Change "516.3" to "516".

4.7.1.3: Delete in its entirety and substitute the following:

"4.7.1.3 Altitude operating. This test shall be performed as specified in Procedure II, Method 500 of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:26Z
Check the source to verify that this is the current version before use.

4.7.1.4.1, first sentence: Change "501.2" to "501".

4.7.1.4.2, first sentence: Change "502.2" to "502".

PAGE 12

4.7.1.5, first sentence: Change "507.2" to "507".

4.7.2: Delete last sentence "Verify...pins." in its entirety.

4.7.3.2, first sentence: Change "+24.3" to "+24.0".

PAGE 13

4.7.3.3: Delete last sentence "Using...SELECT)." in its entirety.

4.8: Delete in its entirety and substitute the following:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A806)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.