MILITARY SPECIFICATION
FUZE, ELECTRONIC TIME: M587
(LOADING, ASSEMBLING, AND PACKING)

This specification is approved for use by USA Armaments Research and Development Command, Department of the Army, and is available for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This Military Specification covers a fuze designated as Fuze Electronic Time: M587 for use in 105mm howitzer, 155mm howitzer, 175mm gun and 8-inch howitzer.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

Military

MIL-A-2550 -- Ammunition and Special Weapons, General Specification for

MIL-F-60965 -- Fuze Electronic Time: M587 (Less Booster Pellet and Cup)

MIL-Q-50829 -- General Quality Assurance Provisions for Proximity Fuzes and Related Components

Beneficial comments (recommendations, additions, deletions) and any pertinent data which maybe of use in improving this document should be addressed to: USA Armament Research and Development Command, ATTN: DRDAR-TST-S, Dover, NJ, 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105 -- Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-1167 -- Ammunition Data Card

MIL-STD-1168 -- Lot Numbering of Ammunition

DRAWINGS

USA, Harry Diamond Laboratories (FSCM 19202)

PL 11711435 -- Fuze Electronic Time: M587 (Loaded)

PDL 11711435 -- Fuze Electronic Time: M587 (Loaded) Packaging For

EDL 11711435 -- Equipment Data List for Fuze, Electronic Time: M587 (Loaded)

PUBLICATIONS

AMCR-385-224 (RDM7-224) -- AMC Safety Manufal (copies of Specifications, Standards, Drawings, and Publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or requests for proposal shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 171-190 -- Department of Transportation Rules and Regulations for the Transportation of Hazardous Materials

(Requests for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D.C. 20402)

3. REQUIREMENTS

3.1 Design and construction. Design and construction shall be in accordance with HDL Drawing 11711435.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

3.1.1 Material. Material shall be in accordance with applicable drawings.

3.1.2 Booster. The booster pellet shall be in accordance with HDL drawing 11720213.

3.1.3 Booster cup. The booster cup shall be in accordance with HDL drawing 11720206.

3.2 Ballistic requirements. The loaded fuze shall meet the applicable ballistic requirements of MIL-F-60965.

3.3 Workmanship. All parts shall be manufactured and finished in a thoroughly workmanlike manner to insure satisfactory functioning and durability. All parts shall be free from chips, dirt, rust, grease, burrs, and corrosion and any other foreign material. The cleaning methods used shall not be injurious to any parts, cause corrosion, or other damage to any part of the assembly, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE SYSTEM

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Contractor quality assurance system. The contractor shall provide and maintain an adequate quality system in compliance with MIL-Q-50829.

4.2 Government verification. All quality assurance operations performed by the contractor will be subject to Government verification in compliance with MIL-Q-50829.

4.3 Quality conformance inspection. Inspection shall be as specified in MIL-A-2550 and in this document.

4.3.1 Lot formation. The loaded lot shall be the same size as the lot of fuzes (Less Booster Cup and Booster Pellet).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.2 Sampling. Sampling for classification of defects shall be in accordance with MIL-STD-105 and this document. Unless otherwise specified, inspection level II shall apply.

4.3.2.1 Ballistic sample. The sample of fuzes (11711433) to be used for Ballistic tests (see 6.1.3) shall be loaded with booster pellet (11720213) and booster cup (11720206) which have been randomly selected from the lot or lots of booster pellets and booster cups that are to be used in the final assembly of the lot. (The ballistic sample shall contain a proportionate quantity from each lot of booster pellets and booster cups required to complete the fuze lot.) After the ballistic sample has passed, the remainder of the fuzes (11711433) shall have booster pellets and booster cups installed, and samples shall then be drawn for inspections specified in 4.3.5.

4.3.3 Lot acceptance. Lots shall be accepted on the basis of Classification of defects (4.3.5), Ballistic tests (4.3.6), and Material and component certifications (4.3.7). The contractor shall notify the Government QA representative prior to proceeding with inspection for Classification of defects (4.3.5).

4.3.4 Data recording. A written record of the inspection for classification of defects shall be made, but only the defect summary need by supplied to the Government. This sujmary shall be forwarded to the designated Government agency within two (2) working days after Government acceptance of the lot.

4.3.5 Classification of defects. The fuze components, fuze assembly, and packing shall be inspected by using the Classification of defects and applicable drawings. Any of the defect characteristics may be checked on a higher assembly than is indicated in the classification, if desired by the contractor, but in no case shall be checked at a lower assembly level.

4.3.5.1 Fuze, Electronic Time: M587 (Loaded) (11711435)

Categories	Defects	AQL	Method of Inspection
Major			
101	Error on interrogation	100 percent Screening	Fuze Setter M36 DS-1
102	Booster pellet missing	0.15	X-ray (Class II film)
103	2.00-12-UNS-1A thread damaged	0.65	Gage (11004579) as listed on EDL 11711435

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

Categories	Defects	AQL	Method of Inspection
Major			
104	Seating shoulder to aft end exceeds maximum	0.65	Gage (11004579)
105	Booster cup diameter or true position exceeds maximum	0.65	Gage (11004579)
Minor			
201	Booster cup improperly sealed	0.65	Visual DS-2

4.3.5.2 Box, ammo, metal for artillery type and rocket fuzes (8864492).

Categories	Defects	AQL	Method of Inspection
201	Dessicant bag missing	1.5	Visual
202	Marking omitted or illegible	1.5	Visual
203	Cuts or wrinkles in rubber gasket	1.0	Visual
204	Sealing edge of box damaged	1.0	Visual
205	Packing material missing	1.0	Visual
206	Seal leaking (sample size of 20)	2.5	DS-3
207	Loaded box weight incorrect (fuze missing)	1.0	Scale
208	Contents loose	1.0	DS-4

4.3.5.3 Box, wirebound, packing ammunition for artillery type or rocket fuzes (8861213).

Categories	Defects	AQL	Method of Inspection
Minor			
201	Marking omitted or illegible	0.65	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

Categories	Defects	AQL	Method of Inspection
Minor			
202	Seal missing	0.65	Visual
203	Box broken, board loose or protruding nail	0.65	Visual/Manual
204	Contents loose	0.65	Manual

4.3.5.4 Palletizing for M587 Fuze (11726814).

Categories	Defects	AQL	Method of Inspection
201	Box missing	2.5	Visual
202	Strapping loose	2.5	Visual/Manual
203	Marking misleading or unidentifiable	2.5	Visual

4.3.5.5 Defect standards.

DS-1 The fuze when shipped, either from the contractor or from the loading plant should read "P" when interrogated with the M36 Fuze Setter.

DS-2 Fuze shall have a bead of sealant visable for 360° around the sleeve to booster cup joint.

DS-3 The loaded ammunition box (8864492) shall be placed in an air-tight glass or plastic chamber half filled with water. This inclosure shall have a valve by which pressurized air can be admitted and gaged. The box shall be positioned over the water. The internal chamber pressure shall be increased to 20 PSIG. The chamber shall remain at this stabilized pressure for 2 $\pm$0.5 minutes. The box shall then be lowered into the water and the exhaust valve on the chamber opened so that the pressure drops to atmospheric pressure. The box shall be observed for a minimum of one minute to determine if there are any air leaks. A steady stream or a recurring succession of bubbles from any surface or point shall be cause for rejection.

DS-4 When manually shaken, the package shall not rattle or give other indication of looseness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.6 Ballistic sample tests. The ballistic sample tests shall be performed by the Government at a Government Proving Ground (see 6.1.3).

4.3.7 Material and component certification. Prior to acceptance, the contractor shall demonstrate by means or certifications or statements of findings, that only materials and components conforming to the item specification and drawings have been used.

5. PREPARATION FOR DELIVERY

5.1 Packing, packaging, preservation, and marking. The fuzes shall be packed and marked for shipment as specified on drawings listed on PDL 11711435. The container shall be in accordance with 49 CFR, Parts 171-190. Explosive shipping classification of the smallest shipping package shall be as defined under 49 CFR.

5.2 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

5.3 Ammunition lot number. Lot number information shall be as specifed in MIL-STD-1168.

6. NOTES

6.1 Ordering information.

6.1.1 Documents. Procurement documents shall specify the title, number, and date of this specification.

6.1.2 Data requirements. The following data are required by this specification to be furnished to the Government and should be entered on DD Form 1423 for each contract.

Paragraph	Data requirements	Applicable DID
4.1.1	Contractor furnished designs (MIL-Q-50829, 3.6.1)	DI-R-1713
4.3.4	Defect summary	DI-R-1721
5.2	Ammunition data cards	DI-R-1410

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

6.1.3 Government furnished material. Fuze, Electronic Time: M587 (Less Booster Pellet and Booster Cup) (P/N 11711433) shall be supplied as GFM under the following conditions. The samples for Ballistic test shall be selected from the lot of fuzes (Less Booster) at the plant of the supplying contractor. The sample shall be packaged eight to a metal ammunition box (P/N 8864492) with top support (P/N 9232149) and bottom support (P/N 9232148). The metal cans shall be packed in commercial card-board boxes of optional size, which protect the cans and contents from damage in transportation, and shipped to the loading plant with the rest of the lot, similarly packed. The sample will be assembled with booster pellet (P/N 11720213) and booster cup (P/N 11720206) repacked in the metal boxes, using the supports supplied, and shipped to the testing installation. Upon successful completion of the Ballistic tests, the balance of the lot will be loaded and examined for compliance with the classification of defects.

Custodian:
Army -AR

Preparing Activity:
ARMY: AR

Agent:
ARMY: HD

Project No: 1390-A192

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.