MILITARY SPECIFICATION

NETWORK B: 10526468

This amendment forms a part of Military Specification MIL-N-60210(MU), dated 4 March 1965.

Paragraph 3.4.1.4, Line 5: Delete "minus 6 volts" and substitute "minus 5 volts"; Last line: Delete "minus 2.3 volts" and substitute "minus 3.5 volts".

Paragraph 3.4.5.4: Delete "state" and substitute "stage".

Delete paragraph 3.4.6.2 and substitute new paragraph 3.4.6.2.

"3.4.6.2 Selection and input diodes.- The selection and input diodes shall have a forward voltage drop more positive than -1.0 volt dc, with the following exceptions: The forward voltage drop of diodes CR4 and CR9 shall be more positive than -1.1 volt dc. The forward voltage drop of diodes CR2, CR3, CR6, CR7, CR8 and CR13 shall be more positive than-1.2 volt dc".

Delete paragraph 3.7 Electrical wiring in its entirety and substitute the following:

"3.5 Electrical wiring.- Wiring and connections shall be in accordance with electrical schematic, Drawing F10526471".

Table I, Characteristic 108, Test Procedures Column: Delete "4.5.3.3.1" and substitute "4.5.2.3.1"; Characteristic 121, Test Procedures Column: Delete "4.5.2.6.6" and substitute "4.5.2.6.5".

Table III, Characteristic 305, Test Procedures Column: Add "4.5.1.3.2"; Characteristic 308, Test Procedures Column: Delete "3.5.2.1.4" and substitute "4.5.2.1.4" and add: "4.5.1.5".

Paragraph 4.4.1.1, Item 8, Description Column: Delete "impednace" and substitute "impedance"; Item 13, Description Column: Delete "(Item) 11" and substitute "(Item 10)".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.2.1.4, 4.5.2.2.5, 4.5.2.5.6 and 4.5.2.6.6. In order to demonstrate this capability, the tests of 4.5.2.1.4, 4.5.2.2.5, 4.5.2.5.6 and 4.5.2.6.6 shall be minimum of once each 6 hours of the 24-hour period. The final test shall be conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically energized as described in Table IV."

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2."

Paragraph 4.5.2.1.1.1: Delete and substitute:

"4.5.2.1.1.1 Forward voltage drop.- Connect Pin 7B to the minus 6 volt supply voltage through a 680 ohm, 1/2 watt ± 5% resistor and ground Pin 8B. The voltage measured from ground to Pin 7B shall be less positive than plus 0.5 volt. No other voltage shall be connected during this test."

Paragraph 4.5.2.1.2: Delete "in Pin 5B" and substitute "to Pin 5B".

Paragraph 4.5.2.1.2.2: Delete "temove" and substitute "remove".

Paragraph 4.5.2.1.3, line 6: Delete "minus 6 volts" and substitute "minus 5 volts". And in line 9: Delete "minus 2.3 volts" and substitute "minus 3.5 volts".

Paragraph 4.5.2.1.4, line 2: Delete "03" and substitute "of".

Paragraph 4.5.2.2.1.2, line 6: Delete "ahll" and substitute "shall".

Paragraph 4.5.2.2.4, line 2: Delete "4.5.2.2.1.3" and substitute "4.5.2.2.1.2". Also add at the end of 4.5.2.2.4, the following sentence: "At the end of these tests, remove the resistor load and power supplies connected in 4.5.2.2.1.2".

Paragraph 4.5.2.4.1.2: Delete sentence 4.

Paragraph 4.5.2.5.6, line 1: Delete "5B" and substitute "3B".

Paragraph 4.5.2.6.2: Delete the last sentence and substitute the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

following:

"The voltage measured at the pin specified in Column 2 of Table XV shall be as specified in Column 3 for compliance with 3.4.6.2."

Delete Table XV and substitute new Table XV.

"TABLE XV

1 Ground Pin	2 Measure Voltage at Pin	3 Voltage more positive than
55B	43B	-1.0
44B	43B	-1.0
57B	55A	-1.0
51B	55A	-1.0
26A	24B	-1.0
28B	24B	-1.0
TP1	24B	-1.0
26A	26B	-1.0
26B	25B	-1.0
49B	49A	-1.1
49A	25B	-1.0
41A	26B	-1.0
26B	25A	-1.0
49B	TP1	-1.2
57A	TP1	-1.2
TP1	25A	-1.0
28B	29B	-1.2
29B	29A	-1.0
34A	32A	-1.0
40A	32A	-1.0
32A	29A	-1.0
43A	29B	-1.2
29B	31A	-1.0
34A	33A	-1.0
33A	31A	-1.0
29B	36A	-1.0
40A	49A	-1.1
49A	36A	-1.0
29B	38A	-1.0
TP1	38A	-1.0
43A	45B	-1.2
41A	45B	-1.2
45B	TP3	-1.0
32A	TP3	-1.0
45B	46A	-1.0
57A	33A	-1.0
33A	46A	-1.0
45B	TP2	-1.0
49A	TP2	-1.0
45B	51A	-1.0
TP1	51A	-1.0"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.6.3; Line 5: Delete "26B" and substitute "24B".

Paragraph 4.5.2.6.4; Line 2" Delete "Table 1" and substitute "Table IV".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A052

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.