MIL-P-50578C (AR)
AMENDMENT 2
31October 1980
SUPERSEDING
AMENDMENT 1

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, RA, M549 & M549A1
(WITH WARHEAD AND MOTOR BODY)
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-P-50578C(AR), dated 20 June 1979.

PAGE 31

Paragraphs 4.5.3.1 and 4.5.3.2: Delete in their entirety and substitute the following:

"4.5.3.1 Functioning. All test projectiles shall be conditioned and fired at 70 degrees Fahrenheit ($^{o}$F) at Charge 8, M203 series propelling charge conditioned at 70$^{o}$F. In order to minimize the effects of met conditions the test shall not be fired in either one (for normal inspection) or three (for tightened inspection) series of 10 rounds each. The first two subgroups for tightened inspection shall be fired at a quadrant elevation of 33 degrees and the last subgroups for tightened inspection or the single group for normal inspection shall be fired at a quadrant elevation of 51 degrees. Time lapses of more than 15 minutes between consecutive rounds shall not be permitted and it is desirable that each 10 round series be completed within one (1) hour. Range probable errors shall be calculated for each 10 round subgroup and then a pooled range probable error (for tightened inspection) shall be computed for determination of compliance with 3.6.1.2.1.

$$\text{Subgroup RPE (percent)} = RPEj = \sqrt{\frac{\sum X_i - 1/n\sum(X)^2}{n-1}} \times \frac{100\% \times .6745}{\text{Ave. Range (j)}}$$

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

Pooled RPE (percent) = RPEp =

$$\sqrt{\frac{RPE_1{}^2(n_1-1) + RPE_2\ (n_2-1) + RPE^2\ (n_3-1)}{DF}}$$

Where X = Individual horizontal range within each subgroup.

Where DF = Degrees of Freedom = n + n....n(j) - number of subgroups.

4.5.3.2 Safety. The projectiles for this test shall be divided into three equal groups. Group 1 shall be conditioned and fired at -65°F at Charge 8, M203 series propelling charge conditioned at -65°F. Group 2 shall be conditioned and fired at 145°F with an M203 propelling charge conditioned at 145°F. Group 3 shall be conditioned at 145°F and fired with a PXR-6297 proof propelling charge conditioned at 70°F. The cold phase (Group 1) shall be fired at a quadrant elevation of 51 degrees and the hot phases (Group 2 & 3) shall be fired at a quadrant elevation of 24 degrees."

PAGE 35

* Add the following new paragraph:

"6.13 International standardization agreement. Certain provisions of this specification are the subject of international standardization agreement QSTAG 605. When amendment, revision or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices, if required."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No.: 1320-A561



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z.
Check the source to verify that this is the current version before use.