MIL-W-80105C
AMENDMENT 3
7 March 1988
SUPERSEDING
AMENDMENT 2
3 April 1986

MILITARY SPECIFICATION

WELDING TORCH SETS, ARC, GAS-SHIELDED TUNGSTEN ELECTRODE

This amendment forms a part of Military Specification, MIL-W-80105C, dated 18 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, delete "Size 80 - 80 amp" and substitute "Size 75 - 75 to 80 amp."

PAGE 8

3.5.1, line one, after "electrode extension cap" insert "(except on Model 24)."

3.5.1.1, add to end of paragraph "specified."

PAGE 9

3.5.2, delete and substitute:"

"3.5.2 Gas equipment. Unless otherwise specified (see 6.2.1), each welding set shall be furnished with a pressure regulator and a single or dual flowmeter. The flowmeter or pressure regulator may be furnished as a single unit."

PAGE 10

3.6.4, line 3, after tank add: "or radiator."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:38Z
Check the source to verify that this is the current version before use.

3.5.2.1, delete and substitute:

"3.5.2.1 Flowmeter. The flowmeter shall be of the floating ball type, with single or dual calibrations. Single flowmeters shall measure one gas and dual flowmeters shall measure two gases. The minimum range shall be from 5 to 95 cubic feet per hour for helium and 0 to 60 cubic feet per hour for argon."

3.5.2.2, delete and substitute:

"3.5.2.2 Pressure regulator. The pressure regulator shall have an input gage calibrated in pounds per square inch (PSI) for use with both argon and helium gas. When specified (see 6.2.1), the pressure regulator shall be of the two-stage regulating type."

PAGE 13

6.2.1, following "k" insert:

"l. Equipment furnished, if different (see 3.5.2)."

"m. Two-stage regulator, when specified (see 3.5.2.2)."

6.2.1,i. delete and substitute:

"i. Specify length of each extension cap required, in inches: (see (see 3.5.1) (2-19/64, 3-3/16, 3-5/16, 3-13/16, 3-3/4, 7-1/8, 7-3/8, 7-15/16, 7-7/16, and 3-3/8). Specify each nozzle length required, standard nozzle lengths available, in inches: (5/8, 1, 1-5/32, 1-5/16, 1-7/32, 1-11/16, 1-13/16, 1-7/8, 1-27/32, 1-31/32 and 3-7/32)."

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review activities:
Army - ME, CE
Navy - SH
Air Force - 84
DLA - GS

User activities:
Navy - YD, MC, CE

Preparing activity:
DLA - IP

Project (3431-0191)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:38Z
Check the source to verify that this is the current version before use.