
INCH-POUND
MIL-C-39010/2D
4 January 1994
SUPERSEDING
MIL-C-39010/2C
1 March 1985

MILITARY SPECIFICATION SHEET

COILS, FIXED, RADIOFREQUENCY, MOLDED, MICROMINIATURE, MAGNETICALLY SHIELDED (IRON CORE-IRON SLEEVE), ESTABLISHED RELIABILITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-39010.



Ltr	Dimensions are in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
A	.152 (3.86)	172 (4.37)
B	390 (9 91)	430 (10.92)
C	1 250 (31.75)	1 626 (41.30)
D	023 (0.58)	027 (0 69)

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for information only

FIGURE 1 Dimensions and configuration

(D) denotes changes

AMSC N/A FSC 5950

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:30Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions See figure 1

Material Iron core with iron sleeve.

(D) Weight 0.04 ounce maximum.

Operating temperature range: -55°C to +105°C

Dielectric withstanding voltage. Method 301 of MIL-STD-202; test voltage of 1,000 V rms.

Barometric pressure Method 105, test condition C, of MIL-STD-202; 70,000 feet with a test voltage of 200 V rms.

Electrical characteristics: See tables I and II.

Inductance See table I

Inductance tolerance See table I.

Q values See table I

Self-resonant frequency See table I

Percent coupling 3 percent maximum

DC resistance. See table I.

Temperature rise 15°C.

Terminal pull 5 pounds

(D) Part or Identifying Number (PIN) M39010/02 (dash number from table I)

(D) Supersession data. This specification supersedes MS75088 dated 4 September 1985.

Source: https://assist.dla.mil -- Downloaded: 20260-21T16:30Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial) and dash numbers.

Dash number 1/	Inductance µH	Inductance tolerance ± percent	Q minimum	Test frequency (MHz)	Self-resonant frequency minimum (MHz)	DC resistance (25°C) maximum (ohms)	Rated dc current (mA) 2/
AR91**	.91	5	44	25	140	.07	1,070
A1R0**	1 00	5, 10	44	25	140	.07	1,070
A1R1**	1.10	5	44	7.9	130	.10	895
A1R2**	1.20	5, 10	44	7.9	130	.10	895
A1R3**	1.30	5	44	7.9	115	12	815
A1R5**	1.50	5, 10	44	7 9	115	12	815
A1R6**	1.60	5	44	7.9	105	.14	755
A1R8**	1.80	5, 10	44	7.9	105	.14	755
A2R0**	2 00	5	44	7.9	100	19	650
A2R2**	2 20	5, 10	44	7 9	100	19	650
A2R4**	2 40	5	44	7.9	92	.28	535
A2R7**	2.70	5, 10	44	7 9	92	.28	535
A3R0**	3.00	5	44	7 9	85	.35	480
A3R3**	3.30	5, 10	44	7 9	85	.35	480
A3R6**	3 60	5	44	7.9	75	40	450
A3R9**	3.90	5, 10	44	7.9	75	40	450
A4R3**	4.30	5	44	7 9	70	.55	380
A4R7**	4.70	5, 10	44	7.9	70	.55	380
A5R1**	5.10	5	44	7 9	65	.72	335
A5R6**	5.60	5, 10	44	7.9	65	.72	335
A6R2**	6 20	5	44	7 9	55	1.02	280
A6R8**	6.80	5, 10	50	7.9	55	1.02	280
A7R5**	7 50	5	50	7 9	50	1.32	245
A8R2**	8.20	5, 10	50	7.9	50	1.32	245
A9R1**	9.10	5	50	7 9	46	1.62	220
A100**	10.00	5, 10	50	7 9	46	1.62	220
A110**	11.0	5	50	2 5	44	2 00	200
A120**	12 0	5, 10	50	2.5	44	2 00	200

1/ The complete dash number will include two additional letters (indicated by **). The first additional letter will indicate the inductance tolerance and the second additional letter will indicate the failure rate symbol (e.g , M, P, R, S) and will be added to the end of the dash number

2/ The rated dc current is based on 90°C ambient temperature with a 15°C rise

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:30Z
Check the source to verify that this is the current version before use.

(D) TABLE II Electrical characteristics (final) 1/

Inspection group	Allowable variation from initial measurement		Allowable percent from specified minimum value in electrical characteristics (initial) table	
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±5	---	---	-10
Group IV	±5	±(3% +.001 ohm)	2/	-10
Group V	±5	±(2% +.001 ohm)	2/	-10
Quality conformance inspection Group B				
Subgroup 1	±5	±(2% +.001 ohm)	2/	-10
Subgroup 3	±5	---	---	-10
Subgroup 4	±5	±(3% +.001 ohm)	2/	-10

1/ Test fixture allowance of + 01 µH shall be added to all change in inductance limits ±(_ percent +.01 µH)

2/ The self-resonant frequency shall be not less than the value specified in table I

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - AR, ME, MI
Navy - AS, CG, MC, OS, SH
Air Force - 17, 19, 99
DLA - ES

Preparing activity
Army - ER

Agent
DLA - ES

(Project 5950-0831-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:30Z
Check the source to verify that this is the current version before use.