
MILITARY SPECIFICATION SHEET

COILS, FIXED, RADIOFREQUENCY, MOLDED, MICROMINIATURE (PHENOLIC CORE), ESTABLISHED RELIABILITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-39010.



Ltr	Dimensions are in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
A	.146 (3.71)	.166 (4.22)
B	.365 (9.27)	.385 (9.78)
C	1.250 (31.75)	1.626 (41.30)
D	.023 (0.58)	.027 (0.69)

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for information only.

FIGURE 1. Dimensions and configuration

(D) denotes changes

AMSC N/A

FSC 5950

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1.

Material: Phenolic core.

(D) Weight: 0.03 ounce maximum.

Operating temperature range: -55°C to +125°C.

Dielectric withstanding voltage: Method 301 of MIL-STD-202; test voltage of 1,000 V rms.

Barometric pressure: Method 105, test condition C, of MIL-STD-202; 70,000 feet with a test voltage of 200 V rms.

Electrical characteristics: See tables I and II.

Inductance: See table I.

Inductance tolerance: See table I.

Q values See table I

Self-resonant frequency: See table I.

DC resistance: See table I.

Temperature rise: 35°C.

Terminal pull. 5 pounds.

(D) Part or Identifying Number (PIN): M39010/06 (dash number from table I).

(D) Supersession data: This specification supersedes MS18130 dated 16 September 1985.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:31Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial) and dash numbers.

Dash number 1/	Inductance µH	Inductance tolerance ± percent	Q minimum	Test frequency (MHz)	Self-resonant frequency minimum (MHz)	DC resistance (25°C) maximum (ohms)	Rated dc current (mA) 2/
BR15**	.15	5, 10, 20	50	25.0	525	0.030	2,450
BR16**	.16	5	50	25.0	460	0.055	1,810
BR18**	.18	5, 10	50	25.0	460	0.055	1,810
BR20**	.20	5	50	25.0	460	0.055	1,810
BR22**	.22	5, 10, 20	50	25.0	460	0.055	1,810
BR24**	.24	5	45	25.0	360	0.090	1,400
BR27**	.27	5, 10	45	25.0	360	0.090	1,400
BR30**	.30	5	45	25.0	360	0.090	1,400
BR33**	.33	5, 10, 20	45	25.0	360	0.090	1,400
BR36**	.36	5	45	25.0	310	0.12	1,225
BR39**	.39	5, 10	45	25.0	310	0.12	1,225
BR43**	.43	5	45	25.0	310	0.12	1,225
BR47**	.47	5, 10, 20	45	25.0	310	0.12	1,225
BR51**	.51	5	45	25.0	280	0.135	1,150
BR56**	.56	5, 10	50	25.0	280	0.135	1,150
BR62**	.62	5	50	25.0	250	0 150	1,100
BR68**	.68	5, 10	50	25.0	250	0.150	1,100
BR75**	.75	5	50	25.0	220	0.220	900
BR82**	.82	5, 10	50	25.0	220	0.220	900
BR91**	.91	5	50	25.0	200	0.290	785
B1R0**	1.00	5, 10	50	25.0	200	0.290	785
B1R1**	1.10	5	33	7.9	180	0.420	650
B1R2**	1.20	5, 10	33	7.9	180	0.420	650
B1R3**	1.30	5	33	7.9	160	0.500	600
B1R5**	1.50	5, 10	33	7.9	160	0.500	600
B1R6**	1.60	5	33	7.9	150	0.650	525
B1R8**	1.80	5, 10	33	7.9	150	0.650	525
B2R0**	2.00	5	33	7 9	135	0.950	435
B2R2**	2.20	5, 10	33	7.9	135	0.950	435
B2R4**	2.40	5	33	7.9	120	1.20	385
B2R7**	2.70	5, 10	33	7.9	120	1.20	385
B3R0**	3 00	5	33	7.9	110	2.00	300
B3R3**	3.30	5, 10	33	7.9	110	2.00	300
B3R6**	3.60	5	33	7 9	100	2.30	280
B3R9**	3.90	5, 10	33	7.9	100	2.30	280
B4R3**	4.30	5	33	7.9	90	2.60	260
B4R7**	4.70	5, 10	33	7.9	90	2 60	260

1/ The complete dash number will include two additional letters (indicated by **) The first additional letter will indicate the inductance tolerance and the second additional letter will indicate the failure rate symbol (e.g., M, P, R, S) and will be added to the end of the dash number

2/ The rated dc current is based on 90°C ambient temperature with a 35°C rise.

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:31Z
Check the source to verify that this is the current version before use.

(D) TABLE II. Electrical characteristics (final). 1/

Inspection group	Allowable variation from initial measurement		Allowable percent from specified minimum value in electrical characteristics (initial) table	
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±2	---	---	-10
Group IV	±5	±(3% +.001 ohm)	2/	-10
Group V	±5	±(2% +.001 ohm)	2/	-15
Quality conformance inspection Group B				
Subgroup 1	±5	±(2% +.001 ohm)	2/	-15
Subgroup 3	±2	---	---	-10
Subgroup 4	±5	±(3% +.001 ohm)	2/	-10

1/ Test fixture allowance of +.01 µH shall be added to all change in inductance limits ±(_ percent +.01 µH).

2/ The self-resonant frequency shall be not less than the value specified in table I.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, ME, MI
Navy - AS, CG, MC, OS, SH
Air Force - 17, 19, 99
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5950-0831-05)

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:31Z
Check the source to verify that this is the current version before use.