INCH-POUND

MIL-R-39008/5B
23 August 1989
SUPERSEDING
MIL-R-39008/5A
30 December 1983

MILITARY SPECIFICATION

RESISTOR, FIXED, COMPOSITION (INSULATED), ESTABLISHED RELIABILITY STYLE RCR42

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for style RCR42 resistors.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-R-39008 - Resistors, Fixed, Composition (Insulated), Established Reliability, General Specification for.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

* 2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Laboratory Command, Reliability, Logistics and Standardization Division, ATTN: SLCET-R-S, Fort Monmouth, NJ 07703-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5905
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-39008, and as specified herein.

3.2 Design and construction. The resistor shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 Power rating. The power rating shall be 2 watts, based on full load operation (100 percent rated wattage) at an ambient temperature of 70°C. Resistors operated at ambient temperature in excess of 70°C shall be derated in accordance with figure 2. The rated dc or rms continuous working voltage shall not exceed 500 volts.

3.4 Resistance. The minimum resistance value shall be 10 ohms; maximum value shall be 22 megohms.

3.5 Weight. The maximum weight of this style shall be 3.0 grams.

* 3.6 Workmanship. Workmanship shall be as specified in MIL-R-39008.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-R-39008 and as specified herein.

* 4.2 Visual and mechanical examination. Visual and mechanical examination shall be as specified in MIL-R-39008.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-R-39008.

6. NOTES

* (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-R-39008 are applicable to this specification.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:


a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

* 6.3 Power rating. It is essential that no more than 50 percent of the rated wattage be applied if the established failure rate level is to be maintained.

* 6.4 MIL-R-11 substitution data. Resistors of this specification, regardless of their failure rate designation, are substitutes for resistors of the same resistance value and tolerance specified in MIL-R-11/7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:27Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions			
A	.688	(17.48)	±.040	(1.02)
B	1.500	(38.10)	±.125	(3.18)
C	.045	(1.14)	±.003	(.08)
D	.318	(8.08)	±.018	(.46)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in parentheses.
3. Metric equivalents are given for general information only.
4. Lead length for new design and tape and reel packaging shall be 1.00 +.625, -0.000 inch (25.4 +15.88, -0.00 mm).
5. Lead concentric tolerance is to be measured at the point of lead egress from the resistor body.

FIGURE 1. Style RCR42 resistor.




FIGURE 2. Derating curve for high ambient temperatures.

Source: https://assist.dla.mil -- Downloaded: 20261-21T16:27Z
Check the source to verify that this is the current version before use.

* 6.5 High frequency characteristics. Typical values of impedance to dc resistance ratio and phase angle from 100 kHz to 100 MHz are shown on figures 3 and 4 below. Circuit variations in mounting position and lead length can have a significant effect on the high frequency characteristics.




FIGURE 3. Impedance to dc resistance ratio.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:27Z
Check the source to verify that this is the current version before use.




FIGURE 4. Impedance to phase angle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:27Z
Check the source to verify that this is the current version before use.

* 6.6 Peak voltage and pulsed operation. When these resistors are used under low duty cycle pulse applications, the maximum permissible operating voltage is limited by breakdown instead of heating. In such applications, the peak value of the pulse shall not exceed 2.5 times rated rms working voltage or 1,000 volts, whichever is less.

* 6.7 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, OS, TD
Air Force - 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1155-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:27Z
Check the source to verify that this is the current version before use.