A-A-1019A
December 7, 1987
SUPERSEDING
A-A-1019
June 2, 1980

COMMERCIAL ITEM DESCRIPTION

STAPLE, PAPER FASTENING, STANDARD DUTY

The General Services Administration has authorized the use of this commercial item description in lieu of Interim Federal Specification GG-S-00745.

This description covers preformed standard duty staples which are intended to be used for fastening papers.

Salient characteristics.

1. Standard duty staples shall have outside dimensions of 0.500 to .505 inch crowns and 0.250 to 0.266 inch legs. The top face of the staple shall be 0.019 ± 0.001 inch wide. Each staple leg shall be perpendicular to staple crowns to within one degree.

2. Staples shall be cemented together to form a strip. Unless otherwise specified, each strip shall contain no less than 210 staples. Each staple strip shall be a maximum length of 4.30 inches.

3. When staple strips are placed vertically (on end) on a flat, horizontal surface, they shall be perpendicular to that surface to within one degree, in each plane.

4. Unless otherwise specified, staples shall be supplied in boxes containing 24 strips.

5. Tensile strength of the staple wire shall not be less than 135,000 p.s.i. when tested as specified in ASTM Standard Test Method E8.

6. The staples shall be made of either a corrosion resistant metal or have a finish which resists corrosion. When used in a typical office environment, the staples shall not blemish the papers to which they are attached.

DISTRIBUTION STATEMENT A: Approved for public release, distribution is unlimited.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

Standard Clinch. The standard clinch is represented by a staple driven home through two sheets of paper. Each leg shall be folded under so the tips of each leg oppose each other. Further, each tip shall be in a downward slope back toward reentering the paper. The degree and appearance of the clinch shall decline as the number of sheets of paper fastened increases.

Performance. The contractor shall demonstrate that the staple meets the following performance requirements:

With the clinching anvil of the stapler set to produce the standard clinch, insert a full strip of staples. One hundred (100) staples shall be driven and clinched through 2 sheets of 20 pound, chemical wood, bond paper (basis weight 17 x 22 - 500 sheets), conforming to Type IV of Federal Specification UU-P-121N, dated February 14, 1973, continuously, unless jams occur for which the test would be interrupted to clear the jams and for which the jams would be scored against the performance requirements. This test shall be repeated using 23 sheets of paper as described herein, and one hundred (100) operations shall be performed, continuously, unless jams occur for which the test would be interrupted to clear the jams and for which the jams would be scored against the performance requirements. Not less than 95 percent of the staple clinches in each operation shall be properly formed with the standard clinch. Not less than 99 percent of stapling operations in each operation shall be jam free, and jams that do occur shall be cleared easily. Failure to meet these requirements shall be cause for rejection of the box of staples. Each operation as referenced herein refers to the following two distinct operations: 1) the operation using 2 sheets of paper, and 2) the operation using 23 sheets of paper.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Inspection. Inspection, as used herein, is defined as both examination and testing of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

Sampling for inspection and tests. Sampling for inspection and tests shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated. Visual examination of the end item for defects in appearance, construction and workmanship shall be in conformance to the requirements of this description. For examination, except for count, the inspection level shall be II, and the acceptable quality level (AQL) shall be 2.5. The end item shall be tested in accordance with the performance paragraph of this description. The sample for testing shall consist of one box of staples referred to herein, as represented by a single strip randomly selected from it. The sampling plan for test shall be S-2 and 4.0 percent defective. The sample for count shall consist of one box of staples referred to herein, as represented by a single strip randomly selected from it. The sampling plan for count shall be S-2 and 4.0 percent defective.

Lot acceptance. Random samples from each lot shall be examined and tested in accordance with the requirements herein, to determine lot acceptance. A lot shall be all boxes of identical specified staples offered for acceptance at the same time.

Workmanship. Staples shall be free from rust, pitting, and other defects which affect appearance or serviceability.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note. ASTM Standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:11Z
Check the source to verify that this is the current version before use.