COMMERCIAL ITEM DESCRIPTION

LANTERN, ELECTRIC (RECHARGEABLE)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification W-L-210A, Types I and II.

Salient characteristics:

The lantern shall be a complete unit including battery case, light source, switch, handle, reflector assembly, necessary wiring and contacts, a sealed lead acid or nickel-cadmium battery, charger, electric cord (separate or attached), and an adjustable stand or reflector assembly.

Service. Two- and one-half hours continuous service at $70^{\circ} \pm 5^{\circ}$ F without recharging.
For the type I lantern the battery or batteries shall have a minimum of 4.0 volts for rechargeable lead acid or a minimum of 5.0 volts for rechargeable nickel cadmium.
For type II lantern the battery or batteries shall have a minimum of 4.0 volts for rechargeable lead acid or a minimum of 3.6 volts for rechargeable nickel-cadmium.
The battery shall be capable of being recharged a minimum of 200 times.
The charger shall operate on 120 V a.c., 60 Hz, and shall be an integral part of the lantern.
The charger shall recharge the battery within 24-hours at $70^{\circ} \pm 5^{\circ}$ F.
The charger shall have the capability of preventing damage to the battery from overcharging.
The lantern shall be rain-tight as defined in paragraph 32 of UL Standard No. 1236.
Short circuit protection for the internal components.

Beam candlepower. The minimum bean candlepower (candelas) shall be as indicated in table I. The test distance shall be 10-feet between the lantern and photoreceptor. The photoreceptor shall be calibrated using the standard lamp with a color temperature of 2856° K. The photoreceptor shall have a minimum diameter of 1-inch and be equipped with a light filter to yield a response curve matching that of the International Commission on Illumination Standard Observer. The calculation shall be as follows:

$$I = ED^2$$

Where I = Illuminous intensity of the light beam in candelas.
E = Illumination reading of the photometer calculated in footcandles.
D = Distance between lantern and photometer.

Table I - Beam Candlepower

Type	Battery volts	Beam candlepower	Average lamp life hour
I	4.0 or 5.0	17,000	100
II	4.0 or 3.6	4,000	9

The lantern shall have the UL listing mark for rechargeable electric lanterns.
The issues of UL No. 1236 and other test programs in effect on the date of solicitation shall be used to determine compliance with these requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as otherwise provided for under the provision of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.

Packaging, packing and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

UL standards are available from Underwriters Laboratories, Inc., 1285 Walt Whitman Rd, Melville, Long Island, NY 11747.

Preparing activity:

GSA-FSS

GSA DC-01103534

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:13Z
Check the source to verify that this is the current version before use.