[METRIC]

A-A-195D
November 30, 1995
SUPERSEDING
A-A-195C
August 16, 1989

COMMERCIAL ITEM DESCRIPTION

TAPE, PRESSURE-SENSITIVE ADHESIVE (EDGING)

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification L-T-99 which has been canceled.

1. Scope:
This commercial item description covers pressure-sensitive adhesive edging tape which is intended for documents, maps, charts, etc., to protect the edges from tearing or other damage during handling and storage.

2. Salient Characteristics
The backing shall consist of a polyester-fiber or acetate fiber laminate. A tolerance of ± .79 mm (1/32 inch) shall be allowed on all widths.

Tape shall comply with the requirements in Table I when tested with the appropriate test procedure.

TABLE I

	Requirement	Test Method
Adhesion (minimum)	15 N/100 mm (14 oz/in width)	ASTM D 3330M Method A
Tensile (minimum)	437 N/100 mm (25 lb/in width)	ASTM D 3759M

Workmanship. The tape shall be uniformly constructed and free from defects which may impair the utility of the material for the intended use. The adhesive shall be coated in a smooth uniform layer over the entire surface of one side of the tape backing. The tape shall be evenly and tightly wound with no voids. The edges shall be clean cut. When unwound, the tape shall not tear nor shall the adhesive separate from the backing.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Federal Supply Service, 26 Federal Plaza, New York, NY 10278 ATTN.: Engineering Branch (2FYE).

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:05Z
Check the source to verify that this is the current version before use.

3. Regulatory Requirements.

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. Quality Assurance

4.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Sampling for Examination and Testing shall be in accordance with Section 6 of ASTM D 3715M with an AQL of 4 percent defective. The sample unit shall be one roll of tape.

5. Packaging.

Preservation, packing and marking of the tapes shall be as specified in the contract or purchase order.

6. Application for copies of technical documents referenced herein:

The issue date in effect on date of invitation for bids or request for proposal shall be apply.

ASTM standard test methods can be obtained from the American Society for Testing and Materials; 1916 Race Street; Philadelphia, PA 19103.

The Federal Acquisition Regulations (FAR) are available from the Government Printing Office, Washington, D.C. Phone (202) 512-1800.

7. Notes.

7.1 Ordering Data - Purchasers should specify:

a. Length
b. Width
c. Color
d. Preservation, packing and marking.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:05Z
Check the source to verify that this is the currentversion before use.

7.2 National Stock Number Listing:

7510-00-273-9837	7510-00-634-2940	7510-00-634-0284
7510-00-782-6220	7510-00-065-8800	7510-00-093-4798
7510-00-264-3699	7510-00-501-6919	7510-00-634-3050
7510-01-026-4119		

Military Interests:
Custodian:

Army - GL
Navy - SA

Review Activities:
Army - SM, AV

Preparing Activity:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.