A-A-2325
September 27, 1985

COMMERCIAL ITEM DESCRIPTION


FILE, HAND (AMERICAN PATTERN), MILLED CURVED TEETH, FLAT FLEXIBLE BLADE

The General Services Administration has authorized the use of this commercial item description in preference to Type XXIII, Styles A, B, and C of Federal Specification GGG-F-325.

This commercial item description covers hand files used for finishing large flat or slightly curved surfaces of materials in the soft categories and on mild steel.

Salient characteristics:

Material:	Carbon alloy steel.
Width:	Uniform throughout the length.
Thickness:	Uniform throughout the length.
Design:	Both flat sides have milled curved teeth. Both edges smooth (safe). Corners and edges at each end beveled in accordance with good manufacturing practices. Holes near each end countersunk 82 degrees on both sides of the file. Furnished in standard-cut, fine-cut, or smooth-cut as shown in table.
Teeth:	Uniformly cut or etched and of uniform height throughout the fully cut portion. Cutting surfaces hardened to a uniform hardness. The distance between the heel and point of the file, excluding the tang, shall be hardened to not greater than 68 nor less than 64 on the Rockwell C scale. Free from decarburization and brittleness.
Marking:	Marked with the country of origin and the name of the manufacturer or with a trademark of such known character that the source of manufacture may be readily determined.
Workmanship:	The teeth of the file shall be well-defined, sharp, and uniform in height and form. There shall be no evidence of rust or other defect which may impair serviceability, durability, or appearance.



FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

National Stock Number	Length Inches	Dimensions at largest section A Inches	B Inch	Number of teeth per inch Min.	Max.	Allowable distortion (maximum) Inch	Allowable warpage (maximum) Degrees
			Standard-cut				
5110-00-245-3016	14	1-11/32	3/16	7	9	0.050	3
			Fine-cut				
5110-00-560-5295	8	25/32	5/32	15	17	.015	3
5110-00-584-9258	10	1	5/32	13	15	.025	3
5110-00-560-5297	12	1-5/32	3/16	12	14	.025	3
5110-00-245-3015	14	1-11/32	3/16	11	13	.050	3
			Smooth-cut				
5110-00-961-3488	14	1-11/32	3/16	14	16	.050	3

National Stock Number	Flexibility (minimum) Inch arc	Size of holes (approx.) Inch	Distance between holes (approx.) Inches
	Standard-cut		
5110-00-245-3016	5/8	1/4	12-13/16
	Fine-cut		
5110-00-560-5295	1/8	3/16	6-3/4
5110-00-584-9258	1/4	3/16	8-3/4
5110-00-560-5297	3/8	1/4	10-13/16
5110-00-245-3015	5/8	1/4	12-13/16
	Smooth-cut		
5110-00-961-3488	5/8	1/4	12-13/16

Length dimension: Overall length as specified plus or minus 3/16 inch.

Tolerance: Width (A) - plus or minus 1/16 inch.
Thickness (B) - plus or minus 1/16.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.