[INCH-POUND]
A-A-300B
September 24, 1996
SUPERSEDING
A-A-300A
February 13, 1991
A-A-299
May 7, 1980

COMMERCIAL ITEM DESCRIPTION

DUSTPAN

The General Services Administration has authorized the use of this commercial item description (CID), for all Federal agencies.

1. SCOPE

1.1 Scope. This commercial item description covers metal and non metal dustpans.

2. CLASSIFICATION

2.1 Classification. The dustpans shall be of the following types.

Type I - Rubber/plastic
Type II - Steel
Type III - Steel, with a swinging pan.

3. SALIENT CHARACTERISTICS

3.1 Construction. The dustpan shall be constructed so that the front edge shall be in continuous contact with the floor when in use or when pressed to the floor with slight downward pressure applied to the handle. The dustpan shall have a dirt retaining ridge formed within the pan. The handle shall have a means for attaching to a wall.

3.1.1 Type I. The type I dustpan shall be a one-piece construction made from natural rubber, synthetic rubber, a combination of natural and synthetic rubber, a combination of plastic and synthetic rubber, or plastic. The plastic shall be either high density polyethylene or polypropylene. The front edge of the dustpan shall be 10-1/2 to 12-1/2 inches (26.7 - 31.8 cm) wide. The side edges shall be a minimum of 7 inches (17.8 cm) long. The handle shall be a minimum of 3-1/2 inches (8.9 cm) long.

3.1.2 Type II. The type II dustpan shall be made from 0.0127 inch (0.32 mm) minimum thickness sheet steel. Seams shall be sealed to prevent dust leakage. The front edge of the dustpan shall be 11 to 13 inches (27.9 - 33.0 cm) wide. The side edges shall be a minimum of 7 inches (17.8 cm) long. The handle shall be a minimum of 4 inches (10.0 cm) long. The dustpan shall have a durable protective finish to prevent corrosion.

3.1.3 Type III. The type III dustpan shall consist of a pan and a handle. When the dustpan is lifted from the floor by the handle, the pan shall swing downward by gravity into a vertical position so that debris will move into the hooded area. The handle shall balance in the upright position when the pan is flat on the floor. The handle shall not interfere with the entrance of debris into the pan.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102-6114.

FSC 7290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

The pan, consisting of a bottom with sides, back, and hood, shall be made from 0.0164 inch (0.42 mm) minimum thickness sheet steel. Seams shall be sealed to prevent dust leakage. The front edge of the pan shall be 10-1/2 to 12-1/2 inches (25.9 to 31.8 cm) wide. The side edges shall be a minimum of 7-1/2 inches (19.1 cm) long. The clearance from hood top to pan bottom shall be a minimum of 2-1/2 inches (6.4 cm). The pan shall have a durable protective finish to prevent corrosion.

The handle shall be a minimum of 26 inches (66.1 cm) long, shall be made from durable, rigid material. The handle shall be securely fastened to the pan and shall not disengage from the pan during normal use. The handle shall have a durable protective finish.

3.2 Labeling. The dustpans shall be labeled in a plain and permanent manner with the manufacturer's name or trade mark of such known character that the source of manufacture may be readily identified.

3.3 Workmanship. The finished dustpan shall function smoothly and efficiently for the purpose intended and shall be free from chipped finish, sharp edges, splits, dents, corrosion, or any other defect affecting appearance or serviceability.

3.4 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parenthesis are for information purposes only.

3.5 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

4. REGULATORY REQUIREMENTS.

4.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6. PACKAGING.

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or purchase order.

7. NOTES.

7.1 Part Identification Number (PIN). Dustpans conforming with this commercial item description shall be identified by a part number configuration consisting of identification of a portion of the CID number and type. An example of a part number configuration is shown below. This part numbering system is intended for identification and cross-indexing of the item within the federal cataloging system. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

EXAMPLE: AA300-1 = a rubber/plastic dustpan with a short handle

AA3001
- ||
- ||_____ *Type* (1 = I = *rubber/plastic*
- | 2 = II = steel
- | 3 = III = steel; with a swinging pan)
- |
- |_____ Commercial item description number

7.2 Ordering data. Purchaser should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a) Title, number, and date of this commercial item description.
b) Type required.
c) The preservation, packing, *and marking desired.*

7.3 National stock numbers (NSNs). The following NSNs correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

National Stock Number	Type	PIN
7290-00-616-0109	I	AA3001
7290-00-224-8308	II	AA3002
7290-00-634-1996	III	AA3003

7.4 Supersession data. *The Type III dustpan was previously covered by CID A-A-299.*

MILITARY INTERESTS:

Military Coordinating Activity:

Custodian:
Air Force - 99

Review Activity:
Air Force - 84

Civil Agencies Coordinating Activities:
VA-OSS

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.