COMMERCIAL ITEM DESCRIPTION

GLASS CLEANER (LIQUID AND AEROSOL)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification P-G-406.

This commercial item description covers liquid glass cleaner for cleaning and polishing of glass surfaces, plastics, ceramics, chrome, painted surfaces, and stainless steel.

The glass cleaner shall be of the following types and classes:

Type I - Regular
Class 1 - Ready-to-use liquid
Class 2 - Concentrated liquid
Class 3 - Aerosol

Type II - Antifogging
Class 1 - Ready-to-use liquid
Class 2 - Concentrated liquid
Class 3 - Aerosol

Salient characteristics:

The glass cleaners shall not be flammable. When used as directed on the label, the glass cleaners shall not be toxic as defined in the Federal Hazardous Substances Act Regulations (16 CFR 1500.3 (b)(5)).

Class 3 glass cleaners shall be provided in aerosol dispensers.

Flash point. The flash point of the glass cleaners shall be not less than 120° F (48.8° C) when tested as specified in ASTM D 56.

pH. The pH of a 1 percent solution of the ready to use glass cleaner in distilled water shall be not less than 6.5 nor more than 11.0 when tested as specified in ASTM E 70. The pH of a 1 percent solution of the use-dilution of the concentrated glass cleaners shall be not less than 6.5 nor more than 11.0.

Cleaning performance. When tested by GSA Test Method DDC-09 for Glass Cleaners, the glass cleaner shall be equal or better in performance than the reference glass cleaner in cleaning, streaking and smearing.

Reference glass cleaner

Ingredient	Weight percent
Isopropanol	4.0
Dipropylene glycol monomethyl ether	4.0
Ammonium hydroxide (28 % in water)	1.0
Pluronic F 108	0.1
Distilled water	90.9

The issues of the referenced test methods in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Antifogging performance. Type II glass cleaner shall prevent steam condensation as a glass mirror when tested as follows: Take a glass mirror at least 6" by 12" and clean it with cheesecloth in solvent baths in the order listed (a) mineral spirits (naphta, V. M. & P.), (b) dipropylene glycol monomethyl ether, (c) isopropanol, and (d) water. After the water rinse, dry the glass mirror with cheesecloth. To insure complete cleanliness of the mirror, expose it to live steam. A white highly reflective appearance is taken on by the glass in those areas not thoroughly clean. (Insuch cases, the glass mirror should be exposed to the entire solvent cleaning procedure again). Drape one-half of the mirror with a towel and apply the glass cleaner to the other half of the mirror. Wipe until the surface is just damp and then let dry. Hold the mirror 4 inches above the steam source and move the mirror back and forth in order to get an even distribution of the steam. The side treated with the glass cleaner shall show no steam condensation when compared to the untreated side.

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:04Z
Check the source to verify that this is the current version before use.

The containers of glass cleaner shall be labeled in accordance with the Federal Hazardous Substances Act Regulations (16 CFR 1500).

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging, packing, and marking. The packaging and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

Note: Purchasers should state in the contract the type, class and size containers of glass cleaner required.

CSMA methods are available from the Chemical Specialties Manufacturers Association, Incorporated, 1001 Connecticut Avenue, N.W., Washington, DC 20036.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Code of Federal Regulations (CFR), are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:04Z
Check the source to verify that this is the currentversion before use.