A-A-50466A
May 12, 1989
SUPERSEDING
A-A-50466
January 24, 1983

COMMERCIAL ITEM DESCRIPTION

OVEN, MICROWAVE, ELECTRIC
(1800 - 2199 WATT MICROWAVE POWER OUTPUT)

The General Services Administration has authorized the use of this Commercial Item Description (CID) in preference to type II, size 2000; groups 3, 4, and 5; styles 1, 2, 3 and 4; classes 2 and 3 of Federal Specification S-O-1425.

Abstract. This CID covers 1800-2199 watt (W) commercially rated and approved microwave oven intended for use as a means of preparing and reconstituting food. Household and shipboard use microwave ovens are specifically excluded.

Salient characteristics:

1. Description. The microwave oven shall include all components necessary to ensure a fully functional product. All hardware and fittings shall be corrosion-resistant or suitably processed to resist corrosion in accordance with the manufacturer's standard practice. The microwave energy source(s) shall be rendered inoperative when the oven door is opened. Means shall be provided for protection of the microwave energy source(s) from damage caused by excessive reflected microwave radiation from the cooking cavity under small or no load conditions. The power supply shall be protected against overload conditions by fuses or resettable circuit breakers. A forced air circulation system shall be provided which will exhaust water vapor and cooking vapors from the cooking cavity. The ovens shall be furnished with an air intake filter which shall be removable and readily accessible for cleaning or replacement. The oven shall be designed to permit easy accessibility for maintenance and service.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent by letter to: Commanding Officer, Naval Construction Battalion Center, Code 156, Port Hueneme, CA 90046

FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

2. Cooking power. The oven shall deliver a minimum of 1800W cooking power.

3. Cooking cavity. The cooking cavity shall be constructed in a rectangular shape and have a capacity of not less than 0.9 cubic feet (cu ft). Ovens with viewing screens shall have the cooking cavity illuminated. The light shall automatically activate when the door is opened. It shall also remain lighted while a cooking cycle is in progress.

4. Electrical characteristics. The microwave oven shall be designed for operation on 208/240 Volts (V) alternating current (AC), or 120 V AC, 60 Hertz (Hz), single phase power. The maximum amperage shall not exceed 20A. The maximum power input shall not exceed 5500W. The power cord shall be not less than a minimum of 2 feet and not more than a maximum of 6 feet long external of unit equipped with either a 3 wire or 4 wire grounding type plug. All electric motors shall have permanently sealed bearings which require no additional lubrication for the life of the motor. A bleeder resistor or other suitable power dissipating device shall be provided to bleed the charge from the magnetron power supply capacitor when the oven is turned off. The voltage across the capacitor shall be less than 50V within 30 seconds after the power supply is turned off.

5. Controls. All controls shall be located in the front of the oven except the main power disconnect which may be located on the side but be readily accessible from the front of the oven. When desired, the following options shall be provided:

    a. A heat control function which varies the power level output in the cooking cavity.
    b. A defrost function.

    Oven timer shall provide minimum control functions of ON, OFF, timed cooking cycles, and automatic termination of the oven operation after the completion of timing cycle. An audible signal shall sound at the end of the timing cycle or at the end of a cooking cycle. The oven shall have provisions for operation on half power. The microwave energy source shall be inoperative when the door is opened. The timer shall be either a dial, pushbutton, combination dial and pushbutton or digital touchpad control type. Single dial type timers shall have a minimum time setting of not more than 15 seconds, and the maximum time setting shall be not less than 5 minutes. When two dial type timers are provided, one timer shall have a maximum time setting not less than 30 minutes. Pushbutton or touchpad digital timers shall have not less than six different time selection buttons. Means of adjusting the time interval of each selection button or digital touchpad shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

provided. Each button or digital touchpad shall be capable of being adjusted to not more than 6 seconds for the minimum time setting and not less than 120 seconds for the maximum time setting. Combination dial and pushbutton timers shall conform to the previously mentioned requirements for each except that the pushbutton portion shall consist of not less than five different time selection buttons. The digital touchpad timer shall utilize electronic solid-state components which process user information, entered by means of data entries, to control the starting, stopping, timing and heat control function of the oven. A lighted digital read-out panel shall display data entries, and countdown time remaining to the end of the cooking cycle.

6. Weight and dimensions. The weight of the microwave oven shall not exceed 220 pounds and extenal oven dimensions shall not exceed the following:

    32 inches wide
    28 inches high
    28 inches deep

7. Standards compliance. The microwave oven shall conform to the applicable requirements of UL 923, title 21 CFR subchapter J part 1030, NFPA No. 70 and NSF No. 4.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this CID, and that the product conforms to the producer's own drawings, specifications, standards, quality assurance practices, and is the same as the product offered for sale in the commercial market place. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this CID are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-50 to the maximum extent practical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified in the contract or purchase order, the packaging and packing shall be in accordance with the contractor's standard commercial practice and shall assure acceptance by common carrier and provide product protection against deterioration, loss and damage during shipment.

Notes.

Acquisition activity should specify watts output, electrical requirement, 3 wire or 4 wire grouding type plug and any desired control options.

Code of Federal Regulations (CFR) are available from the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

UL Standards are available from the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

NFPA Standards are available from the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

NSF Standards are available from the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, Michigan 48106.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activity

Air Force - 84

User Activity

Navy - MS

CIVIL AGENCY COORDINATING ACTIVITY

GSA-FSS

VA-OSS

BOP

PREPARING ACTIVITY:

Navy - YD

Project 710-0759

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.