A-A-51128A
June 8, 1990
SUPERSEDING
A-A-51128
July 2, 1984

COMMERCIAL ITEM DESCRIPTION

TORCH KIT, SOLDERING (PROPANE GAS)

The General Services Administration has authorized the use of this commercial item description.

Abstract. This description covers a soldering torch kit designed to burn propane gas to produce a flame suitable for soldering and heating.

Salient Characteristics. The torch kit shall meet the following minimum requirements.

1. Design. The torch kit shall be new and of the manufacturer's commercial design in effect on the date of the solicitation. The torch kit shall conform to UL 147. The label or listing of the Underwriters Laboratories, Inc. may be accepted as evidence that the kits conform to this requirement.

2. Components. The soldering kit shall consist of a disposable fuel cylinder (fully loaded), burner unit, pencil burner head, utility burner head (heavy duty), soldering tip, flame spreader, flint lighter, and carrying case.

3. Cylinder. The propane fuel cylinder shall be a nonreusable, non-refillable pressurized gas cylinder having a nominal capacity of 14.1 ounces. The neck of the cylinder shall be one inch in diameter threaded with 20 UNEF threads per inch for connecting the burner unit to the cylinder.

4. Burner unit. The burner unit shall consist of a control valve assembly with a metal to metal seal and a length of brass, brass plated steel, copper, or copper alloy tubing not less than 3 inches in length. The burner end of the tubing shall be externally threaded for attaching the burner heads. The supply end of the burner unit shall be internally threaded for connection to the cylinder. The burner unit shall be configured such that a suitable gas seal will be created between the burner and the cylinder before gas pressure is released from the cylinder.

Beneficial comments recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, 2163 Airways Blvd., Memphis TN 38114-5051.

AMSC N/A FSC 3439

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

5. Pencil burner head. The pencil burner head shall be of brass or copper and shall contain a replaceable orifice which will produce a pencil flame. The lower end of the pencil burner head shall be internally threaded for connection to the burner unit.

6. Utility burner head. The utility burner head shall be similar to the pencil burner head except that the head shall be provided with a larger orifice to produce a flame suitable for work requiring a greater volume of heat. The lower end of the utility burner head shall be internally threaded for connecting to the end of the burner unit.

7. Soldering Tip. The soldering tip shall have a housing of brass, copper, or brass plated steel with a copper tip. Means shall be provided for securing the soldering tip to the pencil burner head.

8. Flame spreader. The flame spreader shall be fan shaped to produce a wide flame to cover a wide area. Means shall be provided for securing the flame spreader to the utility burner head.

9. Flint lighter. The flint lighter shall contain a replaceable flint and shall be not less than six inches in length when measured from the center of the flint to the opposite end of the lighter.

10. Carrying case. The carrying case shall be made of either metal or plastic and shall be of sufficient size to hold all components contained in the set.

11. Threads. All threaded parts used on any component of the kit shall conform to FED-STD-H28.

12. Performance. The torch shall be capable of operating satisfactorily on the fuel for which it is designed. Burning shall be steady and without pulsation in any position. The burner heads, soldering tip, and flame spreader shall operate satisfactorily with the torch.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Source: https://assist.dla.mil Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Environmental protection. During the manufacture of the torch set, materials hazardous to the ecological system as prohibited by the Federal, state, or local statutes in effect on the date of the contract shall not be used or emitted.

Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with ASTM D 3951 or MIL-W-45562 as specified (see ordering data).

Quality assurance.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection, examination, and test requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections, examinations, or tests set forth in this description where such inspections, examinations, and tests are deemed necessary to assure supplies and services conform to prescribed requirements.

Responsibility for compliance. All items shall meet the requirements specified herein. The inspection set forth in this description shall become a part of the contractors overall inspection system or quality program. The absence of any inspection requirements in the description shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Sampling inspection. As a minimum sampling inspection, the supplier shall randomly select the number of samples in table I that is applicable to the lot size. Each sample item shall be inspected to determine conformance with the examination and test. Should any of the sample items fail to meet either the examination or test, the entire lot shall be considered defective and unsuitable for acceptance. A lot is defined as all items presented at one time for acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE I. Sampling plan.

Lot size	Sample size	Lot size	Sample size
2 to 8	2	151 to 280	32
9 to 15	3	281 to 500	50
16 to 25	5	501 to 1,200	80
26 to 50	8	1201 to 3,200	125
51 to 90	13	3201 to 10,000	200
91 to 150	20		

Examination. Each torch kit submitted for sample inspection shall be visually examined to determine conformance with all requirements of this description.

Performance test. Each torch kit submitted for sample inspection shall be tested to determine conformance with paragraph 12 of the salient characteristics.

NOTES

Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Quantity required.

c. Specify preservation, packaging, packing, and marking requirements, if in accordance with MIL-W-45562, specify level.

Federal Standard FED-STD-H28 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

Federal Standard FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

Military Specification MIL-W-45562 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

ASTM D 3851 is available from American Society for Testing and Materials, 1916 Race street, Philadelphia, PA 19103-1187.

UL 147 is available from The Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062-2096.

Source: https://assist.dla.mil Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodian

Army - AL
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3439-0746

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A-51128A	2. DOCUMENT DATE (YYMMDD) 90 06 08

3. DOCUMENT TITLE
TORCH KIT, SOLDERING (PROPANE GAS)

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
JAMES D. THREADGILL, DIPEC-SSG	(901)775-4749	AV 683-4749
c. ADDRESS (Include Zip Code) Defense Industrial Plant Equip. Center 2163 Airways Blvd, Memphis, TN 38114-5051	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.