[INCH-POUND]

A-A-2669
May 19, 1990

COMMERCIAL ITEM DESCRIPTION

BOX, FILING, PLASTIC

The General Services Administration has authorized the use of this Commercial Item Description in lieu of Federal Specifications L-B-565 and LLL-B-650.

This CID covers file boxes intended to be used for the maintenance of index cards or forms printed on card stock.

CLASSIFICATION:

Boxes shall be of the following sizes (See Section 6):

SIZE	
A.	For 3 x 5 inch index cards
B.	For 4 x 6 inch index cards
C.	For 5 x 8 inch index cards

Box color shall be chosen from the following commercially defined and commercially acceptable color list (See Section 6):

COLOR	
1.	Black
2.	Slate Blue
3.	Putty
4.	Beige
5.	Grey

1. SALIENT CHARACTERISTICS:

A. Boxes shall be fabricated of polypropylene plastic.

B. Boxes shall be nonflammable, flame resistant or slow burning when tested against UL Standard 94 HB. Certification of compliance shall be maintained by the contractor and shall be supplied to the Government, upon request.

C. Boxes shall be designed to contain standard, commercial index cards without causing damage to the cards and readily permitting card removal and replacement.

DISTRIBUTION STATEMENT A:
Approved for public release;
distribution is unlimited.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

D. Boxes shall have a hinged lid which, in the closed position, shall sit evenly and squarely on a ledge formed at the upper edge of the base. The lid shall remain securely closed until manually opened.

E. The lid and hinge shall be integral with the base section. The lid shall be hinged to the base at the back of the box. Hinge length shall be not less than the following:

SIZE	HINGE LENGTH
A.	4.00"
B.	4.75"
C.	6.75"

F. The lid, when opened, shall remain in an open position, without additional support, at an angle of at least 90 degrees from a closed position.

G. The hinge shall pass Performance Test #3, Hinge Durability (See Section 4).

H. The interior of the box shall have a smooth finish and the bottom of the interior shall have 6-12 lengthwise projection ridges not less than 0.03 inch high. The projection ridges shall be spaced so as to aid in retaining the cards in position and shall prevent them from sliding along the bottom and slipping down in the boxes.

I. The exterior top, sides and bottom surfaces shall have a commercially acceptable finish.

J. Wall thickness shall be no less than the following:

SIZE	MINIMUM WALL THICKNESS
A.	0.065"
B.	0.075"
C.	0.090"

K. The exterior bottom of the boxes shall have no sharp edges or projections which might scratch or mar a surface on which the box rests.

L. Each box shall be permanently and legibly marked with the name or trademark of the manufacturer (See Section 6).

M. Workmanship: The entire filing box shall be free of defects including, but not limited to burrs, niches, dents, rough or sharp edges, scratches, blisters, crinkling, bubbles, imbedded foreign matter, discoloration or imperfections which will impair serviceability and adversely affect the appearance or which might constitute a personal hazard to the user.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS AND DOCUMENT SOURCES: The following documents form a part of this CID to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply:

Federal Standard:

Fed. Std. No. 123, Marking for Domestic Shipment (Civil Agencies) (Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, Handbooks, and CIDs, as outlined under General Information in the Index of Federal Specifications, Standards and CIDs. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.)

(Single copies of this CID, other CIDs required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston; New York; Philadelphia; Washington, D.C.; Atlanta; Chicago; Kansas City, MO; Fort Worth; Houston: Denver; Los Angeles; San Francisco; and Auburn, WA.)

Military Standards:

MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129, Marking for Shipment and Storage

(Copies for Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the U.S. Navy; Naval Publications and Forms Center; 5801 Tabor Avenue; Philadelphia, PA 19120; or as directed by the contracting officer.)

Public Law:

Public Law 94-580, Resource Conservation and Recovery Act, is part of U. S. Code, Title 42. (Copies of the U. S. Code may be obtained through the Congressional Sales Office, U. S. Government Printing Office, Washington, D. C. 20402).

Industry Standards:

UL Standard No. 94, Tests for Flammability of Plastic Materials for Parts in Devices and Appliances

(Copies are available from Underwriters Laboratories, Inc.; Attn: Publication Stock; 333 Pfingsten Road; Northbrook, IL 60062.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

ASTM D671, Standard Test Method for Flexural Fatigue of Plastics by Constant-Amplitude-of-Force

(Copies are available from The American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

3. RECOVERED MATERIALS: The manufacturer shall utilize recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

4. QUALITY ASSURANCE:

Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the CID, where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Sampling. Samples shall be taken in accordance with MIL-STD-105. Unless otherwise specified, a random sample of boxes shall be taken from each lot, and the sample unit shall be defined as one box.

Sampling.

A. For Visual and Dimensional Inspection. Inspection level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 percent defective.

B. For Tests. Inspection level shall be S-1 with an AQL of 4.0 percent defective.

C. For Preparation for Delivery. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. The inspection level shall be S-2 with an AQL of 4.0 percent defective.

Inspections.

A. Visual and Dimensional Examination. Samples taken in accordance with paragraph "A" under "Sampling" shall be examined to assure the compliance of all visual, dimensional, and workmanship characteristics listed in Section 1.

B. Performance Tests. Samples taken in accordance with paragraph "B" under "Sampling" shall be subjected to the following tests to demonstrate consistency in product functionality, durability, and performance expectations:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

(1) Card Handling
Fill the sample boxes with no less than 200 corresponding, appropriately sized index cards (See Classification). Close lid securely and leave for 24 hours. After 24-hours, remove 20 individual cards from various locations throughout the box, then file them back in similar locations within the same box. Cards shall be filed and removed with ease. Upon completion, check cards for any noticeable damage including, but not limited to, bent or mutilated corners or edges (See Section 1C). Remove all cards and use the same boxes for Test 2.

(2) Lid Operation
The lid shall be fully opened, and fully closed, fifty (50) times. Measure angle of open lid at the beginning of test, then again at the end (for a total of two times). Verify compliance with Section 1D and 1F.

(3) Hinge Durability
This test shall be performed on the first production lot of each contract and after any change in the hinge design or material being used. The specimen shall be cut and prepared in accordance with ASTM D671. Each specimen shall be cut in such a manner as to make the hinge area the point of flex. Only one specimen shall be taken from each sample box. In accordance with ASTM D671, perform 6,500 cycles on each specimen. The hinge area of the specimen shall be examined visually for evidence of cracks or separation (See Section 1G).

C. Examination for Preparation for Delivery. Samples taken in accordance with Section 4C under "Sampling" shall be examined to determine compliance with Section 5.

5. PREPARATION FOR DELIVERY:

A. Packaging/Packing Provisions. Boxes shall be packaged/packed in accordance with standard commercial practice. All packages/packs shall be secured to prevent accidental opening during shipment, handling, storage and redistribution. The box shall be such as to ensure carrier acceptance and safe delivery to the destination, complying with the rules and regulations applicable to the mode of transportation to be used.

B. Marking.

(1) For Delivery to Civil Agencies. In addition to any special marking required by contract or order, marking shall be in accordance with Fed. Std. No. 123. Bar code marking is required, unless otherwise specified (See Section 6).

(2) For Delivery to Military Activities. In addition to any special marking required by contact or order, marking shall be in accordance with MIL-STD-129. Bar code marking is required, unless otherwise specified (See Section 6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

6. NOTES:

A. Certification Statement: The Commercial Item Certification Clause is not required when this Commercial Item Description is used for procurement.

B. Ordering Data: Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(1) Title, number, and date of this Commercial Item Description.
(2) Purchasers should specify desired size (See Classification).
(3) Purchasers should specify desired color (See Classification).
(4) Purchasers should specify only if name or trademark of the manufacturer is not required (See Section 1L).
(5) Purchasers should specify arrangement for inspections and inspection facilities, if different than provisions under Section 4, Quality Assurance.
(6) Purchasers should specify special packaging and packing, if different than provisions in Section 5, Packaging and Packing Provisions.
(7) Purchasers should specify special marking, if different than provisions in Section 5, Marking.
(8) Specify, only if bar code marking is not required (See Section 5, Marking).

C. Reference Part Numbering System (For cataloging use only):

Part Numbering System: The below example describes a black plastic file box for 3 x 5 inch index cards in accordance with CID A-A-2669:

AA2669 - A1

Colors:
1. Black
2. Slate Blue
3. Putty
4. Beige
5. Grey

Size:
A. For 3 x 5 inch index cards
B. For 4 x 6 inch index cards
C. For 5 x 8 inch index cards

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.